
Orbix Deployment Guide

6.3.14

Table of Contents

Preface	6
Audience	6
Related documentation	6
Typographical conventions	7
Keying conventions	7
Getting Started	9
Introduction	9
Configuration and deployment process	9
Orbix Configuration tool (itconfigure)	10
Orbix deployment descriptor	11
Orbix deployer and component XML files	11
Deployed configuration models	11
Implementation Repository	12
Orbix Configuration Tool	12
Configuration setup tasks	12
Runtime management tasks	13
	13
Running the Orbix Configuration Tool	14
Requirements	15
Command syntax	15
Orbix Configuration screen	20
Licensing your Orbix Environment	21
Specifying a license file	22
Configuring and Deploying a Domain	24
Introduction	24
Centralized domain design	24
Creating a New Domain	25
Deploying a Distributed Domain	32
Connecting a Client Machine to a Domain	34

Localizing a Preconfigured Domain	36
Replicating Services in a Domain	37
Updating an Existing Domain	38
Opening a domain	38
Reopening a domain	41
Adding a service	41
Adding a replica service	42
Removing a replica service	44
Repreparing a service	44
Starting and Stopping Orbix Services	45
Setting Java ORB Classes	46
Advanced Configuration and Deployment	48
Creating a Domain in Expert Mode	48
Procedure	48
Configuring a Machine with no GUI	54
Creating the deployment descriptor	55
Deploying on the command line	56
Localizing the domain	56
Changing the domain name	56
Deploying on Multi-homed Machines	57
Multi-homed deployment process	57
Deploying on the command line	58
Deploying with the GUI	58
Modifying hostnames without the -multihome option	59
Configuring your Orbix applications for multi-homed hosts	60
Configuring Orbix in a Cluster	60
Configure a multi-homed Orbix host	61
Configure your Orbix applications as multi-homed	61
Write shell scripts for Orbix services and applications	61

Register your shell scripts	62
Configuring Services to Listen on Network Interfaces	62
Specifying address lists using the Expert wizard	62
Example	62
Specifying address lists on the command line	63
Specifying Custom Locations for Domain Files	63
Configuration domain files	64
Command-line options for custom locations	64
Setting all locations on the command line	65
Partially setting custom locations	66
Redeploying an existing domain	67
Specifying Custom Library Paths	67
Using the command line	67
Using the configuration tool	68
Using Custom XML Files	69
Passing custom XML to itconfigure	69
Deploying custom XML with the GUI	70
Custom XML example	71
Rules for writing XML files	73
Specifying Address Mode Policies	73
Selecting an address mode	74
Specifying a fully-qualified hostname	74
Persistence of address mode policies	75
Restrictions and special cases	75
Node daemon address mode policies	76
Leaving the node daemon name unset	77
Assigning a node daemon name other than the hostname	77
Specifying Custom Certificates	79
Substitution variable file	79
Using the GUI	80

Using the command line	80
Orbix Deployment Descriptors	81
Deployment Descriptor Structure	81
Document structure	81
Recommended deployment descriptor generation	83
Validating manual changes to a deployment descriptor	83
Domain Configuration Elements	84
Example descriptor	84
Domain elements	85
Profile Configuration Elements	88
Example descriptor	88
Service elements	90
Service and component XML Files	94
Orbix Deployment DTD	95
Orbix Component Template Structure	95
ABDeploy.dtd	95
Summary	98
Glossary	99
Notices	104
Copyright	104
Trademarks	104
Examples	104
License agreement	104
Corporate information	105
Contacting Technical Support	105
Country and Toll-free telephone number	105

Preface

Orbix enables you to develop and deploy enterprise-level applications across different platform and programming language environments. This guide explains how to setup an Orbix environment, and examines the Orbix configuration and deployment process in detail.

Note

The scope of this guide is limited to the configuration and deployment features that are supported by Rocket Software. Unsupported configuration and deployment features are not documented. These are proprietary features and are subject to change without notice.

Audience

This guide is aimed at system administrators who are setting up Orbix environments.

It is also aimed at programmers who are developing and deploying Orbix applications. It contains advanced information about customizing Orbix configuration and deployment. This guide should be read in conjunction with the *Orbix Administrator's Guide*.

Related documentation

The document set for Orbix includes the following related documentation:

- *Orbix Administrator's Guide*
- *Orbix Configuration Reference*
- *Orbix Management User's Guide*

Typographical conventions

This guide uses the following typographical conventions:

Constant width	<p>Constant width (courier font) in normal text represents portions of code and literal names of items such as classes, functions, variables, or data structures. For example, text might refer to the <code>CORBA: :Object</code> class.</p> <p>Constant width paragraphs represent code examples or information a system displays on the screen. For example:</p> <pre>#include <stdio.h></pre>
<i>Italic</i>	<p>Italic words in normal text represent <i>emphasis</i> and <i>new terms</i>.</p> <p>Italic words or characters in code and commands represent variable values you must supply, such as arguments to commands or path names for your particular system. For example:</p> <pre>% cd /users/*your_name* !!! note</pre> <p>Some command examples may use angle brackets to represent variable values you must supply. This is an older convention that is replaced with <i>italic</i> words or characters.</p>

Keying conventions

This guide may use the following keying conventions:

No prompt	When a command's format is the same for multiple platforms, a prompt is not used.
%	A percent sign represents the UNIX command shell prompt for a command that does not require root privileges.
#	A number sign represents the UNIX command shell prompt for a command that requires root privileges.
>	The notation > represents the DOS or Windows command prompt.

...	Horizontal or vertical ellipses in format and syntax descriptions indicate that material has been eliminated to simplify a discussion.
[]	Brackets enclose optional items in format and syntax descriptions.
{ }	Braces enclose a list from which you must choose an item in format and syntax descriptions.
	A vertical bar separates items in a list of choices enclosed in { } (braces) in format and syntax descriptions.

Getting Started

This section introduces Orbix configuration and deployment. It also explains how to run the Orbix configuration tool and how to license your Orbix installation.

Introduction


This section introduces Orbix configuration and deployment. It includes the following topics:

- [Configuration and deployment process](#)
- [Orbix Configuration tool \(itconfigure\)](#)
- [Orbix deployment descriptor](#)
- [Orbix deployer and component XML files](#)
- [Deployed configuration models](#)
- [Implementation Repository](#)

Configuration and deployment process

Figure 1 shows a general overview of the Orbix configuration and deployment process.

Figure 1 Overview of Orbix Configuration and Deployment



[Figure 1](#) can be described as follows:

1. The Orbix configuration tool (`itconfigure` command) is used to generate the domain deployment descriptor (`domain-name_dd.xml`).
2. The deployer parses the deployment descriptor, taking input from XML templates for the various Orbix components and services.
3. The deployer deploys the configuration domain into a configuration domain file or the Configuration Repository (CFR), and also into the Implementation Repository (IMR).

The components in [Figure 1](#) are described in more detail in the topics that follow.

Orbix Configuration tool (itconfigure)

The Orbix configuration tool (`itconfigure` command) guides you through configuring Orbix components in your environment. You can use it to perform tasks such as installing a license, creating a configuration domain, or linking to an existing configuration domain.

You can run the Orbix configuration tool in GUI and command-line modes. You should create a domain deployment descriptor by using this tool in GUI mode (shown in [Figure 1](#)).

GUI mode

The GUI creates a domain deployment descriptor file (`domain-name_dd.xml`). You can create the configuration domain specified by this deployment descriptor using the GUI. Alternatively, you can save the descriptor and create your domain later. GUI mode imposes constraints and performs validity checking (for example, on the combinations of Orbix services that are permitted).

Command-line mode

You can also create a configuration domain in command-line mode by passing a previously created deployment descriptor to the `itconfigure` command.

For detailed information on how to use the Orbix configuration tool, see [Configuring and Deploying a Domain](#).

Orbix deployment descriptor

The domain deployment descriptor (`domain-name_dd.xml`) describes the contents of a configuration domain. For example, for a domain named `sample-domain`, a deployment descriptor named `sample-domain_dd.xml` specifies the services, components, features and hosts that are included in that domain. By default, the deployment descriptor file is stored in your `etc\domains` directory, for example:

```
<install-dir>\etc\domains\sample-domain\sample-domain_dd.xml
```

The Orbix configuration GUI generates the deployment descriptor, which it then uses to automatically deploy the specified configuration into your environment (as shown in [Figure 1](#)).

Alternatively, you can also save the deployment descriptor before it is deployed by the GUI, and then perform a command-line deployment at a later stage. This is particularly useful if you want to customize your configuration by editing your deployment descriptor, or use multiple deployments with the same configuration.

For full details of how to perform a command-line deployment, see [Configuring a Machine with no GUI](#). For details on the contents of the deployment descriptor file, see [Orbix Deployment Descriptors](#).

Orbix deployer and component XML files

The deployer parses the deployment descriptor produced by the Orbix configuration GUI. It also takes input from the XML templates for the various Orbix components and services (for example, `event_log.xml`). By default, these XML templates are stored in the following directory:

```
install-dir \asp\ version \etc\conf
```

These template files all conform to a standard XML format as specified by the `ABDeploy.dtd` file. For details of this DTD file, see [Orbix Deployment DTD](#).

You can also specify custom XML files to the deployer. For details, see [Using Custom XML Files](#).

Deployed configuration models

Depending on which option you chose in the configuration GUI, the deployer gathers your configuration information into either a configuration file or a Configuration Repository (CFR), and creates scripts to start and stop the domain services.

The Interoperable Object References (IORs) that the deployer obtains by preparing the domain services are an essential part of this configuration domain data. If these are stored in a file, and clients need access to these IORs, you need to make sure that this file can be accessed by all clients (using NFS or similar network services). If you are dealing with a larger number of clients, or expect to modify configuration data, using a Configuration Repository might be your preferred choice.

A Configuration Repository is a centralized database for all configuration information. This centralized configuration model is suitable for environments with a potentially large number of clients and servers, or when configuration is likely to change.

Implementation Repository

The deployer also stores server process information in the Implementation Repository (IMR). This specifies whether the process can be started up on demand by a node daemon, and includes details such as POA names, and ORB names.

For more details on Orbix configuration models and the IMR, see the *Orbix Administrator's Guide*.

Orbix Configuration Tool

The Orbix Configuration tool guides you through licensing and configuring the components in your Orbix environment. You can also use this tool to manage your environment at runtime. This section includes the following:

- [Configuration setup tasks](#)
- [Runtime management tasks](#)
- [Example screen](#)

Configuration setup tasks

You can use the Orbix Configuration tool to perform basic setup tasks such as the following:

- Install or update your license.
- Create a configuration domain.
- Deploy services into a configuration domain.
- Link to existing configuration domains.
- Create server replicas for clustering.
- Add services to existing configuration domains.

The Orbix configuration tool analyzes your installation and provides you with the options available for your system.

Runtime management tasks

In addition, when you have set up your environment, you can use this tool to perform runtime tasks such as the following:

- Start and stop your Orbix services.
- Open a command prompt configured for your domain.
- Launch the Administrator Web Console.
- Launch other configuration tools (for example, Orbix Configuration Explorer).
- Open other GUI tools for specific Orbix services (for example, Orbix Notification Service Console).

For information on using runtime tools such as the Administrator Web Console and the Orbix Configuration Explorer, see the *Orbix Management User's Guide*.

Note


The Orbix Configuration Explorer and Administrator Web Console are no longer automatically installed. They are available as an optional component. To install, please download and extract the GUI components archive and follow the installation instructions.

The GUI components archive can be downloaded from our Software License & Download (SLD) site,.

The GUI components have been separated from the product as they do not fully comply with the Section 508 and WCAG accessibility requirements and guidelines. It is intended that future product releases will include updated GUI components that comply with the relevant accessibility guidelines.

[Figure 2](#) shows a newly created configuration domain named `my-domain`. The left pane displays details such as the domain and machine name, and all the services that have been configured. The right pane displays summary information about the domain. While the toolbar across the top displays buttons for licensing and various runtime options, such as starting services, and launching other tools.

Figure 2 Orbix Configuration GUI



Running the Orbix Configuration Tool

This section explains the full syntax of the `itconfigure` command, which is used to run the Orbix Configuration tool. It includes the following:

- [Requirements](#)
- [Command syntax](#)
- [Orbix Configuration screen](#)

Requirements

Before you run the configuration tool, check the following system requirements:

- Set `JAVA_HOME` so it points to your current Java installation.
- Set UNIX access permissions to account for the following contingencies:
- The configuration tool must have write access to directories `/var/opt/iona` and `/etc/opt/iona`. These directories are usually restricted to accounts with `superuser` privileges.
- The configuration tool prompts you to designate a user to run domain services, and sets ownership of files and directories accordingly.
- Set the `IT_PRODUCT_DIR` environment variable to point to the latest Orbix installation on your system.

Command syntax

To run the configuration tool, use this command syntax:

```

itconfigure
[-ORBproduct_dir install_dir]
[-ORBlicense_file license_file]
[-nogui]
[-gui]
[-load, -l domain_descriptor]
[-deployed_descriptor, -d file]
[-compatible]
[-entities file]
[-save, -s file]
[-localize]
[-from host]
[-name domain_name]
        [-file, -f]
        [-cfr, -c]
        [-link, -i hostname]
        [-expert, -e]
[-host, -h hostname]
[-multihome hostname]
        [-corbalocs {true|false}]
[-etc config_dir]
[-var var_dir]
[-range, -r base_port]
[-port iiop_port]
[-tlsport tls_port]
[-ndport iiop_port]
[-ndtlsport tls_port]
[-credentials credentials]
[-hostnamePolicy policy]
[-libs, -L path]
[-substitutions file]
        [-prefer_ipv6 {true|false}]
[-prefer_ipv4 {true|false}]
[-listen_address_list list]
[-remove replica]
[-reprepare service]
[-service service]
[-instance service]
[-alt_master replica]
[-jvm64]
[-help, -?]
[-demos]

```

The configuration tool options are described as follows:

<code>-ORBproduct_dir *install_dir*</code>	Specifies your installation directory when Orbix is installed in a non-default location and the <code>IT_PRODUCT_DIR</code> environment variable is not set.
<code>- ORBlicense_file *license_file*</code>	Specifies your license directory when the Orbix license file is not stored in the default location and the <code>IT_LICENSE_FILE</code> environment variable is not set. For more details, see Licensing your Orbix Environment .
<code>-nogui</code>	Runs the configuration tool silently. This option can be used with <code>-load</code> , <code>-link</code> , and <code>-save</code> . For example, see Replicating Services in a Domain .
<code>-gui</code>	Runs the configuration tool GUI. This is the default.
<code>-load, -l *domain_descriptor*</code>	Loads a preconfigured domain descriptor file. When used in conjunction with <code>-nogui</code> , silently deploys the local parts of the configuration defined in the deployment descriptor. For more details, see Deploying a Distributed Domain .
<code>- deployed_descriptor, -d *file*</code>	Specifies the deployment descriptor of an existing configuration domain. This enables you to add an additional service to an existing domain.
<code>-compatible</code>	For interoperability with previous versions, this loads the specified file with the <code>-load</code> option as an Orbix 5.x driver file. For more details, see Migrating from Orbix 5.1 Driver Files .
<code>-entities *filename*</code>	Uses the specified entities file when loading the driver file specified with the <code>-load</code> option. For more details, see Migrating from Orbix 5.1 Driver Files .
<code>-save, -s *filename*</code>	Saves a deployment descriptor in the specified file. When used with <code>-nogui</code> , this option will not deploy the saved configuration.
<code>-localize</code>	Replaces all deployment nodes in a descriptor with the local host. For more details, see Localizing a Preconfigured Domain .
<code>-from</code>	Specifies the deploy node to replace when localizing a multi-profile descriptor.

<code>-name</code> <code>*domain_name*</code>	Specifies the name of the domain. The specified name overrides the name in a loaded domain descriptor. For more details, see Changing the domain name
<code>-file, -f</code>	Creates a file based domain.
<code>-cfr, -c</code>	Creates a cfr-based domain.
<code>-link</code> <code>*cfr_host*</code>	Specifies the machine which hosts the domain's configuration repository.
<code>-expert, -e</code>	Go straight into Expert mode.
<code>-host, -h</code> <code>*hostname*</code>	Specifies the name of the domain's host machine. This setting overrides the setting in a loaded domain descriptor.
<code>-multihome</code> <code>*hostname*</code>	Denotes that the specified host is virtual on a multi-homed host. For more details, see Deploying on Multi-homed Machines .
<code>-corbalocs</code> <code>{true false}</code>	Use corbalocs instead of IORs where possible. In non-GUI mode this supersedes the settings in the loaded descriptor.
<code>-etc *etc_dir*</code>	Specifies the directory where configuration information is stored.
<code>-var *var_dir*</code>	Specifies the directory where database files are stored.
<code>-range</code> <code>*base_port*</code>	Specifies the base port number from which to begin allocating port numbers. This option is only used in conjunction with <code>-nogui</code> .
<code>-port</code> <code>*iiop_port*</code>	Overrides the default CFR IIOP port when used with <code>-link</code> .
<code>-tlspport</code> <code>*tls_port*</code>	Overrides the default CFR TLS port when used with <code>-link</code> .
<code>-ndport</code> <code>*iiop_port*</code>	Overrides the default node daemon IIOP port when used with <code>-link</code> .
<code>-ndtlspport</code> <code>*tls_port*</code>	Overrides the default node daemon TLS port when used with <code>-link</code> .
<code>-libs, -L</code> <code>*path*</code>	Prefixes the library path to the built-in path used when preparing and running Orbix services. For more details, see Specifying Custom Library Paths .


<code>-substitutions *file*</code>	Specifies substitution file in properties file syntax containing values for substitution variables. For more details, see Specifying Custom Certificates .
<code>-prefer_ipv6 {true false}</code>	Specifies deployment as IPv6 where possible.
<code>-prefer_ipv4 {true false}</code>	Specifies deployment as IPv4 where possible.
<code>- listen_address_ list *list*</code>	Listen on specified addresses
<code>-credentials</code>	Specifies credentials in the following format: "username=<name>, \ password_file=<file>, domain=<domain>"
<code>-hostnamePolicy *policy*</code>	<p>Specifies the address mode policy for IORS. Value can be one of the following:</p> <ul style="list-style-type: none"> - <code>ip</code> (IP addresses) - <code>localhost</code> ('localhost'), - <code>localhost_ip</code> ('127.0.0.1'), - <code>long</code> (fully qualified hostname), - <code>short</code> (unqualified hostname—the default). <p>For more details, see Specifying Address Mode Policies.</p>
<code>[-remove *replica*]</code>	Permanently removes a replica service from an existing domain (for example, a replica locator). For more details, see Updating an Existing Domain .
<code>[-reprepare *service*]</code>	Re-prepares an existing indirect persistent service after creating or removing a replica locator.
<code>[-service *service*]</code>	Adds a service to an existing domain.

<code>[-instance *service*]</code>	Adds a replica instance that was configured as the preferred master replica to an existing domain.
<code>[-alt_master *replica*]</code>	Adds a new preferred master. This is used when you remove a replica service from an existing domain.
<code>[-jvm64]</code>	Enables support for a 64-bit version of Java by running the JVM with the '- d64 ' switch. If the Orbix installation contains 64-bit versions of the services, this will deploy using the 64-bit services.
<code>-help, -?</code>	Displays an explanation of the command flags.
<code>-demos</code>	Specifies the configuration needed to run the Orbix demos in the domain.

Orbix Configuration screen

When the Orbix configuration tool runs for the first time, it displays a screen similar to that shown in [Figure 3](#):

Figure 3 Main Configuration Window



Using the **Orbix Configuration Welcome** dialog, you can perform basic configuration setup tasks, such as create a new configuration domain, or update an existing one. For detailed information on how to perform all the main configuration tasks, see [Configuring and Deploying a Domain](#).

Licensing your Orbix Environment

The Orbix configuration tool enables you to specify the location of your Orbix license file.

Note


You must first specify your license details before you can perform actions such as creating an Orbix configuration domain.

Specifying a license file

To specify a license file:


1. From the Orbix configuration tool main menu, select **Tools>License**. Alternatively, click the **License** button in the toolbar, shown in [Figure 4](#):

Figure 4 Orbix License Button



2. This displays a dialog similar to that shown in [Figure 5](#):

Figure 5 Entering the License File



3. Enter the location of the license file that you wish to install in the **License File** text box. Alternatively, use the **Browse** to navigate to the file. You should have received this file from your Rocket Software representative and stored it in a secure location.

The default locations are as follows:

Windows	<code><install-dir>\etc\licenses.txt</code>
UNIX	<code><install-dir>/etc/opt/iona/licenses.txt</code>

4. Click **OK** to return to the main screen.

The `licenses.txt` file is copied from your specified location. Any existing license files are overwritten. When you have specified a license file, you will not need to perform these steps again.

Configuring and Deploying a Domain

Orbix provides a GUI-based configuration tool to guide you through generating an Orbix environment.

Introduction

A configuration domain contains all the configuration information used by Orbix ORBs, services, and applications. The Orbix Configuration tool configures and deploys Orbix components into a configuration domain. It can also link a machine to an existing configuration domain, or make updates to an existing domain.

Centralized domain design

The Orbix Configuration tool provides a centralized mechanism for designing a distributed configuration domain. While designing your domain, you specify all of the machines that are to host services in your domain, which services are run on each machine, and which machines, if any, host replicas. You can also deploy location services onto machines that host custom servers.

When you have designed your configuration, you must then go to each machine in the domain and deploy the configuration. This populates each machine's configuration databases and correctly deploys the services on each machine.

The Orbix Configuration tool **File>New** menu provides the following setup options:

- **Standard:** This enables you to create a new configuration domain from scratch. It is used to determine the type of configuration being created, what ports the core services use, and what services will be deployed into the domain.
- **Expert:** This enables you to create a new configuration domain from scratch. It is similar to using **Standard**, but it provides access to advanced configuration options. This option is recommended if you are familiar with Orbix administration.
- **Deploy:** This enables you to load and deploy a previously created deployment descriptor, to deploy services on the host machines in a domain, and to deploy replicated services in a domain. For more information, see [Replicating Services in a Domain](#).
- **Open:** This enables you to open an existing configuration domain, and make incremental changes as necessary. For example, you may wish to add additional services to an existing domain, or create replica servers.

- **Connect:** This enables you to connect a client machine to an existing configuration domain. The new machine will link to the existing configuration repository to retrieve its configuration information.

Note

This option fails to create a domain if the configuration repository is not running, or if the domain is file based.

For details of other tasks that you can perform using the Orbix Configuration tool, see [Runtime management tasks](#).

Creating a New Domain

The Orbix Configuration tool's **File>New>Standard** menu option enables you to create a new configuration domain, or modify an existing one, by walking you through the procedure and providing basic configuration options.

For more advanced configuration options, use the **File>New>Expert** option (explained in the next section).

To create a configuration domain, follow these steps:

1. Start the Orbix Configuration tool using the `itconfigure` command (see [Getting Started](#)).
2. From the main menu, select **File>New>Standard**. This displays a screen similar to [Figure 6](#).

Figure 6 Domain Type Screen

Create a Configuration Domain - Standard Mode

Steps

1. Domain Type
2. Service Startup
3. Security
4. Fault Tolerance
5. Select Services
6. Confirm Choices
7. Deploying ...
8. Summary

Domain Type

Configuration Identification

You can create many different configuration domains and access them by their unique name.
What name do you wish to give this configuration domain?

Configuration Domain Name:

Configuration Domain Type

The configuration tool can create configuration domains with different combinations of Orbix services.
Which Orbix services do you want to include in this domain?

☒ All Licensed Services
☐ Select Services

Storage Location

Configuration Directory: ...

Data Directory: ...

<Back **Next>** Finish Cancel


3. Specify the domain name. If you are creating a new domain, this name must be unique among any pre-deployed configuration domains. If it is not, the existing domain is overwritten.

Note

On AIX, if you wish Orbix services to be launched on start up, the domain name must be no longer than seven characters.

4. Set the level of services to deploy into the domain by selecting one of the following options:
- **All Licensed Services** automatically deploys all services for which you have purchased licenses.
 - **Select Services** enables you to select which services you wish to deploy into the domain on the particular machine.
5. Specify the directories where you would like configuration data stored on this system. In most cases, the defaults are sufficient.
6. Click **Next** to select how your services start. This displays a screen similar to [Figure 7](#).

Figure 7 Startup Mode and Base Port



7. Choose one of the following options:

• **A minimal set of services launched by a script I can run** generates a script that starts the location service and, if selected, the configuration repository. All other deployed services will be started on demand.

Note


When one of the following two options is selected, the location service is deployed by default. You will not be able to unselect it.

- **A minimal set of services launched at machine startup** configures the location service and, if selected, the configuration repository to start up when the machine is booted. All other deployed services will be started on demand.
- **All services launched by a script I can run** generates a script that will start all deployed services.

8. Enter a number for the **Base Port**. This is the number from which Orbix begins sequentially assigning listener ports for its services. The default is **3075**.

9. Click **Next** to configure your domain security features. This displays a screen similar to [Figure 8](#).

Figure 8 Setting Security Features



10. Select a protocol:

• **Insecure communication (IIOP/HTTP)** configures your domain so that it does not use TLS or HTTPS protocols. It rejects any attempts to make a secure connection.

Note

This is the only mode in which the Firewall Proxy Service will run.

- **Secure communication (TLS/HTTPS)** configures your system so that all communication is done securely. Any attempts to make a connection using a protocol other than TLS or HTTPS are rejected.
- **Secure and insecure communication** configures your system so that it can use IIOP, TLS, HTTP, and HTTPS protocols.

Note

This option is automatically selected if you configure the IS2 Security Infrastructure. You can only select secure communication.

11. Select the security features you wish to enable in the domain:

- “ **Expose services through Firewall** configures your domain to use the firewall proxy service.

Note

This option is only available for insecure domains.

- “ **Security Service** configures your domain to take advantages of the ORBIX security platform. For more information read the *Security Guide*.

Note

This option forces you to use TLS and HTTPS. Therefore the firewall proxy service is unavailable.

- “ **Enable Access Control for Core Services** is only available for use when the IS2 security infrastructure is configured, For more information read the *Security Guide*.


12. Click **Next** to configure any replicas you wish to include in your domain. This displays a screen similar to [Figure 9](#).

Figure 9 Replica Configuration

The screenshot shows a window titled "Create a Configuration Domain - Standard Mode". On the left, a "Steps" sidebar lists: 1. Domain Type, 2. Service Startup, 3. Security, 4. **Fault Tolerance**, 5. Select Services, 6. Confirm Choices, 7. Deploying ..., and 8. Summary. The main area is titled "Fault Tolerance" and contains a "Replication" section. The text reads: "You can run multiple replicas of the core Orbix services to make your system fault tolerant. The service instances on the replica hosts act as backups." Below this is a "Replication Hosts:" label and a table with one header "Host" and one empty row. To the right of the table are three buttons: "Add", "Remove", and "Edit". At the bottom of the window are four buttons: "<Back", "Next>", "Finish", and "Cancel".

13. To add a replica to the domain, click **Add**, and enter the machine's host name and a listener port in the **Add Host** dialog, shown in [Figure 10](#).


Figure 10 Add Host Dialog



To remove a replica from the list, highlight its hostname and click **Remove**. When you have specified all of the replicas for your domain, click **Next**.

14. If you chose to deploy only selected services, you will see a screen similar to [Figure 11](#).

Figure 11 Selecting Services to Deploy




Note

You must check **Demos** if you wish to use the demo programs provided with Orbix.

If you chose to deploy all licensed services, go to step 16.

15. Select the services you wish deployed into your configuration. When you have selected the desired services, click **Next** to see a summary of the configuration options you have chosen. This displays a screen similar to [Figure 12](#).

Figure 12 Confirmation Screen



16. If you have configured replicas for this domain, or have configured services to run on a different host, you should save the domain descriptor. To save a domain descriptor for this domain, click **Save**.

Note

The name of the domain descriptor must end in "_dd".

17. Click **Next** to create the domain and deploy the local services.
18. When the domain is successfully created, the **Finish** button becomes enabled. Click it to close the tool.


Deploying a Distributed Domain

When you have designed a distributed domain, you must deploy the domain on all of the hosts that make up the domain. To do this, you must take the deployment descriptor created when you designed the domain and migrate it to each host machine.

The Orbix Configuration tool provides the following options for deploying your domain on the remaining hosts:

- Use the **File>Deploy** option from the GUI main menu.
- Use the `-load` and `-nogui` command-line options.

Figure 13 Deploying a Domain



The simplest way to deploy the local part of a domain is to use the **Deploy** option. To use this option, perform the following steps:

1. Select **File>Deploy** from the main menu.
2. Select the deployment descriptor from the file selection dialog, and click **Open**.
3. A screen similar to [Figure 13 on page 23](#) should appear. Enter the location for the configuration databases to be stored, verify the domain name, and click **Next**.

4. Verify that the configuration details displayed in the **Confirmation** screen are accurate. If so, click **Next** to deploy the local services.
5. When the domain has successfully deployed, click **Finish** to exit.

Figure 14 Initializing a Domain

Create a Configuration Domain - Expert Mode

Steps

1. **Domain Details**
2. Storage Locations
3. Select Services
4. Confirm Choices
5. Deploying ...
6. Summary

Domain Details

Domain Name:

Location Domain:

☒ File Based Domain
 ☒ Allow Insecure Communication

☐ Configuration Repository Domain
 ☐ Allow Secure Communication

☐ Launch Domain Services on Machine Startup

☐ Generate EMS configuration files

Address Mode Policy for Object References:

☐ Listen on Address

☐ Use Corbalocs

If you can not or do not want to run the Orbix Configuration GUI, you can deploy a your domain on the local host using the following command line syntax:

```
itconfigure -nogui -load deployment-descriptor
```

This command deploys the specified domain and the services for the local host.

Connecting a Client Machine to a Domain

You may often need to configure machines into a domain that only run client programs. These client programs do not need to run any CORBA services, however, they must access the domain's configuration. The Orbix Configuration tool enables you to connect a new machine to an existing configuration domain. The new machine retrieves and stores its configuration in the configuration repository on the existing host machine.

Note

The **Connect** wizard does not enable you to deploy additional services on a machine. It only generates scripts that enable the current machine to join an existing configuration.


There are two approaches to connecting a client machine to an existing domain:

- To connect a new machine to an existing domain using its deployment descriptor file, perform the following steps:.
- Users without access to a deployment descriptor can also connect a new machine using the Connect to a Configuration Domain wizard. To connect this way, perform the following steps:.

To connect a new machine to an existing domain using its deployment descriptor file, perform the following steps:

1. Select **File>Connect** from the GUI main menu.
2. If you have access to a deployment descriptor, select **Yes** in the dialog shown in [Figure 15](#).

Figure 15 Target Domain Dialog.



3. Select the deployment descriptor from the file selection dialog, and click **Open**.
4. In the **Connect to a Configuration Domain** wizard, enter the details for your link domain. For example, you can specify **General** details such as the location of your configuration files, and **Node Daemon** or **Security** details, if applicable. This wizard is shown in [Figure 16](#).

Figure 16 Connecting to a Domain

Connect to a Configuration Domain - Orbix Configuration

Steps

- 1. Link Domain Details**
2. Confirm Choices
3. Deploying ...
4. Summary

Link Domain Details

General | Node Daemon | Security

Domain Details

Domain Name:

☒ Allow Insecure Communication

☐ Allow Secure Communication

Target CFR Settings

Host:

IIOP Port:

TLS Port:

Storage Location

Configuration Directory: ...

Data Directory: ...

<Back | **Next>** | Finish | Cancel

5. Click **Next** to confirm your input and view a summary of the configuration in the **Confirmation** screen.
6. Click **Next** to create the local files needed to connect the machine to the configuration domain and deploy the local services.
7. When the machine is successfully connected to the domain, in the **Summary** screen, select **Finish**.

Users without access to a deployment descriptor can also connect a new machine using the **Connect to a Configuration Domain** wizard. To connect this way, perform the following steps:

1. Select **File>Connect** from the GUI main menu.
2. Because you do not have access to a deployment descriptor, select **No** in the dialog shown in [Figure 15](#).
3. In the **Connect to a Configuration Domain** wizard, enter the hostname and port of the CFR to which you wish to connect the new machine. If applicable, enter a location for the configuration files, and **Node Daemon** or **Security** details. The wizard is shown in [Figure 16](#).
4. Click **OK** to confirm your input and view a summary of the configuration.
5. Click **Next** to create the local files needed to connect the machine to the configuration domain and deploy the local services.
6. When the machine is successfully connected to the domain, in the **Summary** screen, select **Finish**.

Localizing a Preconfigured Domain

You may need to create a duplicate configuration, one that is identical, except for the hosts that it runs on. Some reasons for doing this are:

- Creating test and production configurations that are identical in everything but the host on which they run.
- Migrating a system from one machine to another.
- Packaging an Orbix installation with a software distribution. You can then ship a configuration template that can be run on each destination machine, with the services localized for that host, rather than the host on which the configuration was created.

If you wish to deploy a preconfigured domain, the Orbix Configuration tool provides two options:

- Use the GUI in Expert mode, and select **Localize**.
- Run the `itconfigure` command with the `-localize` and `-nogui` options.

To use the Orbix Configuration GUI to deploy a localized domain, complete the following steps:

1. Select **File>New>Expert** from the main menu.
2. In the screen shown in [Figure 14 on page 24](#), click **Initialize**, located at the bottom left of the screen.
3. Select the preconfigured domain descriptor from the file selection dialog.
4. Click **Localize**. This replaces the name of the host defined in the original configuration with the local host name.
5. Click **Next**.

6. Click **Finish**.

Alternatively, you can make changes to suit the needs of your environment (see [Deploying a Distributed Domain](#)).

If you can not or do not wish to run the GUI, you can deploy a localized domain from the command line by running:

```
itconfigure -nogui -localize [-from host] -load deployment-descriptor
```

Running this command first replaces a deploy node in the descriptor with the host specified in the `-from host` option or with the local host. It then deploys an exact replica of the specified domain on the new host.

The `-from host` option enables you to select the deploy node to replace when localizing a multi-profile descriptor.

You can specify other changes to the deployed domain by using other command-line options.

Replicating Services in a Domain

You can use the Orbix Configuration tool to configure a machine to use replicas of an existing CFR, locator, naming, and security service. A machine configured to host replicas can also host services as part of an existing configuration domain.

Note

To configure a machine to host replica services, you should have already specified that the domain include replicas when you created it ([Figure 9](#)).

To deploy a CFR-based replica, perform the following steps:

1. Copy the generated deployment descriptor from the host machine to the replica machine that you wish to configure. The deployment descriptor name is *domain_name* `_dd.xml`. For example, the domain descriptor for a domain named `Apollo` will be `Apollo_dd.xml`.
2. Run the **OrbixConfiguration** tool. From the main menu, select **File>Deploy**.
3. In the **Load Descriptor** dialog, select the domain descriptor that you wish to replicate. Click **Open**.
4. A screen similar to [Figure 13 on page 23](#) should appear. Enter the location for the configuration databases to be stored, verify the domain name, and click **Next**.

5. Verify that the configuration details displayed in the **Confirmation** screen are accurate. If so, click **Next** to deploy the local services.
6. When the replica is successfully deployed, click **Finish**.

Updating an Existing Domain

The Orbix Configuration tool enables you to perform dynamic updates on an existing configuration domain (for example, add services or replica services after the domain is created). You can use the **File>Open** option to specify an existing domain descriptor file. Alternatively, use the **File>Reopen** option to access the list of recently used domains. This section includes the following:


- [Opening a domain](#)
- [Reopening a domain](#)
- [Adding a service](#)
- [Adding a replica service](#)
- [Repreparing a service](#)
- [Removing a replica service](#)

Opening a domain

To open an existing domain, perform the following steps:

1. Select **File>Open** from the main menu.
2. Select the deployment descriptor using the **Select Descriptor** dialog, shown in [Figure 17](#).


Figure 17 Select Descriptor Dialog



This dialog also enables you to specify **Standard Settings** and **Advanced Settings** for domains with non-default locations.

3. Click **OK**. This loads up the domain and displays summary information in the GUI, shown in [Figure 18](#).

Figure 18 Loaded Domain



When the domain has been opened, you can then start or stop its services, perform dynamic updates (for example, add a service or replica service), or launch consoles for that domain.

Note

In CFR or link domains, the effective deployment descriptor for the domain is obtained from the CFR itself. Therefore, to open a CFR domain, at least one CFR replica must be running.

Reopening a domain

The **Reopen** option enables you to select a domain from a list of recently used domains, without having to specify a domain descriptor.


To use this option, select **File>Reopen** from the main menu, and select the domain that you wish to reopen.

Adding a service

To add a service to an existing domain, perform the following steps,

1. Select the machine node on which you want to add the service.
2. Right-click to select **Add**, and select the service that you require. [Figure 18](#) shows an example of adding a CORBA Events service.

Figure 19 Adding a Service to a Domain



The domain services must be running, and you can only select from services that are not already in the domain. You can only add services on the host that the **Orbix Configuration** tool is run. To extend a domain to include another host, create a link domain (see [Connecting a Client Machine to a Domain](#)).

When you add a new service, the local domain scripts, configuration files, and log files are updated with details of the new service. The domain scripts include the following:

```
domain-name_env
```

```
start_domain-name_services
```


```
stop_domain-name_services
```

Adding a replica service

To add a replica service to an existing domain, perform the following steps:

1. Select the machine node in the left pane, right click to select **Add**, and select the replica service that you require. [Figure 20](#) shows an example of adding a replica locator.

Figure 20 Adding a Replica Service to a Domain



The domain services must be running, and you can only select from services that are not already in the domain. You can only add services on the host that the **OrbixConfiguration** tool is run. To extend a domain to include another host, create a link domain (see [Connecting a Client Machine to a Domain](#)

Note

You can replicate the CFR, locator, and naming services using the **Orbix Configuration** tool. Security replicas must be configured manually (see the *Security Guide* for details).

- After selecting the replica service, you can specify details such as the **Instance Name** and ports for your replica service. [Figure 21](#) shows an example of the **Add Location Service Replica** dialog.

Figure 21 Add Location Service Replica dialog

Add Location Service Replica - Orbix Configuration

Hosts

Host:

Instance Name:

Endpoints: ☒ Insecure ☐ Secure

IIOP Port:

HTTP Port:

Other Instances:

Host	Instance Name
summer	summer

Service Launching

☒ Standalone Service

☒ Launch Service on Domain Startup

Other Properties

☒ Managed

☐ Performance Logging

☐ Firewall Proxy

☒ Dynamic Logging

OK Cancel

- After adding the replica, you may be prompted to perform additional steps. For example, after adding a replica locator, you must reprepare any indirect persistent services. This ensures that the object references for these services include the address of the locator replica, and enables clients to be correctly directed to these services.

Removing a replica service

To permanently remove a replica service from a domain, perform the following steps:

1. Select the service in the left pane, and right click to select **Remove**. When removing a replica, it must be running in the domain.

This action removes details of the service from the domain scripts (for example, `start_my-domain_services`).

2. After removing a replica, you may be prompted to perform additional steps. For example, after removing a replica locator you must reprepare any indirect persistent services. This ensures that their object references do not include the address of the removed locator.


Repreparing a service

After creating or removing a replica locator, you must first reprepare any indirect persistent services. This ensures that the object references for these services include the correct locator address information.

For example, when creating a locator replica, an indirect persistent service must be reprepared to ensure that its object reference includes the address of the locator replica. When removing a locator replica, repreparing ensures that it no longer includes the address of the removed locator.

To reprepare a service, select the service in the left pane, and right click to select **Reprepare**. [Figure 18](#) shows an example.

Figure 22 Repreparing a Service



Starting and Stopping Orbix Services

The Orbix Configuration tool automatically generates start and stop scripts. These enable you to manually activate and deactivate all services deployed on the configured host. You can activate these scripts directly in the GUI or using the command line.

To start all services for the current domain that are deployed on this machine, select **Run>Start** from the main menu, or click the **Start** button in the toolbar.

Alternatively, you can start all domain services using the following command:

```
config-dir/bin/start_domain-name_services
```

To stop all services for the current domain that are deployed on this machine, select **Run>Stop** from the main menu, or click the **Stop** button in the toolbar.

Alternatively, you can stop all domain services using the following command:

```
config-dir/bin/stop_domain-name_services
```

To start or stop an individual service, select the service in the left pane, right click, and select **Start** or **Stop**.

For details of starting and stopping individual services on the command line, see the *Orbix Administrator's Guide*.

To set your command shell to recognize a specific domain, select **Run>Command Shell**.

Alternatively, you can set your environment using the following command:

```
config-dir/bin/domain-name_env
```

Setting Java ORB Classes

Note

This section applies only to versions of Java earlier than Java 11. From Java 11 onwards the following procedure is unnecessary because of the removal of the Java CORBA module in modern JDKs.

To run Java applications, Orbix must use its own ORB classes instead of Sun ORB classes. You can ensure that Orbix finds the correct classes one of the following ways:

- Use an `iona.properties` file.
- Use Java system properties when invoking the Java interpreter.

You can create an `iona.properties` file in the `JAVA_HOME/jre/lib` directory. This file should contain the following settings:

```
org.omg.CORBA.ORBCLASS=com.ionacorba.art.artimpl.ORBImpl  
org.omg.CORBA.ORBSingletonClass=com.ionacorba.art.artimpl.  
ORBSingleton
```

Note

The **Orbix Configuration** tool automatically creates an `iona.properties` file in the `install-dir\etc\domains\domain-name` directory. This file is added to the `CLASSPATH` set by your domain's initialization script.

You can invoke the Java interpreter with the `-D` options as follows:

```
java -Dorg.omg.CORBA.ORBCLASS=com.ionacorba.art.artimpl.ORBImpl  
-Dorg.omg.CORBA.ORBSingletonClass=com.ionacorba.art.artimpl.ORBSingleton  
app-name
```

Advanced Configuration and Deployment

This section explains advanced custom configuration and deployment features offered by Orbix.

Creating a Domain in Expert Mode

Expert mode provides advanced users a more flexibility when creating and modifying configuration domains. It enables you to specify well-known addresses for Orbix services, and also to configure the services to run using direct or indirect persistence.

Procedure

To create a configuration domain using expert mode, complete the following steps:

1. From the main menu, select **File>New>Expert**.
2. In the **Domain Details** screen, enter a name for the domain and specify if the domain is to be file-based or CFR-based, shown in [Figure 23](#).

Figure 23 Domain Details Screen

Create a Configuration Domain - Expert Mode

Steps

1. Domain Details
2. Storage Locations
3. Select Services
4. Confirm Choices
5. Deploying ...
6. Summary

Domain Details

Domain Name:

Location Domain:

☒ File Based Domain
 ☒ Allow Insecure Communication

☐ Configuration Repository Domain
 ☐ Allow Secure Communication

☐ Launch Domain Services on Machine Startup

☐ Generate EMS configuration files

Address Mode Policy for Object References:

☐ Listen on Address

☐ Use Corbalocs

3. Select the level of security for your domain:

- **Allow Insecure Communication** configures your domain to allow communication over insecure protocols such as HTTP.
- **Allow Secure Communication** configures your system to allow secure communication using TLS or HTTPS.

4. To have the domain be started on system start-up place a check next to **Launch Domain Services on Machine Startup**.

Note

If you choose to have the domain services launch at machine startup as Windows services, the system path needs to contain certain directories. For versions of Java earlier than Java 11, these are:

- %IT_PRODUCT_DIR%\asp\6.3\bin
- %IT_PRODUCT_DIR%\bin
- %JAVA_HOME%\jre\bin\server

If you chose **Set the variables for all users** at installation, then the path is already correctly set.

For Java 11 onwards, the necessary directories are:

- %IT_PRODUCT_DIR%\asp\6.3\bin
- %IT_PRODUCT_DIR%\bin
- %JAVA_HOME%\bin\server

5. If you wish to integrate your domain into an Enterprise Management System (for example, IBM Tivoli, BMC Patrol, or HP Openview), check **Generate EMS configuration files**.

6. Use the **Address Mode Policy for Object References** drop-down box to select how services publish hostnames in their object references. Select one of the following options:

- Short (unqualified) hostname
- Fully qualified hostname
- localhost (the default)
- IP Addresss
- 127.0.0.1


7. Click **Next** to specify the location of the files associated with your domain. The **Storage Locations** dialog is displayed, shown in [Figure 24](#).

8. If you wish to store your configuration and logging information in non-default locations, you can specify these using the **Standard Settings** and **Advanced Settings**.

Normally, databases and service log files are stored in the `db` and `log` directories of the **Data Directory**. Configuration files and scripts are stored in `domain` and `bin` directories of the **Configuration Directory**.

If you want more fine-grained control over where the domain service database and log files, and configuration scripts and log files reside, specify the **Advanced Settings**. All required directories are created if they do not already exist.

Figure 24 Storage Locations Screen




9. You can also initialize your domain's service database and log files with those of an existing domain. These domain files are copied from the locations specified by the **Import Databases from** field.

Note

To ensure data integrity, ensure that the other domain's services are shut down when this domain is being deployed. Only databases created with Orbix 6 SP 1, or later, can be imported.

10. Click **Next** to select the services to deploy into the domain. The **Select Services** screen is displayed, shown in [Figure 25](#).
11. In the **Select Services** screen, check the services that you wish to deploy into the domain

Figure 25 Select Services Screen




Note

If you do not check **Demos**, the demo programs included with the installation will not run properly.

- If you wish to deploy a service using non-default settings, click the **Edit** button next to the service's name. This displays a dialog similar to Figure 26. This enables you to configure options specifically for the service (for example, activation modes, replication settings, and optional properties). When you have selected the settings, click **OK** to return to the **Select Services** screen.

Figure 26 Location Settings Dialog



The dialog box is titled "Location Settings - Orbix Configuration". It contains the following sections:

- Hosts:**
 - Host:
 - Endpoints: Insecure Secure
 - IIOP Port:
 - HTTP Port:
- Service Launching:**
 - ☒ Standalone Service
 - ☒ Launch Service on Domain Startup
- Other Properties:**
 - ☒ Managed
 - ☐ Performance Logging
 - ☐ Firewall Proxy
 - ☒ Dynamic Logging

At the bottom right are "OK" and "Cancel" buttons.

Note


Some options may not be available for all services (for example, replication is available for the locator, CFR, security and naming services only).

Standalone Services are direct persistent and therefore are all started individually at domain startup.

Launch Services on Domain Startup are indirect persistent and are started individually with the domain start script.

13. The default is to start services as indirect persistent on demand, via the locator and node daemon. After selecting and configuring the desired services, click **Next** to view the configuration options that you have chosen. This displays a **Confirmation** screen similar to [Figure 27](#).
14. If you have configured replicas for this domain or have configured services to be run on different hosts you must save a domain descriptor. To save a descriptor, click **Save**.

Figure 27 Confirmation Screen



15. If you want to proceed to deploy, click **Next** to create the domain and deploy any local services.

16. When the domain is successfully created, the **Finish** button becomes enabled. Click **Finish** to exit.

Configuring a Machine with no GUI

You may need to occasionally configure and deploy an Orbix domain on a machine with no GUI capabilities (for example, a server on a remote site). The Orbix Configuration tool supports this by enabling you to create a domain deployment descriptor on one host, and then deploy it on another host.

Orbix provides a command-line version of the configuration tool (`itconfigure -nogui`) for users who cannot deploy using a GUI application. This parses a pre-existing deployment descriptor and deploys the specified configuration domain.

Creating the deployment descriptor

The recommended method of generating the deployment descriptor is to first run the Orbix configuration tool on a GUI-enabled machine, and then save the deployment descriptor for later use in command-line mode. This ensures that the generated XML document is valid.

To create the deployment descriptor, complete the following steps:

1. On a machine with GUI capabilities, run the configuration GUI and select **File>New>Expert** from main menu.
2. To design the domain, follow the steps outlined in [Creating a Domain in Expert Mode](#).
3. On the **Select Services** screen, click **Settings**. This displays a dialog box similar to the one shown in [Figure 28](#).
4. In the **Host** text box, enter the name of the remote host, and click **Apply**.
5. In the **Confirmation** screen, click **Save** to save the deployment descriptor.

Figure 28 Domain Defaults Dialog

Domain Defaults - Orbix Configuration

Hosts

Host:

Base Port:

Address Mode Policy for Object References:

Monitoring

☐ Instrumented

Uplink Dir: ...

Service Launching

☐ Standalone Service

☐ Launch Service on Domain Startup

Other Properties

☐ Managed

☐ Performance Logging

☐ Firewall Proxy

☐ Dynamic Logging

Deploying on the command line

To deploy a deployment descriptor on the command line, perform the following steps:

1. Copy your deployment descriptor file to the machine without GUI capabilities.
2. At the command prompt, change directory to the location of your domain deployment descriptor, for example:

```
<install-dir>\etc\domains\sample-domain
```

3. Enter the following command:

```
itconfigure -load sample-domain_dd.xml -nogui
```

`itconfigure` reads the specified deployment descriptor, finds the profile matching the current host's IP address and deploys the services in this profile. If no such match is found, `itconfigure` prints an information message and exits.

4. Repeat this process on any other hosts for which you have configured services.

Localizing the domain

If the descriptor contains exactly one profile/node, and that node does not match the local host, use the following command:

```
itconfigure -load sample-domain_dd.xml -nogui -localize
```

This replaces the name and IP address of the node specified in the deployment descriptor with name and IP address of the local host.

Changing the domain name

If you wish to change the name of the configuration domain, use following command:

```
itconfigure -load sample-domain_dd.xml -nogui -name my-domain
```

The name specified using `-name` overrides the name specified in the descriptor.

Note

On AIX, if you wish Orbix services to be launched at start up, the domain name must be no longer than seven characters.

Deploying on Multi-homed Machines

You may need to configure and deploy an Orbix domain on a *multi-homed* server machine. This is a machine that has more than one IP address and corresponding hostname, and where only one address/hostname is configured as the default.

If you want to use a non-default Orbix hostname, you can supply it explicitly to the **Orbix Configuration** tool. This provides a `-multihome` command-line option, where the alternate hostname can be specified.


Specifying the `-multihome` option to `itconfigure` instructs Orbix-supplied services, such as the locator, to use the specified hostname when listening on a `host:port` and embedding a host into an IOR.

Multi-homed deployment process

When you click the configuration tool's **Finish** button, the behavior in GUI mode is identical with command-line mode. The configuration tool has a deployment descriptor loaded in memory, and must decide which services to deploy. The selection process is as follows:

- The configuration tool looks for the host node that matches the localhost IP address, using `InetAddress.getLocalHost().getHostAddress()`.
- If a matching host is found, the configuration tool deploys the services specified in this node's profile.
- If no matching host is found, the configuration tool displays a dialog that enables you to deploy on another hostname. For example, [Figure 29](#) shows the dialog displayed when there are more than two nodes.

Figure 29 Dialog for More than Two Nodes



You can choose to deploy the services for one of these nodes. This only succeeds if you are on a multi-homed machine, and the selected node's IP address/name maps to another non-default network interface on this machine. The exception is when there is no interaction between the services on the selected node.

For more information on deployment descriptor nodes and profiles, see [Orbix Deployment Descriptors](#).

Deploying on the command line

On the command line, you can specify the host to consider as the local node to `itconfigure`. This avoids the step described in [Multi-homed deployment process](#).

If the deployment descriptor has a `<dd:node>` `name` attribute set to the name of a virtual or additional network adapter (for example, `othello`), you can deploy the services for this node using the following command:

```
itconfigure -nogui -multihome othello -load <descriptor-name>
```

The `-multihome` option instructs `itconfigure` to look for a node matching the specified `-multihome` value instead of finding one that matches the localhost's default IP address.

Deploying with the GUI

In GUI mode, you can also use the `-multihome` option when starting the GUI to avoid the step described in [Multi-homed deployment process](#). When you click **Finish**, `itconfigure` initializes the default host with the one specified by `-multihome`. Unless you manually alter the host field(s), no dialog appears when you click **Finish** because there is no conflict to resolve.

To configure and deploy a domain on a multi-homed machine using the GUI, complete the following steps:

1. On a multi-homed machine, run the configuration tool with the `-multihome` command-line option, and specify the alternate hostname. For example, on a multi-homed machine with primary hostname `orion`, and an alternate hostname `othello`, use the following command:

```
itconfigure -multihome othello
```

2. Select **File>New>Expert** from main menu, and follow the steps outlined in [Creating a Domain in Expert Mode](#).
3. In the **Select Services** dialog, click **Settings**. This displays a dialog box similar to the one shown in [Figure 28 on page 40](#).
4. The **Host** box should match the hostname specified by the `multihome` parameter on the command line.
5. Click **Apply**.


6. Because the configuration tool has been informed of the alternate hostname, deployment can then proceed as normal (see [Creating a Domain in Expert Mode](#)).

Modifying hostnames without the -multihome option

If you do not use the `-multihome` option, and you modify the content of the hosts field, `itconfigure` displays the dialog shown in [Figure 30](#).

If you click **Yes**, the services are deployed. The last sentence in this message shows that this conflict can also arise when the host is a truly remote machine, and forcing local deployment would not make sense.

Figure 30 Multi-homed Message



Configuring your Orbix applications for multi-homed hosts

Specifying the `-multihome` option to `itconfigure` instructs Orbix-supplied services, such as the locator, to use the specified hostname when listening on a `host:port`, and embedding a host into an IOR. However, by default, Orbix applications written by the user still use the default hostname.

To use a multi-homed hostname with your Orbix application, you must specify values for the following configuration variables in your application configuration scope:

- `policies:iiop:client_address_mode_policy:local_hostname`
- `policies:iiop:server_address_mode_policy:local_hostname`

For example, the following `itadmin` commands show examples of setting both these variables:

```
itadmin variable create -scope ApplicationScope \
-type string -value Hostname \
policies:iiop:client_address_mode_policy:local_hostname
itadmin variable create -scope ApplicationScope \
-type string -value Hostname \
policies:iiop:server_address_mode_policy:local_hostname
```

These settings configure applications listening on random ports to use the specified hostname. The most common use case is when the domain is for a single host. In this case, you can create these variables in the global configuration scope.

Configuring Orbix in a Cluster

A cluster is a group of two or more machines, in which the following applies:

- Each machine has its own hostname.
- There is also a virtual hostname/IP address, but this is assigned to only one machine at a time.
- A shared disk drive can be mounted by only one machine at a time

A cluster is a means of providing failover. Software, configuration files, databases, and so on, can be stored on the shared disk. While server applications always advertise themselves using the virtual hostname.

Clustering software is used to monitor the health of software running on the active computer. If something goes wrong, a failover is made to another computer in the cluster. This section explains how to set up a cluster in an Orbix environment.

Configure a multi-homed Orbix host

On the currently active machine in the cluster, install Orbix on the shared disk, and run the following command:

```
itconfigure -multihome virtual-hostname
```

This configures Orbix services such as the locator for use on a multi-homed host. For full details, see [Deploying on Multi-homed Machines](#).

Configure your Orbix applications as multi-homed

To use a multi-homed hostname with Orbix applications you have written, specify values for the following configuration variables in your application configuration scope:

- `policies:iiop:client_address_mode_policy:local_hostname`
- `policies:iiop:server_address_mode_policy:local_hostname`

This instructs your applications listening on random ports to use the specified hostname. For more details, see [Configuring your Orbix applications for multi-homed hosts](#).

Write shell scripts for Orbix services and applications

Write shell scripts that do the following:

- Start Orbix services and user-written Orbix server applications.
- Stop your Orbix server applications and Orbix services.
- Check the health of Orbix services and Orbix server applications (for example, using `ps` and `grep`).

For more details, see [Starting and Stopping Orbix Services](#).

Register your shell scripts

Finally, you must register your Orbix shell scripts with the clustering software used in your environment.

Configuring Services to Listen on Network Interfaces

By default, `itconfigure` generates domains in which services are configured to listen on all interfaces on that host. This behavior can be changed by explicitly specifying a list of listen addresses *as a comma-separated list of hostnames or IP addresses*. Using dedicated listen addresses is useful for example if you want to set up to domains on the same host listening on the same ports, where each domain's services would receive client requests from independent networks.

Specifying address lists using the Expert wizard

You can specify a listen address list on the first page of the **Expert** wizard. The value entered in this text field will be used in set the following configuration variable:

```
wka:transport:addr_list = ["publish address(listen address list):port"];
```

In this syntax, the publish address is the address (as hostname or IP address, depending on the selection of the address mode policy) the server uses when it publishes object references. See also section [Specifying Address Mode Policies](#).

Example

When specifying a listen address list of `10.2.3.57` and deploying a locator, using insecure transports only and the default IIOP port, on host `orion`, the following variable will be defined for the locator:

```
plugins:locator:iiop:addr_list = ["orion(10.2.3.57):3075"];
```

Specifying address lists on the command line

You can also specify the listen addresses on the command line, using the `-listen_address_list` `List` option:

For example:

```
itconfigure -nogui -load sample_dd.xml -listen_address_list 10.2.3.57
```

In either case, the addresses are used only if and when deployment takes place. They are not stored in the deployment descriptor because they are not portable (i.e. they usually become meaningless if the descriptor is localized on another host).

Specifying Custom Locations for Domain Files

This section explains how to specify custom locations for all your configuration domain's files by passing properties to `itconfigure`. It includes the following topics:

- [Configuration domain files](#)
- [Command-line options for custom locations](#)
- [Setting all locations on the command line](#)
- [Partially setting custom locations](#)
- [Redeploying an existing domain](#)

Note

You can also set these custom locations using the Orbix Configuration GUI. For more details, see the **Advanced Settings** in [Creating a Domain in Expert Mode](#).

Configuration domain files

Orbix configuration domain files include start, stop, and `_env` scripts, domain databases, domain log files, and configuration (`.cfg`) files.

Specifying custom locations for these domain files enables you to use a directory structure such as the following:

- `domains/bin/*_env|start*|stop*`
- `domains/config/*.cfg|cfr-*.cfg`
- `domains/dbs/<domain>/<service>/...`
- `domains/logs/<domain>/...`

Command-line options for custom locations

By default, domain start/stop and environment scripts are stored in the `bin` subdirectory of your `<config_dir>`. Domain configuration files are stored in the `domains` subdirectory in your `<config_dir>`.

By default, database files are stored in the `<domain_name>/dbs` subdirectory of your `<var_dir>`. Service log files are stored in the `<domain_name>/logs` subdirectory of your `<var_dir>`.

The default locations for `<config_dir>` and `<var_dir>` are shown in [Table 1](#). These locations can be overwritten using the command-line options to `itconfigure` and properties displayed in [Table 1](#).

Table 1: Properties and Options for Custom Directory Locations

Location for	Property	Command line option	Default location
Configuration files and scripts for all domains (<code><config_dir></code>)	<code>com.iona.dep</code> <code>loy.config.d</code> <code>ir</code>	<code>-etc</code>	Windows: <code>%IT_PRODUCT_DIR%\etc</code> UNIX: <code>/opt/etc/iona,</code> <code>\$IT_PRODUCT_DIR/</code> <code>etc or \$HOME/etc</code>

Location for	Property	Command line option	Default location
Database and log files for all domains (<code><var_dir></code>)	<code>com.iona.deploy.data.dir</code>	<code>-var</code>	Windows: <code>%IT_PRODUCT_DIR%\var</code> UNIX: <code>/opt/var/iona, \$IT_PRODUCT_DIR/var</code> or <code>\$HOME/var</code>

Setting all locations on the command line

The `itconfigure` command enables you to specify the custom locations for the domain log, data, script and configuration files. The configuration GUI also provides feedback on locations that are passed to `itconfigure` as properties. If all four configuration file locations are set, the GUI does not prompt for the `config` and `var` directories. Instead, it displays the values for these four directories in non-editable text fields.

To deploy your custom locations, specify your custom locations to `itconfigure` on the command line for example:

```
e:\Program Files\iona\asp\version\bin>itconfigure -name -nogui d1\
-Dcom.iona.deploy.config.bin.dir=e:\domains\bin \
-Dcom.iona.deploy.config.domains.dir=e:\domains\config \
-Dcom.iona.deploy.domain.db.dir=e:\domains\dbs\d1 \
-Dcom.iona.deploy.domain.log.dir=e:\domains\log\d1
```

This provides more fine-grained control. The command-line properties are explained in [Table 2](#).

Table 2: Properties for Custom File Locations

Location for	Property	Default location
Domain start/stop and env scripts	<code>com.iona.deploy.config.bin.dir</code>	<code><config_dir>/bin</code>

Location for	Property	Default location
Domain configuration files	<code>com.iona.deploy.config.domains.dir</code>	<code><config_dir>/domains</code>
Domain data files	<code>com.iona.deploy.domain.db.dir</code>	<code><var_dir>/ <domain_name>/dbs</code>
Domain log files	<code>com.iona.deploy.domain.log.dir</code>	<code><var_dir>/ <domain_name>/logs</code>

Note

If all four properties are specified, values for the `etc` and `var` directories do not need to be specified (their default values are not relevant). However, if any of these values is not specified, it defaults to a subdirectory of the `var` or the `etc` directory.

Partially setting custom locations

If all four custom locations have not been set, a value for the configuration and/or data directories is required, so that the missing value can be replaced with a subdirectory of the configuration or data directory. The GUI displays the configuration and data directories in editable text fields, and displays the directories that have already been set in non-editable text fields.

For example, specify the following on the command line:

```
e:\Program Files\iona\asp\version\bin>itconfigure \
-Dcom.iona.deploy.domain.db.dir=e:\domains\dbs\d1 \
-Dcom.iona.deploy.domain.log.dir=e:\domains\log\d1
```

This will be displayed in the **Storage Locations** screen. You can select the default configuration directory (for example, `e:\program_files\iona`), or overwrite this value with a custom location. If you click **Next** and continue to select and deploy services, your domain files will be located as follows:

scripts	<code>e:\Program Files\iona\etc\bin</code>
configuration files	<code>e:\Program Files\iona\etc\domains</code>
databases	<code>e:\domains\dbs\d1</code>

service and deployer log files	e:\domains\log\d1
--------------------------------	-------------------

Note

If the `etc` directory does not exist and needs to be created, `itconfigure` requires your confirmation. However, it does not require confirmation to create the domain log and domain database directories.

Redeploying an existing domain

Before deploying, the configuration tool checks for existing scripts in the `bin` directory, configuration files (and sub-directories named `<domain_name>`) in the `domains` directory, databases in the `db` directory, and logs in the `log` directory.

If any such files exist, this indicates that a domain with the same name already exists. The configuration tool only continues and deletes the existing files after your confirmation. This has the same effect as in the default case. For example, domain log files and domain databases are located in `<var_directory>/<domain_name>/db` and `<var_directory>/<domain_name>/log`. Only the sub-directories are deleted, leaving the `<var_directory>/<domain_name>` directory.

Specifying Custom Library Paths

This section explains how to specify a custom library path on the command-line or using the configuration GUI.

This enables you to put shared libraries in different directories and still deploy, without needing to change system defaults that may need root/administrator permissions.

Using the command line

The `-libs` (shorthand `-L`) option to the `itconfigure` command has the following syntax:

```
-libs <library-path>
```

or

```
-L <library-path>
```

Specifying this option causes `itconfigure` to pass the supplied library path to the deployer. The deployer then prepends the path to the built-in path used when preparing and running Orbix services.

The library path argument is a list of directories to be searched for shared libraries when a service is run. The syntax of the list is the same as the platform-specific path syntax, as shown in the following examples.

UNIX:

```
itconfigure -load sample_dd.xml -libs /usr/my_libs:/home/me/lib -nogui
```


Windows:

```
itconfigure -load sample_dd.xml -libs c:\usr\my_libs;d:\me\lib -nogui
```

Using the configuration tool

You can also use the **Orbix Configuration** tool to specify library paths to the deployer.

Figure 31 Options dialog



To specify a library path, perform the following steps:

1. Select **Tools>Options** to display the **Options** dialog.
2. Enter your path in the **Library Path** field, for example:

```
c:\usr\my_libs;d:\me\lib
```

If you are using a multi-homed machine, you can enter the required machine name in the **Host** field.

Using Custom XML Files

This section explains how to automate the process of deploying an Orbix configuration domain, and subsequently add or modify some of its configuration data (for example, adding a scope for a service developed at your site).

In previous versions of Orbix (for example 5.x), you could only do this by manually modifying the `ABDriver.dtd` and `<domain_name>_driver.xml` files generated by the `itconfigure` tool. Orbix 6.0.2 and higher enable you to do this by passing a system property to the `itconfigure` command. This section includes the following topics:

- [Passing custom XML to itconfigure](#)
- [Deploying custom XML with the GUI](#)
- [Custom XML example](#)
- [Rules for writing XML files](#)

Passing custom XML to itconfigure

To use custom XML files, you must first supply the path to the directory containing your files to the `itconfigure` tool. You can do this by passing a system property to `itconfigure`, for example:

```
itconfigure -Dcom.ionadeploy.custom.xml.dir=e:\custom\conf
```


The specified directory should exist and contain at least one file with the `.xml` extension.

Deploying custom XML with the GUI

To deploy custom XML files, perform the following steps:

1. Select **File>New>Expert** from main menu.
2. Click **Next** to display the **Storage Locations** screen
3. Click **Next** to display then **Select Services** screen, shown in [Figure 32](#). The **Custom Components** checkbox at the bottom right of the screen is disabled. This is unchecked when no custom components are selected.


Figure 32 Custom Components in Select Services



4. Click the **Select** button on the right of the **Custom Components** checkbox to display the **Select Custom Components** dialog, shown in [Figure 33](#). This enables you to select components from your specified directory.

Click **OK**. The **Custom Components** checkbox is then displayed as checked.

Figure 33 Select Custom Components



Custom XML example

For example, if you select the custom XML file with the following content:

```

<?xml version="1.0" encoding="UTF-8"?>
<!DOCTYPE ABDeploy SYSTEM "ABDeploy.dtd">
<ABDeploy>
<service>
<dataId>example_using_custom_xml_files</dataId>
</service>
<process>
<stage action="filePopulate">
<source>
<Dsection>main</Dsection>
</source>
</stage>
</process>
<section name="main">
<configScope>
<dataId>custom</dataId>
</configScope>
<configData scope="custom">
<dataId>custom:example:var</dataId>
<dataType>list</dataType>
<dataValue>This</dataValue>
<dataValue>is</dataValue>
<dataValue>just</dataValue>
<dataValue>an</dataValue>
<dataValue>example!</dataValue>
</configData>
</section>
</ABDeploy>

```

Then the generated configuration will include the following fragment:

```

custom
{
custom:example:var = ["This", "is", "just", "an", "example!"];
};

```

Note

If you select more than one custom component, the order in which they are deployed is non-deterministic. Do not make any assumptions about the order in which custom components are deployed, except that they are deployed after all Orbix services and components.

Rules for writing XML files

If you write your own XML files, you should obey the following rules:

- Only use a simple service element (one with just a `dataId` child).
- Use simple process elements and stages with one of the following actions only: `filePopulate`, `configPopulate`.
- Do not use constraints.
- Use `configData` elements with a `dataType` of `list`, `string`, or `long`.
- Do not use external entities.

Warning

The schema for the Orbix deployer XML files is not fully documented. A subset of the complete DTD is supported and documented. Unsupported features are subject to change without notice. For details, see [Orbix Deployment DTD](#).

Specifying Address Mode Policies

This section explains how to use address mode policies to control the way in which host names and/or IP addresses are published in IORs. In previous versions of Orbix, you could do this by specifying the host DNS alias or IP address. Orbix 6.0 and later use policies. These are portable and enable you to design your configuration domain on one host (run `itconfigure` in GUI mode and save the descriptor), and deploy it elsewhere, without the need to supply actual hostnames or IP addresses at that later stage.

This section includes the following topics:


- [Selecting an address mode](#)
- [Specifying a fully-qualified hostname](#)
- [Persistence of address mode policies](#)
- [Restrictions and special cases](#)
- [Node daemon address mode policies](#)
- [Leaving the node daemon name unset](#)
- [Assigning a node daemon name other than the hostname](#)

Selecting an address mode

To select an address mode, perform the following steps:

1. Run the configuration GUI using the `itconfigure` command.
2. Select **File>New>Expert** from main menu. This displays the **Domain Details** screen.
3. Select your preferred policy using the **Address mode policy for Object References** drop-down box, shown in [Figure 34](#).

Figure 34 Selecting an Address Mode Policy



Specifying a fully-qualified hostname


To use fully qualified hostnames in IORs, you must ensure that `itconfigure` knows the fully qualified host name. Depending on your network configuration, this cannot always be obtained with JDK 1.3 APIs.

However, you can do this by invoking the `itconfigure` command using the `-host` option, for example:

```
itconfigure -host orion.dublin.emea.iona.com
```

Alternatively, you can edit the host field in the **Domain Defaults** dialog shown in [Figure 35](#). This dialog is displayed opens when you click **Settings** on the **Service Settings** screen, shown in [Figure 35](#):

Figure 35 Specifying a Hostname



Persistence of address mode policies

If you chose not to deploy now, and save the descriptor to deploy on other hosts, you can still use the selected address mode policy on the other hosts because the policy is persisted by the descriptor.

The descriptor stores addresses as policies (instead of literal string IP addresses or names). This enables you to apply the same policy on other hosts, using the `-localize` option to `itconfigure`. For more information, see [Replicating Services in a Domain](#).

Restrictions and special cases


While the deployment descriptor schema supports node-specific address mode policies, the Orbix configuration GUI only allows you to specify the address mode policy on a global level—for all nodes.

If you must use different policies on different nodes, please refer to [Orbix Deployment Descriptors](#), and manually edit the descriptor. The same applies if you want one more level of granularity and specify address mode policies on a per-service basis. There is one case, however, where you can specify address mode policies on a per-service basis. The Orbix configuration tool enables you to set service-specific address mode policies for the node daemon.

Node daemon address mode policies

The **Node Daemon Settings** dialog, shown in [Figure 36](#), enables you to specify the address mode policy for node daemons:

Figure 36 Node Daemon Settings Dialog



Therefore, if you want all services, except for the node daemon, to publish fully qualified host names, you must first change the global address mode policy to `fully qualified hostname`. For the node daemon, you can override this with the localhost IP policy (`127.0.0.7`).

Note

This policy is used for all node daemons in the domain. `itconfigure` does not allow you to interactively specify the node daemon's address mode policy on a per instance basis.

Leaving the node daemon name unset

It is also possible (but not recommended) to avoid giving the node daemon an explicit name. The default is node daemon name is `iona_services.node_daemon.<hostname>`, which corresponds to the ORB name and configuration scope. For example:

```
iona_services.node_daemon.my_hostname {
  plugins:node_daemon:name = "iona_services.node_daemon.my_hostname";
  ...
}
```

To leave the node daemon name unset, check **Don't set variable `plugins:node_daemon:name`**, displayed in [Figure 36](#).

If a node daemon does not have a name configured, at startup, it registers itself with the locator, and identifies itself as a node daemon named `<host>`, where `<host>` is obtained by `gethostname()`. This value depends on the host on which the node daemon is started.

Note

This may break the mapping between a process and node daemon. A process that is registered to be monitored and started on demand by node daemon `<activating host>` can only be activated if a node daemon with the name `<activating host>` exists. In addition, generated start and stop scripts will not stop such a node daemon.

Assigning a node daemon name other than the hostname

You can also assign a node-daemon name that is not related to the hostname. You can do this by editing the node details in the deployment descriptor file. The recommended approach is to deploy using `itconfigure`, update the deployment descriptor, and then re-deploy with the new descriptor file.

The following example shows these steps in more detail:

1. Deploy as normal using `itconfigure`. However, you must choose the IP address mode policy (see [Selecting an address mode](#)). For example, for a machine named `spring`, the deployment descriptor would include:

```
<dd:nodes>
<dd:node name="spring" ip="10.5.1.101" profile="spring">
<dd:policies>
<dd:policy name="address_mode" value="ip"/>
</dd:policies>
</dd:node>
</dd:nodes>
<dd:profile id="spring">
```

2. Update the deployment descriptor to remove any relation between the hostname (`spring`) and the node name (in this case, `summer`). For example:

```
<dd:nodes>
<dd:node name="summer" ip="10.5.1.101" profile="summer">
<dd:policies>
<dd:policy name="address_mode" value="ip"/>
</dd:policies>
</dd:node>
</dd:nodes>
<dd:profile id="summer">
```

The values of the `profile` and `node name` attributes can be different, for example:

```
<dd:nodes>
<dd:node name="summer" ip="10.5.1.101" profile="profile_1">
<dd:policies>
<dd:policy name="address_mode" value="ip"/>
</dd:policies>
</dd:node>
</dd:nodes>
<dd:profile id="profile_1">
```

In addition, for a node on which a locator is running, the value of the `ip` attribute can be an IP alias instead of an IP address, for example:

```
<dd:node name="1" ip="001my.intra.net" profile="profile_loc_1">
<dd:policies>
<dd:policy name="address_mode" value="ip" />
<dd:policy name="use_corbalocs" value="true" />
</dd:policies>
<dd:resource name="iiop" value="17701" />
<dd:resource name="iiop_secure" value="17702" />
</dd:node>
```

3. Finally, re-deploy the domain with the updated deployment descriptor:

```
itconfigure -nogui -load <deployment_descriptor_name_dd.xml>
```

Specifying Custom Certificates

The **Orbix Configuration** tool can process custom values for any substitution variables. These are variables that have been defined in the `substitute_vars` section of the XML files in your `install-dir/asp/version/etc/conf` directory. This section shows how to use substitution variables to specify custom security certificates. It includes the following:

- [Substitution variable file](#)
- [Using the GUI](#)
- [Using the command line](#)

Substitution variable file

When using substitution variables, you must pass a substitution variable file to `itconfigure`. This file contains replacement values for all defined substitution variables. This file should be specified in property file format, for example:

```

ROOT_TRUSTED_CA_LIST_POLICY="C:\\orbix\\custom_certs\\calist.pem"
ITADMIN_ADMIN_CERT_ROOT_DIR="C:\\orbix\\custom_certs"
SERVICES_AUTH_METHOD_DATA=["filename=C:\\orbix\\custom_certs\\
\\administrator.p12",
"password_file=C:\\orbix6\\custom_certs\\administrator.pwf"]
UTILITIES_AUTH_METHOD_DATA=["filename=C:\\orbix\\custom_certs\\
\\utilities.p12",
"password_file=C:\\orbix6\\custom_certs\\utilities.pwf"]
KDM_AUTH_METHOD_DATA=["filename=C:\\orbix\\custom_certs\\
\\kdmadministrator.p12",
"password_file=C:\\orbix6\\custom_certs\\kdmadministrator.pwf"]
KDM_CERT_CONSTRAINTS=["C=US,O=ABigBank*,CN=abc*", "C=US,O=ABigBank*,CN=xyz*"]
KDM_ADM_CERT_CONSTRAINTS=["C=US,O=ABigBank*,CN=abc*"]

```

Each value must be enclosed in quotes as shown in this example file.

Using the GUI

In the **Orbix Configuration** GUI tool, the **Substitutions** button is displayed at the bottom of the **Expert** panel (see [Figure 34 on page 54](#)). When the **Substitutions** button is clicked, this launches a dialog that enables you to enter the location of the substitution file.

Using the command line

On the command line, you can use the `-substitutions` option to pass the substitution file location to `itconfigure`, for example:

```
itconfigure -nogui -load descriptor -substitutions properties file
```

Warning

When using the `-substitutions` option to configure custom certificates for a deployed system, the substitutions file should *not* contain the pass phrase directly.

Instead, it should contain the location of the password files containing the pass phrases (see [Substitution variable file](#)).

Because the password file(s) stores the pass phrase in plain text, such files should not be readable by anyone except the administrator.

Orbix Deployment Descriptors

This section explains the data structure and grammar of the Orbix domain deployment descriptor.

Deployment Descriptor Structure

The Orbix domain deployment descriptor (`domain-name_dd.xml`) describes the contents of a configuration domain. This section outlines the overall structure of this file. It includes the following topics:

- [Document structure](#)
- [Recommended deployment descriptor generation](#)
- [Validating manual changes to a deployment descriptor](#)

Document structure

The `<domain-name>_dd.xml` file must conform to the following document structure:

Example 37: Deployment Descriptor Structure

	<pre><?xml version="1.0" encoding="UTF-8"?></pre>
[1] (#document-structure)	<pre><dd:descriptor> <!--This deployment descriptor version 1.0 has been generated by Orbix tools--></pre>
[2] (#document-structure)	<pre><dd:configuration> <dd:domain>domain-name</dd:domain> ... </dd:configuration> <!--Concrete node information for this deployment--></pre>

[3] (#document-structure)	<pre> <dd:nodes> <dd:node name="hostname" ip="ip-address" profile="hostname" <dd:resource name="some-resource" value="some- value" /> ... <dd:policies> <dd:policy name="some-policy" value="some-value" /> </dd:policies> ... </dd:node> ... </dd:nodes> </pre>
[4] (#document-structure)	<pre> <dd:feature id="feature-name"> <dd:resource type="directory" name="some-resource" / > </dd:feature> <!--The following profiles will be deployed--> </pre>
[5] (#document-structure)	<pre> <dd:profile id="hostname"> </pre>
[6] (#document-structure)	<pre> <dd:service name="service-name" ... > ... </dd:service> ... </pre>
[7] (#document-structure)	<pre> <dd:component /> ... </dd:profile> </dd:descriptor> </pre>

This deployment descriptor structure is described as follows:

1. The `<dd:descriptor>` element is the containing root element of the deployment descriptor XML vocabulary. It specifies an XML namespace named `dd`. This element indicates what version of the deployment descriptor XML vocabulary is being used. In this case, the absence of a version attribute indicates that this is version 1.0.
2. The `<dd:configuration>` element specifies the general configuration information for the domain (for example, its name, type, and location domain).

3. The `<dd:nodes>` element specifies information about the host machines included in the domain. Each `<dd:nodes>` element one or more `<dd:node>` element, one for each host machine. A `<dd:node>` element can include optional `<dd:resource>` and `<dd:policies>` elements. A `<dd:resource>` element specifies resources used by domain-level features; while `dd:policies` specifies policies that apply to all services on that node.
4. The `<dd:feature>` element specifies information about domain-level features.
5. The `<dd:profile>` element specifies a logical group of services and components that maps to a particular node.
6. The `<dd:service>` element specifies the details for a particular service (for example, the naming service).
7. The `<dd:component>` element specifies the details for a particular component (for example, Orbix demos). The difference between a component and a service is that services maintain live database information as part of the domain state, whereas a component does not.

These elements are described in more detail with examples in the sections that follow.

Recommended deployment descriptor generation

The recommended method of generating a deployment descriptor is to run the Orbix configuration tool on a GUI-enabled machine, and, if necessary, save the deployment descriptor for later use in command-line. Generating the descriptor in GUI mode ensures that the generated XML document is valid, and checked for dependencies.

Certain combinations of services and features are not permitted. For example, a descriptor that contains an indirect persistent, on-demand naming service, but no node-daemon, is invalid. Using different transports for different services is also invalid. Lastly, a descriptor with a node daemon that has secure endpoints only, and a locator with insecure endpoints only is not valid. This is because the locator would not be able to communicate with the node daemon.

Validating manual changes to a deployment descriptor

You can edit the domain deployment descriptor file to meet your requirements using any text editor. However, any changes you make must be checked for validity and dependencies.

Running the Orbix configuration tool enforces consistency on a deployment descriptor that has inconsistent relationships between services, or has incorrect container descriptions. You can validate manual changes to a deployment descriptor by running the following command:

```
itconfigure -nogui -load descriptor.xml -save somefile.xml
```

If the descriptor is correct, `descriptor.xml` and `somefile.xml` will be identical in structure. Otherwise, the configuration tool reports an error message, and exits without saving to the specified document (`somefile.xml`).

Domain Configuration Elements

This section explains the domain-specific information contained in an example deployment descriptor file. It includes the following topics:

- [Example descriptor](#)
- [Domain elements](#)

Example descriptor

The following extract from a deployment descriptor file named `my-domain_dd.xml` shows some example domain-specific elements:

Example 38: Domain-Specific Configuration

```
<?xml version="1.0" encoding="UTF-8"?>
<dd:descriptor>
<!--This deployment descriptor version 1.0 has been generated by Orbix
tools-->
<dd:configuration>
<dd:domain>my-domain</dd:domain>
<dd:source>file</dd:source>
<dd:location_domain>my-domain.location</dd:location_domain>
</dd:configuration>
<!--Concrete node information for this deployment-->
<dd:nodes>
<dd:node name="summer" ip="10.2.4.82" profile="summer" />
</dd:nodes>
<!--The following profiles will be deployed-->
<dd:profile id="summer">
...
</dd:profile>
</dd:descriptor>
```

Domain elements

The following table explains all the domain-specific elements:

Table 3: Domain-Specific Elements

Element	Description
<code><dd:descriptor></code>	Specifies the XML namespace details for the deployment descriptor.
<code><dd:configuration></code>	Specifies the general configuration information for the domain (for example, its name, type, and location domain)
<code><dd:domain></code>	Specifies the configuration domain name (in this case, <code>my-domain</code>).
<code><dd:source></code>	Specifies the configuration domain type. Can be either <code>file</code> , <code>cfr</code> , or <code>link</code> (<code>.cfg</code> text file, Configuration Repository, or a link domain).

Element	Description
<code><dd:location_domain></code>	<p>Specifies the location domain name. This takes the form <code>< domain-name >.location</code> (for example, my-domain.location).</p> <p>A location domain is a group of servers that are registered with the same locator daemon.</p>
<code><dd:nodes></code>	<p>This is a container for all host machines in a configuration domain that belong to the same <code>dns</code> domain. It has a single <code>dns</code> attribute (for example, <code>dns = "dublin.emea.myco.com"</code>).</p> <p>There can be multiple <code><dd:nodes></code> in one deployment descriptor. For example:</p> <pre><dd:nodes dns="dublin.emea.myco.com"> <dd:node name="summer" ip="10.2.4.82" profile="summer.dublin.emea.myco.com" /> <dd:node name="onion" ip="10.2.1.101" profile="onion.dublin.emea.myco.com" /> </dd:nodes> <dd:nodes dns="boston.amer.mycorp.com"> <dd:node name="jupiter" ip="10.5.3.18" profile="jupiter.boston.amer.mycorp.com" /> </dd:nodes></pre>
<code><dd:node></code>	<p>Specifies the identity of a particular host machine in the domain. It has three attributes:</p> <ul style="list-style-type: none"> - <code>name</code> specifies the hostname. - <code>ip</code> specifies the IP address. - <code>profile</code> specifies a logical group of services and components to deploy on the specified node. <p>A <code><dd:node></code> element can also include optional <code><dd:resource></code> and <code><dd:policies></code> elements.</p>
<code><dd:profile></code>	<p>Specifies a logical group of services and components. Its <code>id</code> attribute corresponds to the <code><dd:node profile></code> attribute. In this version of Orbix, only one profile per node is supported.</p>

Element	Description
<code><dd:feature></code>	<p>Specifies information about optional domain-level features. These are implemented separately from the deployer and invoked at the end of the deployment process. The following example is for integration with IBM Tivoli management:</p> <pre><dd:descriptor ... <dd:feature xmlns:dd="http://ns.iona.com/aspdd" id="tivoli-integration"> <dd:resource type="directory" name="configuration-files" /> </dd:feature> ... </ dd:descriptor></pre>
<code><dd:resource></code>	<p>Specifies resources used by domain-level features. For example:</p> <pre><dd:resource type="directory" name="configuration-files" /></pre> <p>This specifies a resource that is a file system directory named <code>configuration-files</code>.</p>

Element	Description
<code><dd:policies></code>	<p>As a child of the <code><dd:node></code> element, specifies policies that apply to all services on that node. Currently, there is only one available policy:</p> <p><code>address_mode</code> For example:</p> <pre><dd:nodes> <dd:node name="orion2" ip="10.2.1.101"> <dd:policies> <dd:policy name="address_mode" value="ip" /> </dd:policies> </dd:node> </dd:nodes></pre> <p>For more details on this example, see Conversion Process from Orbix 5.1 to an Orbix 6.x Descriptor.</p> <p>Policies can also be specified on a per-service bases (see Profile Configuration Elements). Service-specific policies override node-specific policies.</p>

Profile Configuration Elements

A profile specifies a group of configured services and components for a particular node. This section explains the profile-specific information contained in an example deployment descriptor file. It includes the following topics:

- [Example descriptor](#)
- [Service elements](#)
- [Service and component XML Files](#)

Example descriptor

The following is a complete listing of a deployment descriptor file named `my-domain_dd.xml`. It shows an entire profile configured for a default domain:

Example 39: Profile Configuration

```
<?xml version="1.0" encoding="UTF-8"?>
<dd:descriptor>
<!--This deployment descriptor has been generated by ASP tools-->
<dd:configuration>
<dd:domain>my-domain</dd:domain>
<dd:source>file</dd:source>
<dd:location_domain>my-domain.location</dd:location_domain>
</dd:configuration>
<!--Concrete node information for this deployment-->
<dd:nodes>
<dd:node name="summer" ip="10.2.4.83" profile="summer" />
</dd:nodes>
<!--The following profiles will be deployed-->
<dd:profile id="summer">
<dd:service name="locator">
<dd:activation mode="manual" />
<dd:run mode="direct_persistent" proxified="false"
managed="true" authenticated="false" />
<dd:endpoint protocol="iiop" port="3075" />
</dd:service>
```

```

<dd:service name="node_daemon">
<dd:activation mode="manual" />
<dd:run mode="direct_persistent" proxified="false"
managed="true" authenticated="false" />
<dd:endpoint protocol="iiop" port="53079" />
</dd:service>
<dd:service name="naming">
<dd:activation mode="on_demand" />
<dd:run mode="indirect_persistent" proxified="false"
managed="true" authenticated="false" />
<dd:endpoint protocol="iiop" port="0" />
</dd:service>
<dd:service name="management">
<dd:activation mode="manual" />
<dd:run mode="direct_persistent" proxified="false"
managed="true" authenticated="false" />
<dd:endpoint protocol="iiop" port="53085" />
<dd:endpoint protocol="http" port="53185" />
</dd:service>
<dd:component name="demos" />
</dd:profile>
</dd:descriptor>

```

Service elements

The following table explains the profile-specific elements

Table 4: Profile-Specific Elements

Element	Description
<code><dd:service></code>	Specifies the identity of a service. Its <code>name</code> attribute is the service name (for example, <code>locator</code>).

Element	Description
<code><dd:activation></code>	<p>Specifies how a service is activated. Its single <code>mode</code> attribute has the following possible values:</p> <ul style="list-style-type: none">- <code>manual</code> specifies that it must be activated using a start command or a script.- <code>on_demand</code> means that the node daemon starts the service when requested by a client.- <code>system_service</code> specifies that the service will be started at boot time. <p>On Windows, the service will be installed as an NT service.</p> <p>On Unix, appropriate run control scripts will be created. For more details, see the <i>Orbix Administrator's Guide</i>.</p>

Element	Description
<code><dd:run></code>	<p>Specifies how a service is run. It has the following attributes, all of which are optional:</p> <ul style="list-style-type: none"> - <code>mode</code> specifies whether the service uses the locator to resolve persistent object references (indirect persistence), or its IOR contains a well-known address for the server process (direct persistence). Possible values are <code>indirect_persistent</code> or <code>direct_persistent</code>. Defaults to <code>indirect_persistent</code>. - <code>proxified</code> specifies whether service is registered with the Firewall Proxy Server. Possible values are <code>true</code> or <code>false</code>. This attribute is optional. Defaults to <code>false</code>. - <code>managed</code> specifies whether service is registered with the management service. Possible values are <code>true</code> or <code>false</code>. Defaults to <code>false</code>. - <code>authenticated</code> specifies whether the service is registered with the security service. Possible values are <code>true</code> or <code>false</code>. Defaults to <code>false</code>. - <code>perflog</code> specifies whether the service is configured for performance logging. This is necessary for integration with Enterprise Management Systems (for example, IBM Tivoli). Possible values are <code>true</code> or <code>false</code>. Defaults to <code>false</code>. - <code>dynlog</code> specifies whether the service is configured for dynamic logging. For details on dynamic logging, see the <i>Orbix Administrator's Guide</i>.

Element	Description
<code><dd:endpoint></code>	<p>Specifies details of a service communication endpoint. It has three attributes:</p> <ul style="list-style-type: none"> - <code>protocol</code> specifies the protocol used by the service. Possible values are <code>iop</code> and <code>http</code>, as well as <code>fps<n></code>, where <code><n></code> is the number of the proxy group. The <code>fps<n></code> protocol is only used by the Firewall Proxy Service to indicate its proxy ports. - <code>port</code> specifies the port number used by the service (for example, <code>9000</code>). - <code>secure</code> specifies if the endpoint is secure. Values are <code>true</code> or <code>false</code>. A secure endpoint is one that includes TLS (Transport Layer Security). For example, if <code>secure="true"</code> is set on an endpoint where <code>protocol="http"</code>, a <code>https</code> endpoint is configured.
<code><dd:configuration></code>	<p>Specifies configuration overrides for the service. This enables you to change a small number of configuration settings in your domains, at the scope of a service, without modifying the shared description.</p> <pre><dd:service name="..." ... > <dd:configuration name="variable-name" value="value" action="set" stage="preprepare" /> <dd:configuration name="variable-name" action="unset" /> ... </dd:service></pre> <p>Available actions are <code>set</code> and <code>unset</code>. The default is <code>set</code>, so the <code>action</code> attribute can be omitted. Configuration overrides only change the value at the service instance scope.</p>

Element	Description
<code><dd:polices></code>	<p>Specifies information about any policy overrides for that service. Currently, there is only one available policy:</p> <p><code>address_mode</code> Specified values must match those already specified in the <code><dd:node></code> element (see Domain Configuration Elements).</p> <p>The following example shows policy overrides for address modes and ORB hostnames:</p> <pre><dd:service ... > <dd:policies> <dd:policy name="address_mode" value="ip" /> </dd:policies> </ dd:service></pre> <p>For more details on this example, see Conversion Process from Orbix 5.1 to an Orbix 6.x Descriptor.</p>
<code><dd:component></code>	<p>Specifies a component for the profile. It has a single <code>name</code> attribute. An example value is <code>demoss</code>.</p>

Service and component XML Files

`<dd:service>` and `<dd:component>` elements have corresponding XML source documents containing the data needed to deploy the configuration domain. Many of these XML source documents correspond to `orbix` services. Other XML documents contain core information that is needed for all configurations.

Note

These XML source documents are proprietary IONA documents. These XML source documents and their XML schema are not fully documented and subject to change without notice.

However, to enable you to write and use your own custom XML source documents, a subset of the schema is documented and supported. Custom XML files that comply with this partial schema will continue to work with future versions of Orbix, even though the overall schema may change. For details of the partial schema, see [Orbix Deployment DTD](#).

Orbix Deployment DTD

This appendix lists the supported DTD for the Orbix component XML templates. These XML template files are used to deploy Orbix components and services. The supported DTD is a subset of the complete DTD. Unsupported features are not documented.

Orbix Component Template Structure

The Orbix component XML template documents use a Document Type Definition (DTD) document to define the tags and values that make up the data and the structure the data takes. The DTD defining the configuration data is `ABDeploy.dtd`.

All XML documents used as source for an Orbix configuration must specify `ABDeploy.dtd` as its DTD, and conform to the structure it defines.

Warning

The schema for the Orbix deployer XML files is not fully documented. Only a subset of the complete DTD is supported and documented. Unsupported features are not documented, and are subject to change without notice.

ABDeploy.dtd

[Example 43](#) shows the subset the `ABDeploy.dtd` file that is supported by Rocket Software. This file defines the structure of configuration XML component templates.

Example 43: The DTD defining Orbix configuration source documents.

```
<!-- Application Builder Data Deployment Definition -->
<!ENTITY % ABDriver SYSTEM "ABDriver.dtd">
<!ENTITY % DynamicDriver SYSTEM "dynamic_deploy.dtd">
```

1	<pre> <!ELEMENT ABDeploy (service?, process?, section*)> <!ELEMENT configData (dataType, (dataValue?))> <!ATTLIST configData scope CDATA #IMPLIED> <!ELEMENT dataId (#PCDATA)> <!ELEMENT dataType (#PCDATA)> <!ELEMENT dataValue (#PCDATA)> </pre>
2	<pre> <!-- service --> <!ELEMENT service (data)> </pre>
3	<pre> <!-- process --> <!ELEMENT process (stage*)> </pre>
4	<pre> <!ELEMENT stage (source*)> <!ATTLIST stage action (populate prepare ntInstall ntUninstall removeReplica run templates filePopulate configPopulate populateHandler) #REQUIRED store (environment properties domain bootDomain adminDomain cfrDomain imr tmp) "domain" domain (domain cfrDomain adminDomain) "domain"> </pre>
5	<pre> <!ELEMENT source (file?, Dsection*)> <!ELEMENT file (#PCDATA)> </pre>
6	<pre> <!ELEMENT Dsection (#PCDATA)> <!ATTLIST Dsection os NMTOKENS #IMPLIED os_family (unix windows) #IMPLIED security (iiopOnly iiopTls tlsOnly is2_iiop is2_semi is2_tls) #IMPLIED </pre>
8	<pre> <!-- section --> <!ELEMENT section ((configScope configData)*)> <!ELEMENT configScope (dataId)> <!-- --> %DynamicDriver; %ABDriver; </pre>

The numbered elements in [Example 43](#) are explained as follows:

1. `<ABDeploy>` is the root element of every `Orbix` configuration document. It must be the first tag and is required for the document to be valid.

`<ABDeploy>` can contain one `<service>` element, `<process>` element, and any number of `<section>` elements.

2. `<service>` specifies information about a service that the deployer needs to deploy it.

This element must be present in custom XML files to satisfy the more general syntax. Aside from using its `id` attribute to identify the custom component for your own documentation purposes, it is of no further relevance to custom XML files.

3. `<process>` specifies when and how certain `<section>` elements are processed. Can contain any number of `<stage>` elements.

4. A `<stage>` element can reference one or multiple `section`s that can reside in one or more XML files. A `<stage>` element has one or more `<source>` elements.

The `action` attribute of the `stage` determines the target location of the configuration data processed in the `<stage>`. It decides where the configuration data specified in the `configData` elements in the stage's `section`s will be placed.

The attributes `store` and `domain` have default values.

Note

The values `filePopulate`, `configPopulate` and `populateHandler` for attribute `action` are now deprecated. They are still supported to protect investment in any custom XML files that may have been written against the former DTD, and map internally to the following combination of values for the `action` and `store` attributes:

Newly written custom XML files should use these combinations instead of the deprecated values.

A custom XML file's `<stage>` element should rarely have more than one `<section>` child element.

5. `<source>` has an optional attribute `file`, the value of which, if specified, indicates in which XML file the sections referred to in the CDATA of the `<Dsection>` child elements can be found. Custom XML files most likely specify their sections locally, so this attribute is not needed.
6. A `<source>` element can have one or several `<Dsection>` child elements.
7. A `<Dsection>` element is a reference to a set of `<configData>` elements which is itself contained in a `<section>`. The `Dsection`'s CDATA provides the mapping.

It is an error if a `<Dsection>` element references a `<section>` that cannot be found (in the local file, or in the file denoted by its parent source element).

While `DSection`s in XML files can have `constraint` attributes (meaning the data in the references sections is processed only if the constraint is met), custom XML files should not use these constraint attributes.

8. A `<section>` element is a container for a set of `<configScope>` and/or `<configData>` elements. It has one mandatory `name` attribute, which is used to map to `<Dsection>` elements appearing in the as child elements of a `<process>` element. A `<section>` element must contain at least one `<configScope>` or `<configData>` element.

`<section>` elements are used to support multiple installation and configuration scenarios.

Summary

In practice the full complexity described in [Example 43](#) is rarely needed. Most custom XML files will provide sufficient functionality if the following conditions are met:

- The `<process>` element contains one `<stage>` element (the `action` attribute of which is set to `configPopulate`).
- The `<stage>` element contains one `<source>` element, without the `file` attribute being set.
- The `<source>` element contains one `<Dsection>` element (without any attributes), and this `<Dsection>` element's CDATA is the same as the name of a `<section>` to be found further on in the document.
- The document contains one `<section>` element.
- The `<section>` element contains any number of `<configData>` elements.
- A `<configData>` element and its child elements hold the equivalent information to an `itadmin` `variable create` command—they specify variable scope, name, type and value(s).

Glossary

A

administration

All aspects of installing, configuring, deploying, monitoring, and managing a system.

ART

Adaptive Runtime Technology. A modular, distributed object architecture, which supports dynamic deployment and configuration of services and application code. ART provides the foundation for ORBIX software products.

ATLI2

Abstract Transport Layer Interface, version 2. The current transport layer implementation used in ORBIX.

C

Certificate Authority

Certificate Authority (CA). A trusted third-party organization or company that issues digital certificates used to create digital signatures and public-private key pairs. The role of the CA in this process is to guarantee that the individual granted the unique certificate is, in fact, who he or she claims to be. CAs are a crucial component in data security and electronic commerce because they guarantee that the two parties exchanging information are really who they claim to be.

CFR

See [configuration repository](#).

client

An application (process) that typically runs on a desktop and requests services from other applications that often run on different machines (known as server processes). In CORBA, a client is a program that requests services from CORBA objects.

configuration

A specific arrangement of system elements and settings.

configuration domain

Contains all the configuration information that Orbix ORBs, services and applications use. Defines a set of common configuration settings that specify available services and control ORB behavior. This information consists of configuration variables and their values. Configuration domain data can be implemented and maintained in a centralized Orbix configuration repository or as a set of files distributed among domain hosts. Configuration domains let you organize ORBs into manageable groups, thereby bringing scalability and ease of use to the largest environments. See also [configuration file](#) and [configuration repository](#).

configuration file

A file that contains configuration information for Orbix components within a specific configuration domain. See also [configuration domain](#).

configuration repository

A centralized store of configuration information for all Orbix components within a specific configuration domain. See also [configuration domain](#).

configuration scope

Orbix configuration is divided into scopes. These are typically organized into a root scope and a hierarchy of nested scopes, the fully-qualified names of which map directly to ORB names. By organizing configuration properties into various scopes, different settings can be provided for individual ORBs, or common settings for groups of ORB. Orbix services, such as the naming service, have their own configuration scopes.

CORBA

Common Object Request Broker Architecture. An open standard that enables objects to communicate with one another regardless of what programming language they are written in, or what operating system they run on. The CORBA specification is produced and maintained by the OMG. See also [OMG](#).

CORBA naming service

An implementation of the OMG Naming Service Specification. Describes how applications can map object references to names. Servers can register object references by name with a naming service repository, and can advertise those names to clients. Clients, in turn, can resolve the desired objects in the naming service by supplying the appropriate name. The Orbix naming service is an example.

CORBA objects

Self-contained software entities that consist of both data and the procedures to manipulate that data. Can be implemented in any programming language that CORBA supports, such as C++ and Java.

CORBA transaction service

An implementation of the OMG Transaction Service Specification. Provides interfaces to manage the demarcation of transactions and the propagation of transaction contexts. Orbix OTS is such a service.

CSIV2

The OMG's Common Secure Interoperability protocol v2.0, which can be used to provide the basis for application-level security in both CORBA and J2EE applications. The IONA Security Framework implements CSIV2 to transmit user names and passwords, and to assert identities between applications.

D**deployment**

The process of distributing a configuration or system element into an environment.

H**HTTP**

HyperText Transfer Protocol. The underlying protocol used by the World Wide Web. It defines how files (text, graphic images, video, and other multimedia files) are formatted and transmitted. Also defines what actions Web servers and browsers should take in response to various commands. HTTP runs on top of TCP/IP.

I**IDL**

Interface Definition Language. The CORBA standard declarative language that allows a programmer to define interfaces to CORBA objects. An IDL file defines the public API that CORBA objects expose in a server application. Clients use these interfaces to access server objects across a network. IDL interfaces are independent of operating systems and programming languages.

IFR

See [interface repository](#).

IIOP

Internet Inter-ORB Protocol. The CORBA standard messaging protocol, defined by the OMG, for communications between ORBs and distributed applications. IIOP is defined as a protocol layer above the transport layer, TCP/IP.

implementation repository

A database of available servers, it dynamically maps persistent objects to their server's actual address. Keeps track of the servers available in a system and the hosts they run on. Also provides a central forwarding point for client requests. See also [location domain](#) and [locator daemon](#).

IMR

See [implementation repository](#).

installation

The placement of software on a computer. Installation does not include configuration unless a default configuration is supplied.

Interface Definition Language

See [IDL](#).

interface repository

Provides centralized persistent storage of IDL interfaces. An Orbix client can query this repository at runtime to determine information about an object's interface, and then use the Dynamic Invocation Interface (DII) to make calls to the object. Enables Orbix clients to call operations on IDL interfaces that are unknown at compile time.

invocation

A request issued on an already active software component.

IOR

Interoperable Object Reference. See [object reference](#).

L**location domain**

A collection of servers under the control of a single locator daemon. Can span any number of hosts across a network, and can be dynamically extended with new hosts. See also [locator daemon](#) and [node daemon](#).

locator daemon

A server host facility that manages an implementation repository and acts as a control center for a location domain. Orbix clients use the locator daemon, often in conjunction with a naming service, to locate the objects they seek. Together with the implementation repository, it also stores server process data for activating servers and objects. When a client invokes on an object, the client ORB sends this invocation to the locator daemon, and the locator daemon searches the implementation repository for the address of the server object. In addition, enables servers to be moved from one host to another without disrupting client request processing. Redirects requests to the new location and transparently reconnects clients to the new server instance. See also [location domain](#), [node daemon](#), and [implementation repository](#).

N

naming service

See [CORBA naming service](#).

node daemon

Starts, monitors, and manages servers on a host machine. Every machine that runs a server must run a node daemon.

O

object reference

Uniquely identifies a local or remote object instance. Can be stored in a CORBA naming service, in a file or in a URL. The contact details that a client application uses to communicate with a CORBA object. Also known as interoperable object reference (IOR) or proxy.

OMG

Object Management Group. An open membership, not-for-profit consortium that produces and maintains computer industry specifications for interoperable enterprise applications, including CORBA. See www.omg.com.

ORB

Object Request Broker. Manages the interaction between clients and servers, using the Internet Inter-ORB Protocol (IIOP). Enables clients to make requests and receive replies from servers in a distributed computer environment. Key component in CORBA.

OTS

See [CORBA transaction service](#).

P

POA

Portable Object Adapter. Maps object references to their concrete implementations in a server. Creates and manages object references to all objects used by an application, manages object state, and provides the infrastructure to support persistent objects and the portability of object implementations between different ORB products. Can be transient or persistent.

protocol

Format for the layout of messages sent over a network.

S

server

A program that provides services to clients. CORBA servers act as containers for CORBA objects, allowing clients to access those objects using IDL interfaces.

SSL

Secure Sockets Layer protocol. Provides transport layer security—authenticity, integrity, and confidentiality—for authenticated and encrypted communications between clients and servers. Runs above TCP/IP and below application protocols such as HTTP and IIOP.

SSL handshake

An SSL session begins with an exchange of messages known as the SSL handshake. Allows a server to authenticate itself to the client using public-key encryption. Enables the client and the server to co-operate in the creation of symmetric keys that are used for rapid

encryption, decryption, and tamper detection during the session that follows. Optionally, the handshake also allows the client to authenticate itself to the server. This is known as mutual authentication.

T

TCP/IP

Transmission Control Protocol/Internet Protocol. The basic suite of protocols used to connect hosts to the Internet, intranets, and extranets.

TLS

Transport Layer Security. An IETF open standard that is based on, and is the successor to, SSL. Provides transport-layer security for secure communications. See also [SSL](#).

Notices

Copyright

© 1996-2025 Rocket Software, Inc. or its affiliates. All Rights Reserved.

Trademarks

Rocket is a registered trademark of Rocket Software, Inc. For a list of Rocket registered trademarks go to: www.rocketsoftware.com/about/legal. All other products or services mentioned in this document may be covered by the trademarks, service marks, or product names of their respective owners.

Examples

This information might contain examples of data and reports. The examples include the names of individuals, companies, brands, and products. All of these names are fictitious and any similarity to the names and addresses used by an actual business enterprise is entirely coincidental.

License agreement

This software and the associated documentation are proprietary and confidential to Rocket Software, Inc. or its affiliates, are furnished under license, and may be used and copied only in accordance with the terms of such license.

Note: This product may contain encryption technology. Many countries prohibit or restrict the use, import, or export of encryption technologies, and current use, import, and export regulations should be followed when exporting this product.

Corporate information

Rocket Software, Inc. develops enterprise infrastructure products in four key areas: storage, networks, and compliance; database servers and tools; business information and analytics; and application development, integration, and modernization.

Website: www.rocketsoftware.com

Contacting Technical Support

The Rocket Community is the primary method of obtaining support. If you have current support and maintenance agreements with Rocket Software, you can access the Rocket Community and report a problem, download an update, or read answers to FAQs. To log in to the Rocket Community or to request a Rocket Community account, go to www.rocketsoftware.com/support. In addition to using the Rocket Community to obtain support, you can use one of the telephone numbers that are listed above or send an email to support@rocketsoftware.com.

Rocket Global Headquarters
77 4th Avenue, Suite 100
Waltham, MA 02451-1468
USA

Country and Toll-free telephone number

To contact Rocket Software by telephone for any reason, including obtaining pre-sales information and technical support, use one of the following telephone numbers.

- United States: 1-855-577-4323
- Australia: 1-800-823-405
- Belgium: 0800-266-65
- Canada: 1-855-577-4323
- China: 400-120-9242
- France: 08-05-08-05-62
- Germany: 0800-180-0882
- Italy: 800-878-295
- Japan: 0800-170-5464
- Netherlands: 0-800-022-2961
- New Zealand: 0800-003210
- South Africa: 0-800-980-818
- United Kingdom: 0800-520-0439