

## CORBA Trader Service Guide C++

V6.3.14

### **Table of Contents**

Preface	9
Audience	9
Related documentation	9
Typographical conventions	10
Keying conventions	10
An Introduction to the CORBA Trading Service	12
Introduction	12
How clients and servers use a trader	12
Scalability	13
Service Types	13
Service type definition	13
Service type names	14
Interface types	14
Property types	14
Super types	15
Service Offers	16
Service offers	16
The Trader Service's Components	17
Trader components	17
Configuring the Trader Service	19
Configuring and Running the Trader Service	19
Preparatory steps	19
Explanation	20
Steps 1-2: Determine the hosts and ports to be used in the deployment	20
Step 3: Enter the host and port information in the configuration	20
Step 4: Configure the service to run with or without replication	22
Step 5: Run the service in prepare mode to obtain initial references	22
Step 6: Adding the initial references to the configuration	23

Step 7: Running the trader service	
Additional Configuration Information	
Getting Started with the Trader Service	25
Starting the Trader Service	25
Synopsis	25
Stopping the Trader Service	25
The Printer Application	26
Interaction with the trader	26
The IDL specification	27
Trader Service Programming	27
Connecting to the Trader	28
Adding a New Service Offer Type	28
Exporting a Service Offer	30
Querying for a Service Offer	32
Querying for Service Offers	34
How the Trader Service Processes a Query	34
Format of a query	34
Policies	35
A Basic Query for Service Offers	35
Connecting to the trader	35
Querying the trader	36
Selecting a Service from Query Results	37
Output parameters	37
offers	
iterator	38
limits_applied	39
Forming Constraints for Queries	39
Evaluating property values	40
Combining expressions	41
Testing for a property's existence	41

Using arithmetic expressions	42	
Setting Preferences to Sort Service Offers	42	
Creating a preference string	42	
Constructing preference expressions	42	
Returning offers in the order of discovery	43	
Returning offers in descending order	43	
Returning offers in ascending order	43	
Returning offers by constraint	44	
Returning offers in random order	44	
Refining the Properties a Query Returns	44	
Specifying returned properties	44	
Understanding Trader Service Policies	47	
What is a policy?	47	
Policies that Affect Queries	47	
Query semantics	47	
Search policies	48	
Return policy	48	
List of query policies	49	
Policies that Affect Trader Functionality	50	
Evaluating policies	50	
Query policies	50	
Using Policies in a Query	51	
Policies parameter		
Creating a policy list		
Policy types	52	
Setting a Trader's Global Policies	53	
Setting global policies	53	
Global policies	53	
Exporting and Managing Service Offers	55	
Server tasks	55	
Environment	55	

Initializing Service Offer Properties	56
Property structure	56
Getting an offer type's property list	56
Read-only and mandatory properties	57
Exporting a Service Offer to Trader	57
Synopsis	58
Example	58
Getting Service Offer Data from Trader	59
Reviewing offer information	59
Modifying a Service Offer	60
Using modify()	60
Example	60
Readonly properties	61
Policy for supporting modifiable properties	61
Withdrawing a Service Offer from Trader	61
Programming Topics	63
Managing the Service Type Repository	63
Creating service type properties	63
Adding a service type	65
Managing service types	66
Using Dynamic Property Values	66
Dynamic property values	66
Exporting a dynamic property value	66
Using a dynamic property value	68
Allowing dynamic properties	69
Managing Links Between Traders	69
Linked traders	69
Setting policies for linked traders	69
Adding links	71
Removing links	72

Creating lists of links	73
rader Service Console	74
Starting the Trader Console	74
How to start the console	74
Main Window	74
GUI appearance	75
Window elements	75
The Toolbar	76
Terms used in Trader Console	76
The Trader Console Menus	77
The Console menu	77
The Edit menu	77
Using the cut, copy and paste commands	78
Using the Clone and Modify commands	78
The View menu	78
The Insert menu	79
The Tools menu	79
Managing Service Types	79
IDL type support	79
Adding a new service type	79
Removing a service type	82
Masking a service type	82
Unmasking a service type	82
Managing Offers	83
Adding a new offer	83
Modifying an offer	85
Withdrawing offers	86
Managing Proxy Offers	87
Adding a new proxy offer	87

Withdrawing proxy offers	88
Managing Links	89
Adding a new link	89
Modifying a link	90
Removing a link	90
Configuring the Trader Attributes	90
Configuring attributes	90
Support Attributes	91
Import Attributes	92
Link Attributes	94
Admin Attributes	95
Admin attributes	95
Request identifier stem	95
Executing Queries	96
Executing a query	96
Connecting to a New Trader	98
he OMG Constraint Language	100
Introduction	100
Statement	100
Language Basics	100
Basic elements	100
Precedence relations	101
Legal property value types	102
Operator restrictions	102
Representation of literals	103
The Constraint Language BNF	103
The constraint language proper in terms of lexical tokens	103
"BNF" for lexical tokens up to character set issues	105
Character set issues	105
lossary	107

Notices	111
Copyright	111
Trademarks	111
Examples	111
License agreement	111
Corporate information	112
Contacting Technical Support	112
Country and Toll-free telephone number	112

### 1. Preface

CORBA Trader Service is a Java implementation of the Object Management Group (OMG) Trading Service. The CORBA Trader Service provides facilities for object location and discovery. Unlike the CORBA Naming Service where an object is located by name, an object in the Trading Service does not have a name. Rather, a server advertises an object in the Trading Service based on the kind of service provided by the object. A client locates objects of interest by asking the Trading Service to find all objects that provide a particular service. The client can further restrict the search to select only those objects with particular characteristics.

The Trader Service is compliant with the OMG CORBA services: Common Object Services Specification ftp://www.omg.org/pub/docs/formal/98-12-09.pdf) and conforms to the specification's definition of a *full-service trader*, meaning that the service supports all of the functionality described in the specification.

### **1.1 Audience**

This manual is aimed at users wanting to create a trader service for use by their applications.

### **1.2 Related documentation**

The document set for Orbix includes the following:

- CORBA Programmer's Guide
- Administrator's Guide
- CORBA Programmer's Reference

### 1.3 Typographical conventions

This guide uses the following typographical conventions:

Constant width	Constant width (courier font) in normal text represents portions of code and literal names of items such as classes, functions, variables, and data structures. For example, text might refer to the CORBA::Object class.
	Constant width paragraphs represent code examples or information a system displays on the screen. For example:
	<pre>#include <stdio.h></stdio.h></pre>
Italic	Italic words in normal text represent <i>emphasis</i> and <i>new terms</i> .
	Italic words or characters in code and commands represent variable values you must supply, such as arguments to commands or path names for your particular system. For example:
	% cd /users/*your_name* !!! note Some command examples may use angle brackets to represent variable values you must supply. This is an older convention that is replaced with <i>italic</i> words or characters.

### **1.4 Keying conventions**

This guide may use the following keying conventions:

No prompt	When a command's format is the same for multiple platforms, a prompt is not used.
%	A percent sign represents the UNIX command shell prompt for a command that does not require root privileges.
#	A number sign represents the UNIX command shell prompt for a command that requires root privileges.
>	The notation > represents the DOS or Windows command prompt.

	Horizontal or vertical ellipses in format and syntax descriptions indicate that material has been eliminated to simplify a discussion.
[]	Brackets enclose optional items in format and syntax descriptions.
{}	Braces enclose a list from which you must choose an item in format and syntax descriptions.
	A vertical bar separates items in a list of choices enclosed in { } (braces) in format and syntax descriptions.

# 2. An Introduction to the CORBA Trading Service

The Trader Service is a full implementation of the CORBA Trading Object Service. With this service, servers can offer functionality by making a number of objects publicly available. Clients can then get references to objects that match a specified functionality.

### 2.1 Introduction

The CORBA Trader Service is a Trading Object Service that allows an object to be registered with a description of its functionality. This service greatly increases the scalability of distributed systems by making services easier to locate. An example of a service that a client might search for is a printer.

### 2.1.1 How clients and servers use a trader

A trader contains a number of *service types* that describe a service. For example, a printer service type might have properties such as pages\_per\_minute (a long) and location (a string). Service types are stored in a Service Type Repository. Service offers, or offers, are instances of these service types.



Figure 1: Typical trading service process

A server can export an offer to the trader, which includes an object reference for one of its objects and values for properties defined by the service type, for example, "50 pages per minute, located on the first floor".

A client can then query the trading service based on these properties using a filter called a *constraint*. For example, a client could search for a printer where "pages\_per\_minute > 200". The trader then returns to the client an offer of a service. The client can then use the object reference in the offer to invoke on the server.

### 2.1.2 Scalability

The trader can be a tool for constructing efficient distributed applications. The advantage of annotating a service offer with properties, and allowing offers to be filtered on the basis of those properties using a constraint, is that clients can select offers without having to incur the overhead of invoking operations on each object.

For example, suppose that Printer2Interface, which is a subclass of PrinterInterface, has an additional operation, cost(), which returned a value of type float:

```
//IDL
interface Printer2Interface : PrinterInterface {
void page_counter();
float cost();
};
```

In this situation, if the importer needed to select only those printers whose cost is within a certain range, the importer would need to iterate over each printer returned by the trading service to invoke the <code>cost()</code> operation. In a distributed environment, the overhead of this activity could be prohibitively expensive. It is the developer's responsibility to anticipate the types of queries that importers will need to perform and design their service types accordingly.

### 2.2 Service Types

### 2.2.1 Service type definition

Service types are general descriptions of a kind of service. They consist of the following:

- A *type name* (for example, *printer*) uniquely identifies the service type.
- An *interface type* defines the IDL interface to which an advertised object of this type must conform (for example, "IDL:MyAppModule/MyAppInterface:1.0").
- A collection of *property types* defines additional attributes of the service offer (for example, *"long page\_per\_min"*, *"string location"*).

### 2.2.2 Service type names

Each service type in the repository has a unique name. Orbix Trader supports two name formats:

- Scoped names These names have formats such as :: One:: Two. Other supported variations include Three::Four and simply Five.
- **Interface repository identifiers** These names adhere to the format of interface repository identifiers. The most common format is

IDL:[prefix/][Module/]Interface:X.Y

#### **Note**

Although both naming formats follow interface repository conventions, service type names are never used to look up information in the interface repository.

### 2.2.3 Interface types

An *interface type* describes the IDL signature of the advertised service. The interface type is a string whose format should be a scoped name or an interface repository identifier as described above for service type names. When a new service is exported, the trader may use the interface repository to confirm that the object being advertised *conforms* to the interface defined by the interface type. An object conforms to an interface if it implements that interface, or if it implements a subclass of that interface.

### 2.2.4 Property types

A service type can have zero or more *property types*, representing additional information that can be associated with an advertised service.

A property type definition consists of a name, a value type and a mode. The value type is a CORBA::TypeCode, and the mode indicates whether a property is mandatory and whether it is read-only.

The property modes have the following semantics:

- Mandatory—The exporter must provide a value for the property at the time the service is exported. Mandatory properties cannot be removed.
- Read-only—Once an exporter has supplied a value for the property, it cannot be modified. Readonly properties can be removed.

• Mandatory and Read-only—The property must have a value when the service is exported, and cannot subsequently be changed or removed.

A property that is neither mandatory nor read-only is considered optional, and can be changed and removed.

Orbix Trader accepts Java-style identifiers as property names, meaning a property name must start with a letter, and may consist of letters, numbers and underscores.

### 2.2.5 Super types

Service types can *inherit* from other service types, which enables the definition of *super types* that encapsulate behavior and characteristics common to many service types. When a new service type is created that has super types, the trader checks that several prerequisites are met:

- 1. All super types must already exist in the service type repository.
- 2. Any property type definitions in the new service type that have the same name as a definition in a super type must be compatible with the super type definition. For two property definitions to be compatible, their value types must match, and the mode of the new definition must be the same as, or stronger than, the mode of the property in the super type according to the graph in Figure 2.

Figure 2: Property Mode Strengths



3. The interface type of the new service type must conform to the interface type of all super types. Orbix Trader may use the interface repository to verify that this is true.

For example, consider two IDL interfaces, InterfaceA and InterfaceB, defined below:

```
// IDL
interface InterfaceA {
void do_something();
};
interface InterfaceB : InterfaceA {
void do_something_else();
};
```

Here, InterfaceB inherits from InterfaceA. Now, let's define two service types:

```
service ServiceTypeA
{
interface InterfaceA;
property string name;
};
service ServiceTypeB : ServiceTypeA
{
interface InterfaceB;
mandatory property string name;
readonly property float cost;
};
```

In the example above, ServiceTypeB inherits from ServiceTypeA. As such, it inherits all of the property types from ServiceTypeA, and declares an interface type of InterfaceB, which conforms to the interface type of its super type because InterfaceB is a subclass of InterfaceA.

Notice that ServiceTypeB redefines the mode of the "name" property. Whereas the definition in ServiceTypeA does not specify a mode (making the property optional), the definition in ServiceTypeB makes this property mandatory, therefore a value for the property must be supplied when the offer is exported. The reverse is not allowed; a subtype cannot redefine a mandatory property to be optional.

ServiceTypeB also adds a new property, "cost", which is defined to be read-only. Because the property is not mandatory, an exporter does not need to supply a value for it at the time a service offer is exported. However, once a value has been defined for this property, it cannot subsequently be changed.

### 2.3 Service Offers

### 2.3.1 Service offers

A *service offer* is an instance of a service type and represents the advertisement of a service by a service provider.

A service offer has the following characteristics:

- A service type name associates the offer with a particular service type.
- An *object reference* provides the "pointer" (the object reference) to the advertised object that is necessary for clients to invoke the service being offered.
- A set of *properties* describe this service offer and must conform to the property types defined by the service type.

The trader uses the definition of the specified service type to perform several validation steps on a new offer:

- 1. The exporter must provide values for all mandatory properties (including all mandatory properties that the service type inherits from its super types, if any).
- 2. The object must conform to the interface type defined by the service type. Orbix Trader may use the interface repository to verify that this is true.
- 3. The value types of all properties must match the value types as defined by the service type. For example, a value of type double is not allowed for a property whose type is defined as string in the service type.

#### **Note**

Orbix Trader allows an exporter to supply values for named properties that are not defined in the service type.

The value of a property in a service offer can be modified if the mode of the property is not read-only. A property can be removed from a service offer if the property is not mandatory. New properties can also be added to an existing service offer.

### 2.4 The Trader Service's Components

### 2.4.1 Trader components

The Trader Service functionality is divided into components where each component has an associated interface as follows:

- Lookup
- Register
- Admin
- Link
- Proxy

The CORBA Trader Service is a full-service implementation of the OMG's Trading Object Service specification. The following table summarizes the different kinds of traders and the component functionality offered:

Kind of Trader	Component Interfaces				
	Lookup	Register	Admin	Link	Proxy
Full-Service	CORBA Trader Service				
Linked	Х	Х	Х	Х	
Proxy	Х	Х	Х		Х
Stand-alone	Х	Х	Х		
Simple	Х	Х			
Query	Х				

Table 1 Kinds of traders and their components

The functionality of each kind of trader depends on the interfaces that it supports. The following is a list of the kinds of traders specified by the OMG:

- The simplest trader is the *Query trader*, which just supports the Lookup interface. This could be useful, for example, where a trader is pre-loaded and optimized for searching.
- The *simple trader* supports not only the Lookup interface but it also supports exporting of offers with the Register interface.
- The *stand-alone trader* supports the interfaces of a simple trader and additionally supports administration of the trader's configuration settings using the Admin interface.
- The *proxy trader* supports the interfaces of a stand-alone trader and additionally supports the Proxy interface. The proxy trader essentially exports a *lookup* interface for delayed evaluation of offers, and can be used for encapsulating legacy applications, or as a kind of service offer factory.
- The *linked trader* supports the interfaces of a stand-alone trader and additionally supports federation of traders using the Link interface.
- The *full-service trader* combines the functionality of all component interfaces. The Orbix CORBA Trader Service is a full-service trader.

### 3. Configuring the Trader Service

This section provides a description of the steps necessary to configure the Trader Service.

### 3.1 Configuring and Running the Trader Service

These instructions describe how to configure the Trader Service.

### 3.1.1 Preparatory steps

Several preparatory steps are necessary to configure and run the trader service. The specific actions taken at each step are somewhat different depending on whether you want to run the service replicated or non-replicated.

The general sequence of actions are as follows:

- 1. Determine on which hosts you want to run the master trader service and on which hosts any slaves will run.
- 2. Determine the port number on which the master, slaves, and Replicators will listen.
- 3. Enter the host and port number information into the configuration.
- 4. Configure the trader service to run in replicated or non-replicated mode.
- 5. Run the trader service in "prepare" mode to obtain initial references needed to enable clients to interact with the service.
- 6. Add each of the references obtained during step 4 to the configuration database.
- 7. Start the master trader service and any slaves.

### 3.1.2 Explanation

In the following explanation of the steps listed above, example settings are given assuming a deployment of one master trader service instance running on host "master", and one slave trader service instance running on host "slave". In addition, it will be pointed out where steps should be modified or bypassed in order to run a single non-replicated instance of the service.

## 3.1.3 Steps 1-2: Determine the hosts and ports to be used in the deployment

These steps are completely deployment-specific. Depending on the number of trader service instances you want to deploy, you will need to select 1 or more distinct host/port pairs for each instance of the service to use as a communication end-point. In our example, we use a replicated service with one master and one slave. The master runs on host master and listens on port 15001; the slave runs on host slave and listens on port 15001. The master and slave need not listen on the same port number. Also, two or more replicas may run on the same host as long as they listen on different ports.

Furthermore, each trader service instance running in a replicated deployment scenario will also create a *Replicator* object. You must also select the ports on which each Replicator will listen. In the sample configuration, the Replicator always listens on port 15002.

## 3.1.4 Step 3: Enter the host and port information in the configuration

The Trader Service configuration will contain variables set in a global scope (the outer scope not contained within a named block), and variables set in one or more named scopes. The global scope specifies configuration variable settings for all replicas in a replicated deployment, while the named scopes each specify configuration variable settings that apply to a specific trader service instance. The name of each scope corresponds to the ORB name that will be used when launching each instance of the service.

In the default trader.cfg included with the trader service package, there are two named scopes: one for ORB name trading0, and the other for ORB name trading1. All host/port information is set within a named configuration scope.

The host/port information within a given configuration scope is contained in the following variables:

```
trader:iiop:addr_list
replication:Replicator:iiop:addr_list
```

In the sample configuration, these variables are set as follows in the trading scope:

```
trader:iiop:addr_list = ["master:15001", "+slave:15001"];
replication:Replicator:iiop:addr_list = ["master:15002"];
```

These settings indicate that the trader service instance using ORB name trading@ will run on host master and listen on port 15001. The service will be replicated, with the one replica participating in the service running on host slave and listening on port 15001. The Replicator will listen on port 15002.

Note that if more replicas are being used in the deployment, an additional "+<hostname>:<port>" pair would be appended to the list for each replica. If running the service non-replicated, only a single "<hostname>:<port>" pair should be included in the trader:iiop:addr\_list. Including additional pairs in the list will only increase the size of IORs used by the service, but this will result in unnecessary resource consumption when running non-replicated. In addition, in the non-replicated case, the second addr\_list variable listed above need not be set.

In the sample configuration, these same variables are set as follows in the trading1 configuration scope:

```
trader:iiop:addr_list = ["slave:15001", "+master:15001"];
replication:Replicator:iiop:addr_list = ["slave:15002"];
```

These settings indicate that the trader service instance run with ORB name trading1 will run on host slave and listen on port 15001. The service will be replicated, and the one other replica will run on host master and also listen on port 15001. The Replicator used by this service instance will listen on port 15002.

## 3.1.5 Step 4: Configure the service to run with or without replication

Before running the trader service in "prepare" mode, you should decide if you want to run with replication enabled or disabled, and if replication is enabled how many replicas will be used.

Whether replication is enabled or disabled is controlled by the setting of the configuration variable replication:enable. This variable should be set to "True" to enable replication, and to "False" to disable replication.

If running with replication enabled, you must also indicate the number of replicas that will be used by setting the replication:replica\_count to the appropriate value. This variable should be set to the total number of replicas including the master and any slaves. In the example scenario with one master trader service instance and one slave, this variable should be set to 2.

## 3.1.6 Step 5: Run the service in prepare mode to obtain initial references

Now you are ready to run the service in prepare mode, and obtain the initial references necessary for clients to connect to the service. Note that when running a replicated service, each individual replica must be prepared. The command to run the trader service in prepare mode is:

asp/\*Version\*/bin/ittrader prepare [-publish\_to\_file <filename>]

If running with replication enabled, preparing each instance of the trader service will result in three IORs being sent to standard output:

- The IOR of the replicated trader service (which will be the same for all replicas)
- The non-replicated, per-instance trader service IOR
- The IOR of the per-trader service Replicator.

If running with replication disabled only the IOR of the prepared trader service instance will be output.

Save the values for use in step 6.

### 3.1.7 Step 6: Adding the initial references to the configuration

The initial references of each trader service instance and each Replicator need to be added to the configuration.

If running one non-replicated instance of the service, the initial reference to the service returned by preparing the one instance should be set as the value of the following variable in the global configuration scope:

```
initial_references:TradingService:reference
```

If running with replication enabled, the IOR of the *replicated* trader service should be set as the value of the trader service initial reference in the global scope (the same variable as described above for the non-replicated case).

If replication is enabled, or if running multiple non-replicated instances of the service within the same domain, the trader service initial reference variable within each named scope must also be set. If replication is enabled, the value set for the following variable within each named scope should be the non-replicated, per-instance trader service IOR:

initial\_references:TradingService:reference

In addition, the non-replicated IOR of each trader service instance, along with the Replicator IOR for each instance, should be added to the configuration as the values of the variables of the form:

```
replication:replica:<replica id>:TradingService:reference
replication:replica:<replica id>:Replicator:reference
```

In the current example, the IORs returned by preparing the master replica are set as the values of the following variables:

```
replication:replica:0:TradingService:reference
replication:replica:0:Replicator:reference
```

while the IORs returned by preparing the slave replica are set as the values of these variables:

```
replication:replica:1:TradingService:reference
replication:replica:1:TradingService:reference
```

### 3.1.8 Step 7: Running the trader service

To start the trader, enter the command:

ittrader run

### **3.2 Additional Configuration Information**

There are some additional configuration settings to be aware of:

trader:database:dir="./traderdb0";

This variable should be modified, for each replica of the service, to contain the pathname (absolute or relative to where the trader is launched from) of where the trader database will reside.

```
replication:replica_id = "0";
```

This is a numeric ID for the instance of the trader being configured in the current scope.

Each replica should have a unique replica\_id. If a replica's replication:replica\_id is the same value as replication:master then it is the master replica.

#### direct\_persistence

This variable specifies if the service runs using direct or indirect persistence. The default value is FALSE, meaning indirect persistence.

#### iiop:port

This variable specifies the port that the service listens on when running using direct persistence.

### 4. Getting Started with the Trader Service

This section shows an example of a simple printer service to illustrate most of the common functionality in the Trader Service. A printer server makes a printer available for general use. Then, a client application asks the Trader Service for a suitable printer, and uses it to print a document.

### 4.1 Starting the Trader Service

To start the trader, enter the command:

ittrader run

### 4.1.1 Synopsis

```
ittrader [-launcher_help]
[-ORBconfig_dir config_dir_value]
[-ORBconfig_domains_dir config_domains_dir_value] [-ORBdomain_name
domain_name_value]
[-ORBproduct_dir product_dir_value]
[-ORBlicense_file license_file]
[-bg | -background]
[-bg | -background]
[-version]
[run | prepare [publish_to_file = filename]
```

### 4.1.2 Stopping the Trader Service

Enter the command:

itadmin trd\_admin stop

### **4.2 The Printer Application**

The print server creates a Printer service type, and exports the descriptions of several printers to the trader. A client allows the user to execute queries and "print" files.

### 4.2.1 Interaction with the trader

Figure 3 shows the typical interactions clients and servers have with the trader:

Figure 3: Typical Interactions with the trader



- 1. An offer server adds a service type (Printer) to the trader. The Printer type describes properties that office printers have, such as pages per minute. The service type names differ from the IDL interface names in this example, mainly to make their use clearer. For example, there could also be a book\_printer service type that uses the PrintServer IDL interface, but it could have quite different properties such as options for hard or soft book binding.
- 2. The printer server creates a printer\_if object. It exports and object reference to this object to the Trader Service as an *offer* of type Printer. It then waits for incoming requests, as normal.
- 3. The client process queries the Trader Service for a Printer offer.
- 4. The client process then uses the object reference in the offer obtained to invoke the printer server.

### 4.2.2 The IDL specification

The example application uses the following PrintServer IDL interface to describe the interface to a printer object:

```
// IDL
// This interface represents a print server that manages queues
// for several printers.
//
module TraderDemo
{
    interface PrintServer
    {
      typedef unsigned long JobID;
      // Add a file to a printer's queue.
      //
      JobID print (in string queue, in string file);
    };
};
```

### 4.3 Trader Service Programming

This section outlines the three major programming steps used to interact with the trader. These steps are:

1. Add a service type using the offer server:

Create a service offer type if a corresponding one doesn't already exist within the Trader Service. This example creates an Printer service offer type.

2. Register a service offer using the printer server:

Create an object, for example, an instance of the IDL interface PrintServer.

Register the object reference with the Trader Service, within a service offer of type Printer. The server then accepts incoming object invocations as normal.

3. Get a service offer using the client:

Query the Trader Service to get back a service offer.

Use the object reference specified in the service offer to invoke the object on the server.

Note that for simplicity, exception handling is omitted in the sample code.

### 4.3.1 Connecting to the Trader

Servers need to connect to the trader to add a service offer type, for example, or to register a service offer. Clients need to connect to query the trader for service offers. The trader has a number of components represented by IDL interfaces including Lookup, Register, and others. The "TradingService" initial reference is a reference to the CosTrading::Lookup interface.

Do the following steps to get an object reference to the Trader Service:

<pre>[1](#connecting-to-the- trader)</pre>	<pre>CORBA::Object_var obj = orb- &gt;resolve_initial_references("TradingService" );</pre>
<pre>[2](#connecting-to-the- trader)</pre>	<pre>CosTrading::Lookup_var trader; if (!CORBA::is_nil(obj)) { trader = CosTrading::Lookup::_narrow(obj); }</pre>

1. Call resolve\_initial\_references() which returns a CORBA::Object\_ptr.

2. Narrow the object reference.

### 4.3.2 Adding a New Service Offer Type

An offer server inserts a service offer type called printer into the Trader Service. This is essentially a type declaration of an offer. Other servers may then use this type to register printer objects by creating instances of this type. Operations on service offer types are handled by the Service Offer Type Repository component of the Trader Service.

Do the following steps to add an offer type to the Offer Type Repository:

<pre>[1](#adding-a-new- service-offer-type)</pre>	<pre>CosTrading::TypeRepository_var type_obj = trader-&gt;type_repos();</pre>
<pre>[2](#adding-a-new- service-offer-type)</pre>	<pre>CosTradingRepos::ServiceTypeRepository_var trader_repos_obj = CosTradingRepos::ServiceTypeRepository::_narrow( type_obj);</pre>

[3](#adding-a-new-	CosTradingRepos::ServiceTypeRepository::PropStr
<pre>service-offer-type)</pre>	uctSeq_var
	properties = new
	CosTradingRepos::ServiceTypeRepository::PropStr
	uctSeq;
	<pre>properties-&gt;length(3);</pre>
	<pre>properties[0].name = (const char *) "name";</pre>
	<pre>properties[0].value_type = CORBA::_tc_string;</pre>
	<pre>properties[0].mode =</pre>
	CosTradingRepos::ServiceTypeRepository::PROP_MA
	NDATORY_READONLY;
	<pre>properties[1].name = (const char *) "location";</pre>
	<pre>properties[1].value_type = CORBA::_tc_string;</pre>
	<pre>properties[1].mode =</pre>
	CosTradingRepos::ServiceTypeRepository::PROP_MA
	NDATORY;
	<pre>properties[2].name = (const char</pre>
	*)"page_per_min";
	<pre>properties[2].value_type = CORBA::_tc_long;</pre>
	<pre>properties[2].mode =</pre>
	CosTradingRepos::ServiceTypeRepository::PROP_NO
	RMAL;
	<pre>// there are no super types for this service type</pre>
	CosTradingRepos::ServiceTypeRepository::Service
	TypeNameSeq_var
	default_supers = new
	CosTradingRepos::ServiceTypeRepository::Service
	TypeNameSeq;
[4](#adding-a-new-	<pre>trader_repos_obj-&gt;add_type (</pre>
<pre>service-offer-type)</pre>	"Printer", // service type name
	"IDL:TraderDemo/PrintServer:1.0", // idl type
	name
	properties, // property information
	<pre>default_supers // no super types</pre>
	);

The code is described as follows:

- 1. Get a reference to the Service Offer Type Repository.
- 2. The type CosTrading::TypeRepository\_var is a typedef of CORBA::Object, and is essentially a forward reference. After obtaining a reference of this type, narrow it to CosTradingRepos::ServiceTypeRepository.
- 3. Construct the property information of a service offer type. In this example there are three properties: name, location, and page\_per\_min. The main parts of a service offer type include the following:

The name of the service type.

The IDL interface id for this service.

The properties which are a description of the offer. These are as follows:

```
enum PropertyMode {
PROP_NORMAL, PROP_READONLY,
PROP_MANDATORY, PROP_MANDATORY_READONLY
};
struct PropStruct {
CosTrading::PropertyName name;
TypeCode value_type;
PropertyMode mode;
};
typedef sequence<PropStruct> PropStructSeq;
```

4. Invoke the add\_type() function and pass it the relevant parameters.

### 4.3.3 Exporting a Service Offer

When a server wants to make its service offers available, it registers with the Trader Service by exporting service offers. The code in Example 1 demonstrates the steps to export a service offer.

Example1 Exporting a service offer

```
[1](#exporting-a-
service-offer) PrintServer_impl * impl = new
PrintServer_impl();
TraderDemo::PrintServer_var print_server = impl-
>_this();
...
```

<pre>[2](#exporting-a- service-offer)</pre>	<pre>CORBA::Object_var trader = orb- &gt;resolve_initial_references("TradingService"); CosTrading::Lookup_var lookup = CosTrading::Lookup::_narrow(trader); CosTrading::Register_var register = lookup- &gt;register_if();</pre>
<pre>[3](#exporting-a- service-offer)</pre>	<pre>CosTrading::PropertySeq_var properties = new CosTrading::PropertySeq(); properties-&gt;length(3); properties[0].name = (const char *) "name"; properties[0].value &lt;&lt;= "laser4"; properties[1].name = (const char *) "location"; properties[1].value &lt;&lt;= "near coffee machine"; properties[2].name = (const char *) "ppm"; properties[2].value &lt;&lt;= (CORBA::Long) 50;</pre>
<pre>[4](#exporting-a- service-offer)</pre>	<pre>CosTrading::OfferId offer_id = register- &gt;export( print_server, // object reference to the CORBA object "Printer", // service type properties ); // continued in next example</pre>

- 1. The printer server first creates an instance of the printer object.
- 2. The printer server connects to the Trader Service (as described in Connecting to the Trader) and gets a trader\_lookup\_var. It then uses this to access the Trader Service's register component, which handles exporting of service offers.
- 3. The server initializes the service offer properties with relevant values. The properties in service offers are name/any pairs, as follows:

```
typedef any PropertyValue;
struct Property {
PropertyName name;
PropertyValue value;
};
typedef sequence<Property> PropertySeq;
```

4. The server finally invokes the export() function to register the service offer.

### 4.3.4 Querying for a Service Offer

Once offers have been exported to the trader service, clients can use the lookup interface to request services. Example 2 demonstrates a basic query that requests a printer that can print more than 5 pages per minute and uses the first offer returned by the trader.

Example2 Querying for a service offer

	<pre>// The Trader Service reference, trader, was aquired earlier CosTrading::PolicySeq_var default_policies = new CosTrading::PolicySeq();</pre>
	<pre>CosTrading::PolicySeq();</pre>
[1](#querying-for-a-	trader->query (
service-offer)	"Printer", // service type name
	"ppm > 5", // constraint
	"random", // ordering of results
	<pre>default_policies, // no special policies</pre>
	<pre>desired_properties, // set to return all</pre>
	properties
	50, // max amount of offers wanted
	offers, // offers returned
	offer_itr, // remaining offers
	<pre>limits_applied // applied internally by</pre>
	trader
	);
	<pre>PrintServer_impl printer_obj;</pre>

<pre>[2](#querying-for-a- service-offer)</pre>	<pre>if (offers.length() != 0) { printer_obj = PrintServer::_narrow (offers[0].reference);</pre>
<pre>[3](#querying-for-a- service-offer)</pre>	<pre>printer_obj-&gt;print (doc, job_id); }</pre>

- 1. The client queries the Trader Service for a service offer matching certain criteria. In this example:
  - The constraint is that the offers returned have a page\_per\_min value that is greater than 5 pages per minute.
  - The results are returned in random order.
  - The default policies are used.
  - All properties are returned with the offer.
  - A limit is set for the number of offers returned in the offers parameter. The trader will make find all of the possible matches, and return the remainder in the iter parameter.
- 2. The client selects a service offer from those returned in the query and invokes on the server. This simple example uses the first offer in the sequence.
- 3. The client uses the service offer to invoke on the object. In this case, the document is printed using the selected printer offer.
- 4. Any resources created by the trader for the iterator must be explicitly freed up.

### **5. Querying for Service Offers**

In order for clients to find out about and use services offered by the Trader Service, the client code performs queries to obtain one or more service offers. A service offer contains, among other things, an object reference to a service. Clients then use the object reference to access a desired service.

### 5.1 How the Trader Service Processes a Query

It is easy to see how the set of offers that a trader contains can get quite large. In addition, traders can be linked together (federated) to search each other for service offers. This means that a query needs to have controls that complete a search in a reasonable amount of time. A query also needs controls that limit the amount of data returned.

### 5.1.1 Format of a query

A query starts with a service type name. A query then limits a search for appropriate offers by using a constraint on one or more properties of the service. You can also specify other limiting factors including the number of offers returned, a preference on the sort order, and the property values actually returned.

Figure 4 shows how the Trader Service uses these factors to process a query and generate a sequence of desired service offers.



Figure 4: How Query Parameters Affect Offers Gathered

When the Trader Service processes a query, it gathers a sequence of offers together by narrowing down the set of all potential offers in all linked traders. The Trader Service uses query input to determine the following:

- 1. Uses the service name to determine if an offer is of an appropriate service type.
- 2. Uses the property constraints to determine if the offer matches the criteria specified by the client.
- 3. Uses preferences to determine the order in which to place the offer in the sequence of offers created.
- 4. Uses desired properties to determine which of the offer's property values (if any) are returned.

### 5.1.2 Policies

The Trader Service uses policies to control its behavior. For example, the maximum number of offers that can be searched for. You can also include one or more policies and values in a query to control the search behavior for a specific query.

### **5.2 A Basic Query for Service Offers**

### 5.2.1 Connecting to the trader

Clients need to connect to the Trader Service before they query for service offers. Do the following in your client to get an object reference to the trader:

```
// C++
CORBA::Object_var trader_obj trader_obj = orb-
>resolve_initial_references("TradingService");
CosTrading::Lookup_var lookup = CosTrading::Lookup::_narrow (trader_obj);
```

First, call resolve\_initial\_references() which returns a CORBA::Object\_ptr. Then, narrow the object reference to a trader Lookup object.

### 5.2.2 Querying the trader

After connecting to the trader, clients can query the trader for service offers that match any desired criteria.

	<pre>// C++ lookup -&gt; query ( // Query Input</pre>
<pre>[1](#querying-the- trader)</pre>	"IDL:printer:1.0", // service type name
<pre>[2](#querying-the- trader)</pre>	<pre>"(page_per_min &gt; 5) and (page_type == A4)", // constraint</pre>
<pre>[3](#querying-the- trader)</pre>	"random", // preference sort order
<pre>[4](#querying-the- trader)</pre>	<pre>default_policies, // policies desired</pre>
<pre>[5](#querying-the- trader)</pre>	<pre>return_properties, // properties to return</pre>
<pre>[6](#querying-the- trader)</pre>	<pre>10, // Initial number of offers wanted // Query Output offers, // offers returned iterator, // remaining offers limits_reached // Limits reached during query );</pre>

The input parameters to a query are explained in detail as follows:

- 1. The service type name parameter specifies the service type of the offers required. If the exact\_type\_match import policy is specified as true, only the service type is considered and no subtypes. If the exact\_type\_match policy is false or unspecified then subtypes are considered.
- 2. The constraint parameter specifies the constraint for restricting suitable offers. The constraint is a string that conforms to the OMG Constraint Language. Use an empty string if no constraints are required. See Forming Constraints for Queries for more constraint examples.
- 3. A preference parameter specifies the order of the returned sequence of offers. You can sort offers by the following criteria:
  - " In the order in which the Trader Service finds the offers. (This is the default.)
- <sup>"</sup> In descending order based on property values.
- <sup>"</sup> In ascending order based on property values.
- " All offers that meet a constraint first, followed by those offers that do not meet the constraint.
- <sup>"</sup> In random order.

Use an empty string if no sort preference is required. See Setting Preferences to Sort Service Offers for sort preference examples.

- 4. For now, default policies are used for the policies parameter. Policies are discussed in section 5.
- 5. A return-properties parameter specifies the properties to return for the sequence of offers. You can choose to have none, some, or all properties returned. For example, if for your application it is adequate to use the first valid service offer, you can improve efficiency by returning no properties for the returned offers. See Refining the Properties a Query Returns for an example of how to specify some properties to return.
- 6. The how-many-offers parameter specifies the number of offers to be initially returned via the offers out parameter. This example requests 10 initial offers.

The offers are returned as a sequence of offers. You can check for more offers and obtain them by using the iterator output parameter. If the Trader Service reached any policy limits during its search, the policy name is returned in the limits\_reached output parameter. The query() output and how to use it is described in the next section.

### 5.3 Selecting a Service from Query Results

The previous section described how the input parameters to the query() operation controls the offers you get. This section describes details of the output from query().

#### 5.3.1 Output parameters

The output parameters include a sequence of offers, an iterator object to obtain more offers, and a sequence of policy limits that the Trader Service may have encountered as it collected the offers.

```
//C++
lookup -> query (
// Query Input
// Query Output
offers, // offers returned
iterator, // remaining offers
limits_reached // Limits reached during query
);
```

#### 5.3.2 offers

The offers parameter contains the returned sequence of offers. The client selects a service offer from those returned in the query and invokes on the desired server. The following example simply uses the first offer in the sequence:

```
// C++
PrintServer_impl printer_obj;
if (offers.length() != 0)
{
    printer_obj = printer_if::_narrow (offers[0].reference);
    printer_obj->print (doc, job_id);
}
```

#### 5.3.3 iterator

The iterator parameter is an object reference to an OfferIterator interface. If all offers are returned in the offers parameter then the iterator parameter has a null reference value. However, recall that a query specifies the number of offers to be returned. If the number of offers requested is lower than the number the Trader Service found, then an OfferIterator object reference is returned and the remaining offers can be retrieved via that object.

This example shows how to peruse the remaining sequence of offers. In the example, the names of properties are printed:

```
//C++
char * value = 0; // for value of name property
// to tell when to stop
CORBA::Boolean more_offers = 1;
while (more offers) {
try {
more_offers = iterator->next_n(2, offers);
for (long i=0; i < offers->length(); i++) {
(*offers)[i].properties[1].value >>= value;
cout << value << endl;</pre>
}
}
catch (...) {
cerr << "printing names failed" << endl;</pre>
cerr << "Unexpected Exception" << endl;</pre>
exit(1);
}
}
```

Once you are done with the iterator, you must use its destroy() function to release the resources it uses.

#### 5.3.4 limits\_applied

The limits\_applied parameter is a sequence of policy names. If the Trader Service encounters any policy limits during a query, it returns the names of the policies in this sequence. For example, if a query generates more offers than the maximum number of offers the trader is allowed to search for, the name max\_search\_card is returned in the sequence. The values of the policies are not returned.

### **5.4 Forming Constraints for Queries**

This section describes how to use more features of the OMG constraint language to construct effective constraint expressions when querying for service offers. See The OMG Constraint Language for a complete specification of the constraint language.

Although service properties can be defined using the great variety of IDL data types available, not all can be queried with the OMG constraint language. You can use the constraint language for properties defined with the following simple IDL data types: boolean
short, unsigned short
long, unsigned long
float, double
char, Ichar
string, Istring

You can also use the constraint language for properties defined with sequences of the above data types.

#### 5.4.1 Evaluating property values

A constraint contains a comparison of property values. The result of a comparison is a **boolean**. Thus, a potential offer is a match if the Trader Service evaluates the constraint as true.

#### **Comparison operators**

Use the operators ==, !=, >, >=, <, or <= to compare two of the same simple types. For example, the following constraint compares a float property with a float constant value:

float\_property == 1.0

#### Substring operator

Use the operator  $\sim$  to determine if the right operand is a substring of the left operand. The left operand is a property of type string or Istring, and the right operand is another string or string constant. For example:

```
string_property ~ 'String data'
```

String constants are delineated with apostrophes. To embed an apostrophe in a string, precede the apostrophe with a backslash ( $\chi$ ).

#### **Sequence operators**

Use the in operator to test if a value is in a sequence of values. The left operand must be a simple IDL type and the right operand must be a sequence of the same simple IDL type. For example:

'duplex' in output\_options

#### 5.4.2 Combining expressions

Constraints can include combinations of expressions by using the keywords and, or, and not. For example, the following shows a constraint to obtain printers that produce output at a rate greater than 5 pages per minute and that support an A4 page type:

```
(page_per_min > 5) and (page_type == 'A4')
```

The following constraint is to obtain printers that do not produce output at a rate less than 5 pages per minute:

```
not (page_per_min < 5)</pre>
```

You can use parentheses to group expressions for clarity or to override the precedence relations of the constraint language.

#### 5.4.3 Testing for a property's existence

A constraint can test any service type property for its existence, even if the IDL data type used to define it is not a simple data type or sequence of a simple data type. Use the exist keyword to test whether a property exists for given offer:

```
exist page_per_min
```

Because properties with a mandatory mode must exist, it does not make sense to test for their existence. However, searching for the existence of optional properties can provide a powerful means of limiting the offers returned.

#### 5.4.4 Using arithmetic expressions

Constraints can include arithmetic expressions by using the standard operators \*/+-. However, you can only use these operators between numbers and not between property names. For example:

page\_per\_min > 2 \* 5

You can use float and double values where appropriate. Exponential notation is also valid.

### **5.5 Setting Preferences to Sort Service Offers**

#### 5.5.1 Creating a preference string

When querying for service offers, you can set preferences to make the offers return in a particular order. Create a preference string using one of the following formats:

```
first
max *numerical_expression*
min *numerical_expression*
with *constraint_expression*
random
```

A preference string consists of a keyword and, in some cases, an expression. You cannot specify combinations of preferences by using more than one keyword in a single preference string.

#### 5.5.2 Constructing preference expressions

Use the OMG constraint language to construct the preference expressions for max, min, and with formats. When you submit a query with one of these preference expressions, the Trader Service associates a sort value with each offer by evaluating the expression. The offers are then sorted with respect to the sort value and the type of preference as follows:

- A max preference sorts the offers in descending order from the maximum sort value evaluated.
- A min preference sorts the offers in ascending order from the minimum sort value evaluated.
- A with preference returns the offers that evaluate to true before the offers that evaluate to false.

If the Trader Service cannot evaluate the expression for a particular offer (for example, an expression that is based on an optional property may not evaluate), the offers are not discarded but are grouped after those offers that can be evaluated.

#### 5.5.3 Returning offers in the order of discovery

The default behavior of the Trader Service is to return offers in the same order in which they were discovered. You can also specify this behavior by using the first preference.

#### 5.5.4 Returning offers in descending order

Use the preference string format "max *numerical\_expression*" to sort the returned service offers in descending order. For example:

max page\_per\_min

In this example, printers with the highest page\_per\_min value are returned first. The rest of the offers are returned in a descending order based on the sort value calculated in the numerical expression. Any offers that do not have a value for page\_per\_min are returned last.

#### 5.5.5 Returning offers in ascending order

Use the preference string format "min *numerical\_expression*" to sort the returned service offers in ascending order. For example:

min (jobs\_in\_queue)

In this example, printers with the lowest number of jobs\_in\_queue are returned first, followed in ascending order.

#### **Note**

The max and min preference formats do not constrain the offers returned to a maximum or minimum value. For example, the following is an incorrect expression that does not limit a sort to the offers with a minimum page\_per\_min value of 8: min (page\_per\_min == 8) \*This is an incorrect format\*

#### 5.5.6 Returning offers by constraint

Use the preference string format "with constraint\_expression" to order the returned service offers based on a constraint expression. A constraint expression evaluates to either true or false. The offers with a constraint preference that evaluates to true precede those that evaluate to false. For example:

with (page\_per\_min > 10)

This example sorts the returned offers into two groups: the first group has pages per minute values greater than 10, and the second has pages per minute values less than or equal to 10.

#### 5.5.7 Returning offers in random order

Use the random preference to make the Trader Service return offers in random order.

### 5.6 Refining the Properties a Query Returns

#### 5.6.1 Specifying returned properties

You can specify which properties you want returned in the sequence of offers. For example, if your application does not need to use all properties to determine which services to use, it can be more efficient for your memory and network traffic to return only those properties you need.

Example 1 shows how to specify the properties to return.

Example1 Specifying the return of properties

	// C++
<pre>[1](#specifying- returned-properties)</pre>	<pre>CosTrading::Lookup::SpecifiedProps desired_properties;</pre>

<pre>[2](#specifying- returned-properties)</pre>	<pre>CosTrading::PropertyNameSeq_var property_seq = new CosTrading::PropertyNameSeq(); // two properties are specified property_seq-&gt;length(2); property_seq[0] = CORBA::string_dup("location"); property_seq[1] = CORBA::string_dup("page_per_min");</pre>
<pre>[3](#specifying- returned-properties)</pre>	<pre>desired_properties.prop_names(property_seq); CosTrading::PolicySeq_var default_policies = new CORBA::PolicySeq(); lookup-&gt;query ( "IDL:printer:1.0", "(page_per_min &gt; 5) and (page_type == A4)", "random", default_policies,</pre>
<pre>[4](#specifying- returned-properties)</pre>	<pre>desired_properties, // properties to return 10, offers, iterator, limits_reached );</pre>

The code is described as follows:

1. You first declare a SpecifiedProps union for properties.

To return all properties use this code and go to step 4:

// C++
CosTrading::Lookup::SpecifiedProps
desired\_properties(CosTrading::Lookup::all);

To return no properties use this code and go to step 4:

```
// C++
CosTrading::Lookup::SpecifiedProps
desired_properties(CosTrading::Lookup::none);
```

- 2. If you want specific properties returned, create a property name sequence, property\_seq. Make the sequence long enough to contain the names of all properties to be returned and fill it with the names of the desired properties.
- 3. Fill the desired\_properties object with the list of properties to be returned.
- 4. Use the desired\_properties object as a parameter in the query() function call.

# 6. Understanding Trader Service Policies

Trader policies affect how the Trader Service works. Most policies control the scope of a search for offers. A few policies determine certain functionality that applies to the trader itself, including whether a trader supports modifiable properties, whether it supports dynamic properties, and whether it supports proxy offers.

## 6.1 What is a policy?

A policy is a data structure containing a pre-defined policy name and a value for that policy. The value's data type depends on the particular policy. For example, the supports\_modifiable\_properties policy can have a boolean value. A value of 0 means that for the particular trader, properties of service offers cannot be changed after an offer is exported to the trader. A value of 1 means that the trader allows changes to its service offer properties.

## **6.2 Policies that Affect Queries**

### 6.2.1 Query semantics

Most policies that affect queries are scoping policies. These policies relate to the scope of a search when a query is submitted to the trader. Here are the high-level semantics when the trader processes a query:

- 1. Consider the number of initial offers to be searched.
- 2. Match the offers against the constraints specified in the query.
- 3. Consider the number of "hops" between linked traders during a search.
- 4. Order the results according to the preference supplied in the query. (No policies relate to this.)
- 5. Return these offers to the user.

#### 6.2.2 Search policies

search_card	Consider at most this number of offers for the search.
<pre>match_card</pre>	Match at most this number of offers before returning them to be ordered.
hop_count	Allow at most this number of hops from one trader to another linked trader.
return_card	Return at most this number of offers to the client.

The following policies govern the scope of this search:

These policies can be optionally specified in a query. Each of these policies have "tuning" policies associated with them in the trader. The trader tuning policies are called def\_policy and max\_policy where policy is the name of one of the policies listed above. For example, the search\_card policy may be specified in a query and the def\_search\_card and max\_search\_card policies have initial values in the Trader Service when it starts up. The trader policies may be changed using functions from the CosTrading::Admin interface.

If a query doesn't specify a value for a policy, then the appropriate def\_policy value of the trader applies. If the query specifies a value for a policy, then it applies for the duration of that query, except where it exceeds the trader's max\_policy value, in which case the value max\_policy is used. For example, suppose that in the trader, def\_search\_card is 50, and max\_search\_card is 500:

- If the query doesn't specify a search\_card, then at most 50 offers will be considered in the initial search.
- If the query specifies *"search\_card* = 100", then 100 offers will be initially considered.
- If the query specifies "*search\_card* = 600", then, since this exceeds the trader's maximum, at most 500 offers will be initially considered.

#### 6.2.3 Return policy

The policy exact\_type\_match may also be defined in a query. The value of this policy is a boolean. If it is specified as true, then only offers that exactly match the specified service type are considered; super-types are omitted. Otherwise, offers of any conforming service type are considered.

### 6.2.4 List of query policies

Table 2 shows the policies you can set in a query, along with the associated trader policies that affect the query policy. (A complete list and description of each policy is in the *CORBA Programmer's Reference*.)

Table 2 Query policies and Trader 9	Service policies
-------------------------------------	------------------

Policies You Can Set in a Query	Related Trader Service Policies
Searching Service Offers	
exact_type_match	
search_card	def_search_card
	max_search_card
Matching Query Constraints	
match_card	def_match_card
	max_match_card
Number of Returned Offers	
return_card	def_return_card
	max_return_card
Links Between Traders	
hop_count	def_hop_count
	max_hop_count
link_follow_rule	default_follow_rule 1
	def_follow_policy
	limiting_follow_rule a
	link_follow_rule
	max_follow_policy
request_id_stem	request_id_stem
starting_trader	

Optional Trader Capabilities	
use_dynamic_properties	supports_dynamic_properties
use_modifiable_properties	supports_modifiable_properties
use_proxy_offers	supports_proxy_offers

1 a.These are set in the links created between traders. See Managing Links Between Traders.

### 6.3 Policies that Affect Trader Functionality

A trader may support some optional functionality. These include *modifiable properties*, *dynamic properties*, and *proxy offers*. In a particular query, a client may chose not to consider offers that require such functionality, even if the trader supports it (for example, to optimize the speed of a query).

#### 6.3.1 Evaluating policies

To find out if a trader supports any of this functionality, the following attributes are provided in the CosTrading::SupportAttributes interface. The *get* function for these attributes return a booleanrepresenting the value of the policy:

- supports\_modifiable\_properties (default: true)
- supports\_dynamic\_properties (default: true)
- supports\_proxy\_offers (default: true)

### 6.3.2 Query policies

In a query, these policies are specified using the following **boolean** variables. If the trader does not support the functionality, then the corresponding query policy is ignored.

- use\_modifiable\_properties
- use\_dynamic\_properties
- use\_proxy\_offers

### 6.4 Using Policies in a Query

#### **6.4.1 Policies parameter**

You can use the policies parameter in a query to control the query and override some of the default Trader Service policies. A Policy data structure contains two members:

- A PolicyName is a pre-defined string identifier used by a trader to identify a policy.
- A PolicyValue is the value specified for a policy. The PolicyValue is of type any. The type of the any value should match the type of the corresponding policy.

An application may manipulate policies by using a PolicySeq, which is a sequence of Policy data structures.

#### 6.4.2 Creating a policy list

Example 2 shows how to create a policy sequence and pass it to a query():

Example2 Creating a policy sequence

	//C++
<pre>[1](#creating-a-policy- list)</pre>	<pre>CosTrading::PolicySeq_var policies; policies = new PolicySeq(2);</pre>
<pre>[2](#creating-a-policy- list)</pre>	<pre>policies[0].name = (const char *) "search_card"; policies[0].value &lt;&lt;= (CORBA::ULong) 50;</pre>
<pre>[3](#creating-a-policy- list)</pre>	<pre>policies[1].name = (const char *)"use_dynamic_properties"; policies[1].value &lt;&lt;= CORBA::Any::from_boolean (0); lookup-&gt;query("IDL:printer:1.0", "page_per_min &gt; 5", "first",</pre>

<pre>list) desired_properties, how_many_offers, offers,</pre>	[4](#creating-a-policy-	policies,
	list)	<pre>how_many_offers,</pre>
	<pre>[5](#creating-a-policy- list)</pre>	<pre>limits_applied );</pre>

- 1. First create a sequence of Policy structures, and set the number of policies you want to specify for the query. This example uses just two policies.
- 2. Setting the search\_card policy to 50 means that the query should look at a maximum of 50 offers initially before matching this query.
- 3. Setting the use\_dynamic\_properties policy to false means that the query should not consider offers with dynamic properties.
- 4. Use the policy sequence as a parameter in the query() function.
- 5. If the Trader Service encounters any policy limits during a query, it returns the names of the policies in this parameter as a sequence of policy names. For example, if a query generates more offers than the maximum number of offers the trader is allowed to search for, the name <code>max\_search\_card</code> is returned in the sequence. The values of the policies are not returned.

### 6.4.3 Policy types

Table 3 shows the policies you can set and the associated IDL data type for each policy:

Table 3 Policies You Can Set for a Query

Policy Name	IDL Type
<pre>exact_type_match</pre>	boolean
hop_count	unsigned long
<pre>link_follow_rule</pre>	CosTrading::FollowOption
match_card	unsigned long
<pre>request_id_stem</pre>	CosTrading::OctetSeq
return_card	unsigned long

Policy Name	IDL Type
search_card	unsigned long
starting_trader	CosTrading::TraderName
<pre>use_dynamic_properties</pre>	boolean
<pre>use_modifiable_properties</pre>	boolean
use_proxy_offers	boolean

### 6.5 Setting a Trader's Global Policies

#### 6.5.1 Setting global policies

For each policy in the trader, the CosTrading::Admin interface has an associated set function that you can use to set the policy value. The set functions take the form set\_policy\_name(value), where policy\_name is the policy you wish to set. For example, you can use the Admin::set\_max\_match\_card() function to set the max\_match\_card attribute of the ImportAttributes interface.

Also see Setting policies for linked traders for another example of how to set policies.

#### 6.5.2 Global policies

Table 4 summarizes the global trader policies an administration application can set:

Table 4 Trader policies

Policy Name	Туре
<pre>default_follow_rule</pre>	CosTrading::FollowOption
<pre>def_follow_policy</pre>	CosTrading::FollowOption
def_hop_count	unsigned long
def_search_card	unsigned long
def_match_card	unsigned long
def_return_card	unsigned long

Policy Name	Туре
<pre>max_follow_policy</pre>	CosTrading::FollowOption
<pre>max_hop_count</pre>	unsigned long
<pre>max_search_card</pre>	unsigned long
<pre>max_link_follow_policy</pre>	CosTrading::FollowOption
<pre>max_list</pre>	unsigned long
<pre>max_match_card</pre>	unsigned long
<pre>max_return_card</pre>	unsigned long
<pre>request_id_stem</pre>	CosTrading::OctetSeq
<pre>supports_dynamic_properties</pre>	boolean
<pre>supports_modifiable_properties</pre>	boolean
<pre>supports_proxy_offers</pre>	boolean

# 7. Exporting and Managing Service Offers

Application servers can advertise their services by exporting service offers to the Trader Service. Servers can also manage their service offers in the Trader Service by getting offer information, modifying an offer's properties, and withdrawing an offer.

## 7.1 Server tasks

This section describes the following service offer tasks for servers:

- How to initialize service offer properties prior to exporting to the Trader Service.
- How to export service offers to the Trader Service.
- How to get service offer data from the Trader Service.
- How to modify a service offer already in the Trader Service.
- How to withdraw a service offer from the Trader Service.

## 7.2 Environment

All of this section's discussion and associated programming examples can be done within a specific application server, such as the printer server shown in the examples here. However, you might just as likely do this programming with a management server that is separate from the servers supplying specific resources. Whether it is better for your server to export and manage its own offer or for a separate management program to do it depends on your programming style and application design.

## 7.3 Initializing Service Offer Properties

#### 7.3.1 Property structure

Offer properties are stored as a sequence of property structures, where each property is a name-value pair, as follows:

```
// IDL
typedef Istring PropertyName;
typedef any PropertyValue;
struct Property {
PropertyName name;
PropertyValue value;
};
typedef sequence<Property> PropertySeq;
```

### 7.3.2 Getting an offer type's property list

Information about all services that the Trader Service can support is stored as service types in the Trader Service repository. When you develop a server for a specific service, you will need to have the information about the service type's properties. There may be documentation describing these properties or you may need to extract the information from the Trader Service. The section, Managing the Service Type Repository explains how to add service types to a trader and how to list a trader's service type property information.

Before a server can export an offer to a trader, it must initialize the offer's properties. A server initializes the service offer properties with relevant values. For example:

```
// C++
CosTrading::PropertySeq_var properties = new CosTrading::PropertySeq ();
properties->length(3);
properties[0].name = (const char *) "name";
properties[0].value <<= "laser4";
properties[1].name = (const char *) "location";
properties[1].value <<= "near coffee machine";
properties[2].name = (const char *) "page_per_min";
properties[2].value <<= (CORBA::Long) 50;</pre>
```

#### 7.3.3 Read-only and mandatory properties

Before you initialize an offer's properties, check the service type information for any *mandatory* properties and any *readonly* properties. You must set a value for mandatory properties in order to successfully export an offer. Readonly properties cannot be modified once the offer is exported. Each property has assigned to it one of the following modes:

normal	A service offer need not supply a value for this property.
readonly	A service offer need not supply a value for this property. However if it does, the value cannot be modified after its offer is exported.
mandatory	A value for this property must always be provided when a service offer is exported.
mandatory and readonly	A value for this property must be supplied and it cannot be modified after it is exported.

### 7.4 Exporting a Service Offer to Trader

Servers use the export() operation to register a service offer with the Trader Service.

#### 7.4.1 Synopsis

The export() operation takes the following form:

```
// C++
CosTrading::OfferId CosTrading::Register::export(
Any service_object,
String service_type,
PopertySeq properties)
```

It takes the following parameters:

<pre>service_obj ect</pre>	A reference to the object providing the service
<pre>service_ty pe</pre>	The name of the service type that represents the service being offered
properties	A sequence of Property which describes the offer's properties. See Initializing Service Offer Properties for more information.

export() returns a CosTrading::OfferId which uniquely identifies the service offer within the trader. This value is needed to modify or withdraw the service offer.

#### 7.4.2 Example

Example 3 shows how to export a service offer:

Example3 Exporting a service offer

	<pre>// C++ CORBA::ORB_var orb = CORBA::ORB_init(argc, argv);</pre>
<pre>[1] (#example)</pre>	<pre>PrintServer_impl * impl = new PrintServer_impl(); TraderDemo::PrintServer_var print_server = impl-&gt;_this();</pre>

<pre>[2] (#example)</pre>	<pre>CORBA::Object_var trader = orb- &gt;resolve_initial_references("TradingService"); CosTrading::Lookup_var lookup = CosTrading::Lookup::_narrow(trader);</pre>
<pre>[3] (#example)</pre>	<pre>CosTrading::Register_var register = lookup-&gt;register_if();</pre>
<pre>[4] (#example)</pre>	<pre>CosTrading::OfferId offer_id = register-&gt;export( print_server, // the object itself "Printer", // service type properties // initialized in previous example );</pre>

Do the following programming steps to export the service offer:

- 1. Create an instance of the service object. For example, this application uses a printer service.
- 2. Connect to the Trader Service. Call the function resolve\_initial\_references() to get an object reference to the trader and narrow the returned value to get the trader's Lookup object.
- 3. Narrow the Lookup object to get the trader's Register component, which handles service offer exporting.
- 4. Invoke the export() function to export the service offer.

### 7.5 Getting Service Offer Data from Trader

#### 7.5.1 Reviewing offer information

After a server exports an offer, you can review the information contained in the offer by using the describe() operation of the Register interface. This function takes an OfferId as input and returns an OfferInfo structure representing offer information. The following example continues from the previous one:

```
// C++
CosTrading::Register::OfferInfo_var offer_info = register-
>describe(offer_id);
```

The CosTrading::Admin interface includes an list\_offers() function you can use to obtain a list of all offers held by the Trader Service.

### 7.6 Modifying a Service Offer

#### 7.6.1 Using modify()

You can modify any properties of an offer, other than those declared read-only, by using the modify() operation of the trader's Register object to delete, add, or change its properties.

modify() takes the following parameters:

offer_id	The OfferId returned by the trader when the offer was exported.
delete_li st	A sequence of PropertName specifying which properties to delete from the offer.
change_li st	A sequence of <b>Property</b> specifying the properties to modify, along with their new values. New properties can included in this list and they will be added to the offer.

#### 7.6.2 Example

Example 4 shows how to delete a property and how to change the value of a property.

```
Example4 Deleting a property
```

	// C++
F 1 1	Costrading : Proporty NameSog yor delate list - new
[1]	<pre>CosTrading::PropertyNameSeq_var delete_list = new</pre>
(#example)	<pre>CosTrading::PropertyNameSeq();</pre>
	<pre>delete_list-&gt;length(1);</pre>
	<pre>delete_list[0]= (const char *) "page_per_min";</pre>

[2] (#example)	<pre>CosTrading::PropertySeq_var change_list = new CosTrading::PropertySeq (); change_list-&gt;length(1); change_list[0].name = (const char *) "location"; change_list[0].value &lt;&lt;= "A-wing, first floor";</pre>
[3] (#example)	<pre>register-&gt;modify(offer_id, delete_list, change_list);</pre>

- 1. Create a sequence of the property names to be deleted.
- 2. Create the sequence of the properties to be added or modified.
- 3. Finally, call the modify() function

#### 7.6.3 Readonly properties

For situations in which you need to change readonly properties, you can withdraw an offer and then export a new offer, but this changes the offer ID which may affect applications that already hold the current offer.

#### 7.6.4 Policy for supporting modifiable properties

The supports\_modifiable\_properties policy is a boolean attribute that indicates whether or not a specific trader supports modifiable properties. Servers and administration applications can turn support for modifiable properties on or off by using CosTrading::Admin::set\_supports\_modifiable\_properties(). To obtain the current value of this policy, query the

CosTrading::SupportAttributes::supports\_modifiable\_properties attribute.

### 7.7 Withdrawing a Service Offer from Trader

When it is necessary to withdraw an offer from the Trader Service, use the CosTrading::Register::withdraw() function. The function requires as input the offer\_id, which is obtained as a result of the export() function: register->withdraw(offer\_id);

Administration applications can use the following function to withdraw multiple offers satisfying a specified service type and constraint:

```
register->withdraw_using_constraint(type_name, my_constraint);
```

# 8. Programming Topics

*This section is a brief introduction to some advanced programming topics and features of the Trader Service. These topics include adding service types, using dynamic properties, and managing links between traders.* 

### 8.1 Managing the Service Type Repository

Servers cannot export service offers to the Trader Service unless the appropriate service types are stored in the Service Type Repository. You use the operations of the ServiceTypeRepository interface of the CosTradingRepos module to manage service types in a trader. Service types are added to a trader only occasionally, and usually by a management type of server. Service types are rarely removed from a trader.

#### 8.1.1 Creating service type properties

You create service type properties and then you add these properties along with other information to the Trader Service. Example 5 shows how to create service type properties.

Example5 Creating service type properties	
	// C++
<pre>[1](#creating- service-type- properties)</pre>	<pre>CosTradingRepos::ServiceTypeRepository::PropStructS eq_var properties = new CosTradingRepos::ServiceTypeRepository::PropStructS eq; propertyies-&gt;length(3);</pre>
<pre>[2](#creating- service-type- properties)</pre>	<pre>properties[(CORBA::Ulong) 0].name = (const char *)</pre>
<pre>[3](#creating- service-type- properties)</pre>	<pre>properties[(CORBA::Ulong) 0].value_type = CORBA::_tc_string;</pre>

<pre>[4](#creating- service-type- properties)</pre>	<pre>properties[(CORBA::Ulong) 0].mode = CosTradingRepos::ServiceTypeRepository::PROP_MANDAT ORY_ READONLY;</pre>
	<pre>properties[(CORBA::Ulong) 1].name = (const char *) "location";</pre>
	<pre>properties[(CORBA::Ulong) 1].value_type = CORBA::_tc_string;</pre>
	<pre>properties[(CORBA::Ulong) 1].mode = CosTradingRepos::ServiceTypeRepository::PROP_MANDAT ORY;</pre>
	<pre>properties[(CORBA::Ulong) 2].name = (const char *) "page_per_min";</pre>
	<pre>properties[(CORBA::Ulong) 2].value_type = CORBA::_tc_long; mmemorties[(CORBA::Ulong) 2].made</pre>
	<pre>properties[(CORBA::Ulong) 2].mode = CosTradingRepos::ServiceTypeRepository::PROP_NORMAL ;</pre>

The code is described as follows:

- 1. Create a new sequence of property structures and set the length of the sequence to equal the number of properties for the service type.
- 2. For each property, assign a character string to represent the name of the property. This printer example has three properties named name, location, and page\_per\_min.
- 3. Set the data type for the value of each property. This is standard Orbix programming for setting values for typecodes.
- 4. Set the mode for each property.
  - A **PROP\_MANDATORY\_READONLY** mode means the property *must* be set when exporting a service offer of this service type, but once it is exported, it cannot be changed.
  - A **PROP\_MANDATORY** mode means the property *must* be set when exporting a service offer, but its value may be changed later if needed, after the service offer is exported.
  - A **PROP\_READONLY** mode (not shown) means the property may be set when exporting a service offer, but once it is exported, it cannot be changed.
  - A **PROP\_NORMAL** mode means the property may be set in a service offer but it is not required. It can be changed later.

#### 8.1.2 Adding a service type

Example 6 adds a service type named IDL:printer:1.0 to a trader. The interface type name from the IDL file is IDL:TraderDemo/PrintServer:1.0. The properties, created in Example 5 are the next parameter. The super\_types parameter is a list of types from which this service type is derived. A subtype must support properties of its supertypes. In this example, there are no supertypes.

Example6 Adding a service type

	// C++
<pre>[1](#adding-a- service-type)</pre>	<pre>CORBA::Object_var trader = orb- &gt;resolve_initial_references("TradingService"); CosTrading::Lookup_var lookup = CosTrading::Lookup::_narrow(trader); CosTradingRepos::ServiceTypeRepository_var type_repos_obj = CosTradingRepos::ServiceTypeRepository::_narrow(lookup- &gt;type_repos());</pre>
<pre>[2](#adding-a- service-type)</pre>	<pre>CosTradingRepos::ServiceTypeRepository::ServiceTypeName Seq_var super_types = CosTradingRepos::ServiceTypeRepository::ServiceTypeName_ Seq;</pre>
<pre>[3](#adding-a- service-type)</pre>	<pre>type_repos_obj-&gt;add_type (     "IDL:printer:1.0", // service type name     "IDL:printer_if:1.0", // idl type name     properties, // property information     super_types // no super types );</pre>

The code is described as follows:

- 1. Connect to the trader using resolve\_initial\_references, narrow the returned object to a Lookup object, and use that to get a reference to the Trader Service's Service Type Repository.
- 2. Create a list of the supertypes which define the service type being created. For this example, there are no supertypes.
- 3. Call add\_type to add the service type to the Service Type Repository.

#### 8.1.3 Managing service types

After a service type is added to the Trader Service, applications can use other operations of the CosTradingRepos::ServiceTypeRepository interface to manage service types. These include remove\_type() and list\_types(). The describe\_type() operation returns information that describes the type, and the fully\_describe\_type() operation searches recursively to return information on all the supertypes for this type.

You can also hide service types from outside the service type repository by using the mask\_type() operation. This may be used, for example, where a type is no longer needed, but it is the supertype of other types in the type repository. Use the unmask\_type() operation if you need to make a masked service type visible again.

See also the SupportAttributes::type\_repos attribute and the Admin::set\_type\_repos() operation. These get a reference to the type repository interface and set the type repository interface in a trader.

### 8.2 Using Dynamic Property Values

#### 8.2.1 Dynamic property values

Exported offers can contain dynamic property values. These are values that can change at runtime. For example, the number of print jobs in a printer queue. This is done by exporting an object reference that can be invoked to retrieve the current value from the server. Clients and the trader can then dynamically determine the length of the printer queue at the time of a query. This is not as fast as using static values, but it can greatly increase the flexibility involved.

The fact that a property has a dynamic value is only relevant at export time. There is no difference when defining the property in the service type.

### 8.2.2 Exporting a dynamic property value

When a dynamic property value is being exported, then the type CosTradingDynamic::DynamicProp is used rather than the expected type. The trader recognizes this as a special type, and treats it accordingly.

The following code shows how to set properties, including a dynamic property, and then export the offer that contains the dynamic property.

```
Example7 Setting dynamic properties
```

	<pre>// C++ CosTrading::PropertySeq_var properties = new CosTrading::PropertySeq(); properties-&gt;length(4); properties[(CORBA::Ulong) 0].name = (const char *) "name"; properties[(CORBA::Ulong) 0].value &lt;&lt;= "laser4"; properties[(CORBA::Ulong) 1].name = (const char *) "location"; properties[(CORBA::Ulong) 1].value &lt;&lt;= "near coffee machine"; properties[(CORBA::Ulong) 2].name = (const char *) "page_per_min"; properties[(CORBA::Ulong) 2].value &lt;&lt;= (CORBA::Long) 50; CosTradingDynamic::DynamicProp_dynam_prop_val;</pre>
<pre>[1](#exporting-a-dynamic- property-value)</pre>	<pre>dynam_prop_val.eval_if = CosTradingDynamic::DynamicPropEval::_duplicate (dynam_obj);</pre>
<pre>[2](#exporting-a-dynamic- property-value)</pre>	<pre>dynam_prop_val.returned_type = CORBA::_tc_ushort; dynam_prop_val.extra_info &lt;&lt;= (CORBA::UShort) 0; properties[(CORBA::Ulong) 3].name = (const char *) "queue_length";</pre>
<pre>[3](#exporting-a-dynamic- property-value)</pre>	<pre>properties[(CORBA::Ulong) 3].value &lt;&lt;= dynam_prop_val; register_obj-&gt;export( obj, // object reference "IDL:printer:1.0", // service type name properties // seq of properties );</pre>

The code is described as follows:

- eval\_if is essentially a callback object in the server. It implements the IDL interface
   CosTradingDynamic::DynamicPropEval, which contains one operation evalDP, which returns the current
   value of the property in the server when invoked.
- 2. The returned\_type must be the same type as the corresponding property type defined in the service type. extra\_info is essentially ignored by the trader, but may be used by users to carry additional information.
- 3. The dynamic value is assigned to the property value.

#### 8.2.3 Using a dynamic property value

Clients may need to check if the value in a property is dynamic or not, if it is possible that the value may be either a static or dynamic value.

```
Example8 Using a dynamic property value
```

```
// C++
CosTrading::Property prop = properties[2];
CORBA::UShort length;
if (prop.value.containsType(CORBA::_tc_ushort)) {
prop.value >>= length;
cout << "static queue_length " << length << endl;</pre>
}
else if (prop.value.containsType(CosTradingDynamic::_tc_DynamicProp)) {
CosTradingDynamic::DynamicProp * dynam_prop;
prop.value >>= dynam_prop;
CosTradingDynamic::DynamicPropEval_ptr dynam_eval = dynam_prop->eval_if;
CORBA::Any* length_any;
length_any = dynam_eval->evalDP(
prop.name,
dynam_prop->returned_type,
dynam_prop->extra_info);
*length_any >>= length;
cout << "dynamic queue_length " << length << endl;</pre>
}
```

Note that if the trader itself evaluates the dynamic property value, because it is used in a constraint expression (for example, "queue\_length < 10"), then it will return the static value at the time of evaluation in the offer's properties. This is to minimize the evaluation times on dynamic properties.

### 8.2.4 Allowing dynamic properties

While the Trader Service allows dynamic properties by default, a specific trader may be set to not allow dynamic properties. The CosTrading::SupportAttributes::supports\_dynamic\_properties policy is a boolean attribute that indicates whether or not the trader allows dynamic properties. Servers and administration applications can set this policy value by using the operation
CosTrading::Admin::set\_supports\_dynamic\_properties().

### 8.3 Managing Links Between Traders

### 8.3.1 Linked traders

A linked trader shares information about its service offers with one or more other traders. Linked traders allow administrators to organize service types and service offers in logical and more efficient ways for specific environments.

This section describes the following Link function tasks:

- Setting link trader policies.
- Adding and removing links.
- Listing links to other traders.

### 8.3.2 Setting policies for linked traders

Understanding Trader Service Policies introduced several policies that relate to linked traders including hop\_count, link\_follow\_rule, and default\_follow\_rule. A client query can set some of these policies to control the search for offers, but other policies relating to linked traders control the links and may override the query policies.

Example 9 shows the use of request\_id\_stem. This should be a unique value per trader. It will be used in queries send to other traders, to prevent infinite looping. When a trader sees an incoming query with its own request id stem, it does not process the query, and returns a result of zero offers to the calling trader.

Example9 Using request\_id\_stem

```
// C++
// set request_id_stem to "1"
const char * word = "1";
OctetSeq stem(1);
stem.length(1);
stem[0] = word[0];
// admin_obj is a pointer to the Admin Interface of Orbix Trader
admin_obj->set_request_id_stem(stem);
```

The following code shows how to set other trader policies relating to links:

```
// C++
// set all the follow options
CosTrading::FollowOption max_follow = CosTrading::always;
CosTrading::FollowOption max_link_follow = CosTrading::always;
CosTrading::FollowOption def_follow = CosTrading::always;
// set options for hops between traders
int max_hop = 10;
int def_hop = 10;
try {
admin_obj->set_max_follow_policy(max_follow);
admin_obj->set_def_follow_policy(def_follow);
admin_obj->set_max_link_follow_policy(max_link_follow);
admin_obj->set_def_hop_count(def_hop);
admin_obj->set_max_hop_count(max_hop);
} catch (...) {
cerr << "Call to set policies failed" << endl;
exit(1);
}
```

#### 8.3.3 Adding links

Example 10 shows how to add a link from one trader to another. The trader1 establishes a link to trader2. The link is called link\_to\_trader2.

Example10 Linking from one trader to another

```
// C++
CosTrading::LinkName name = CORBA::string_dup("link_to_trader2");
// set CosTrading::FollowOptions for add_link
CosTrading::FollowOption def_pass_on_follow_rule = CosTrading::always;
CosTrading::FollowOption limiting_follow_rule = CosTrading::always;
// link_var is a pointer to the Link Interface of trader1
// target is a pointer to trader2 Lookup Interface
try {
link_var->add_link(
name,
target,
def_pass_on_follow_rule,
limiting_follow_rule
);
} catch (...) {
cerr << "Call to add_link failed" << endl;</pre>
exit(1);
}
```

#### 8.3.4 Removing links

Example 11 shows how to remove a link. The link removed is the one created in Example 10:
Example11 Removing a link

```
// C++
// set LinkName
CosTrading::LinkName name =
CORBA::string_dup("link_to_trader2");
// link_var is a pointer to the Link Interface of trader1
try {
    link_var->remove_link(name);
    } catch (...) {
    cerr << "Call to remove_link failed" << endl;
    cerr << "Unexpected exception" << endl;
exit(1);
}</pre>
```

### 8.3.5 Creating lists of links

Example 12 shows how to create a listing of the links to other traders:

```
Example12 Creating a list of links to traders
```

```
// C++
// lists links of trader1
CosTrading::LinkNameSeq_var link_names = 0;
// link_var is a pointer to the Link Interface of trader1
try {
    link_names = link_var->list_links();
    catch (...) {
    cerr << "Call to list_links failed" << endl;
    cerr << "Unexpected exception" << endl;
    exit(1);
    }
    // This prints the link names
    unsigned long length = link_names->length();
    for (CORBA::Ulong i = 0; i < length; i++)
    cout << (*link_names)[i] << endl;
</pre>
```

# 9. Trader Service Console

The Trader Service Console allows you to manage all aspects of the Trader Service, including service types, offers, proxy offers and links. It also lets you perform queries, and configure the trader attributes.

### **⊘** Note

The Trader Service Console is no longer automatically installed. It is available as an optional component. To install, please download and extract the GUI components archive and follow the installation instructions.

The GUI components archive can be downloaded from Rocket Software.

The GUI components have been separated from the product as they do not fully comply with the Section 508 and WCAG accessibility requirements and guidelines. It is intended that future product releases will include updated GUI components that comply with the relevant accessibility guidelines.

# 9.1 Starting the Trader Console

### 9.1.1 How to start the console

Run the following command in a command window:

ittrader\_console

# 9.2 Main Window

## 9.2.1 GUI appearance

The Trader Service Console main window appears as shown in Figure 5.

Figure 5: The Trader Console main window

🧶 Orbix E2A Trader Console	×
<u>C</u> onsole <u>E</u> dit <u>V</u> iew <u>I</u> nsert <u>T</u> ools	
🖹 I 🕿 🖹 🏥 I 📓 🎒 I 🔍 I 🍇	
Service Types  Description of 'Printer':	
Printer Interface: IDL:TraderDemo/PrintServer:1.0	
Super types:	
None	
Properties: string bldg boolean color float cost_per_page unsigned short ppm string queue Masked: No Incarnation: {0, 1}	
ID: IDL:omg.org/CosTrading/Lookup:1.0, Host: FINN, Port: 53087	

## 9.2.2 Window elements

The main window includes the following elements:		
Menu bar	Provides access to all of the application's features	
Toolbar	Shortcuts for the most common menu commands	
Item type selector	Selects which type of item is shown in the item list	
Item list	Displays the names or identifiers of all items contained in the trader	
Item description	Provides a textual summary of the selected item	

Menu bar Provides access to all of the application's features	
Status bar	Displays information about the trader to which the console is currently connected, including the host, port and IDL interface

### 9.2.3 The Toolbar

The toolbar contains buttons for the most common menu commands.



Figure 6: Trader Console toolbar

### 9.2.4 Terms used in Trader Console

The Trader Service Console uses the term *item* to generically refer to the four types of data managed by a trader service:

- Service types
- Offers
- Proxy offers
- Links

The console window is used to browse these items. The window only shows one type of item at a time, which you can change with the **item type selector** drop-down list or by selecting a type from the **View** menu. When a new *item type* is selected, the current list of items is retrieved from the trader service and displayed in the **item list**.

# 9.3 The Trader Console Menus

## 9.3.1 The Console menu

You use the commands in the **Console** menu to manage the console windows.

New Window	Creates a new console window, connected to the current trader.
Connect	Opens the <b>Connect</b> dialog box, allowing you to connect to a different trader service.
Close	Closes the current console window. If this window is the last console window present, the application exits.
Exit	Quits the application.

### 9.3.2 The Edit menu

The console supports the typical notion of a clipboard, which can be manipulated with cut, copy and paste commands. However, the console does not use the system clipboard, and therefore the application clipboard can only be accessed by windows from the same execution of the application. In other words, if you start two instances of the application, you cannot cut and paste between them. You can cut and paste if you start a single instance of the application, and create multiple windows with the **Console/New Window** command.

Cut	Copies the selected items to the clipboard and then permanently removes the selected items
Сору	Copies the selected items to the clipboard
Paste	Pastes the items from the clipboard into the current trader
Select All	Selects all of the items in the item list
Clone	Creates a clone of the selected item. The appropriate dialog box is displayed to allow you to create a new item, but the fields of the dialog box are initialized with the values from the selected item.
Modify	Edits the currently selected item

Cut	Copies the selected items to the clipboard and then permanently removes the selected items
Delete	Permanently removes the selected items

### 9.3.3 Using the cut, copy and paste commands

There are some issues to be aware of when using the cut, copy and paste operations:

- Service types and links must have unique names; therefore, you will not be able to paste one of these items if an item already exists in the trader with the same name.
- A certain amount of forethought is advised when you wish to cut and paste service types. Since service types can inherit from other service types, you cannot cut a service type that has subtypes. If you wish to cut or delete a number of service types, and if inheritance relationships exist between any of them, you must cut the types that don't have any subtypes first. The same principle applies to pasting service types, in that you cannot paste a type if its supertypes do not exist or have not yet been pasted. It is recommended that you only operate on one service type at a time when using the cut, copy, paste or delete commands.

### 9.3.4 Using the Clone and Modify commands

Note the following when using the clone and modify operations:

- Some types of items, namely service types and proxy offers, cannot be modified. The **Modify** command (and its toolbar equivalent) are disabled while these types are displayed.
- The **Clone** and **Modify** commands operate on a single item at a time. If more than one item is currently selected, the application uses the first of the selected items.

### 9.3.5 The View menu

You use the **View** menu to select the type of items you wish to be displayed in the item list. Selecting a new type of item from this menu is equivalent to changing the setting of the item type selector.

The **Refresh** command causes the application to retrieve an updated list of items from the trader and display them in the item list. This command can be useful if you know (or suspect) that the list of items has been changed by some other client of the trader service.

### 9.3.6 The Insert menu

You use the **Insert** menu when you want to create a new item. It displays a dialog box in which you can supply the information about the new item. If you need to create a new item that is similar to an existing item, you can also use the **Edit/Clone** command.

### 9.3.7 The Tools menu

The commands available in the **Tools** menu provide access to additional features of the trader service.

Query	Perform query operations on the trader and review the matching offers
Attributes	Configure the trader attributes
Withdraw Offers	Removes offers using a constraint expression
Mask Type	Masks the selected service type
Unmask Type	Unmasks the selected service type

# 9.4 Managing Service Types

## 9.4.1 IDL type support

Although the Trader Service supports properties with user-defined IDL types, the console only supports simple IDL types and sequences of simple IDL types.

Refer to Service Types for more information on service types.

## 9.4.2 Adding a new service type

To add a new service type:

1. Select **Insert/Service Type**. The **New Service Type** dialog box appears as shown below.

🌺 New Service Type	×
Service type name:	
Interface:	
	Browse
Super types	
	Add
	Delete
Properties	
	Add
	Edit
	Delete
	OK Cancel

Figure 7: New Service Type dialog box

- 2. Enter a name for the service type in the **Service type name** text box. The name must be unique among all of the service types managed by the trader.
- 3. Enter an interface repository identifier in the **Interface** text box. If the interface repository service is available, clicking the **Browse...** button displays an interface repository browser as shown below.

🌺 Interface Repository Browser	×
Select an interface:	
📑 Interface Repository	٦
ID:	
OK Cancel	

Figure 8: Browsing for an interface

- 4. The browser displays only modules and interfaces. When you select an interface, its identifier is displayed in the **ID** text box below. Click **OK** to accept the identifier you have selected.
- 5. Use the **Add...** and **Delete** buttons to add and remove super types. Clicking the **Add...** button displays the **Super Types** dialog box as shown below. Select any service types you wish to use as super types for the new type and click **OK**. The order in which you add super types is not important.

🌺 Super Types	×
Select super types:	
Printer	
OK Cance	
	_

Figure 9: Selecting super types

6. Use the **Add...**, **Edit...** and **Delete** buttons to manipulate the properties for this service type. Clicking the **Add...** or **Edit...** buttons displays the **Property** dialog box as shown below. Enter a name for the property, select a property type, and use the checkboxes to indicate the mode of this property. Click

🌺 Property	×
Name:	
Type:	
boolean	
Mode	
🗌 Mandatory	🗌 Read-only
	OK Cancel

OK to add the new property.

Figure 10: Adding a property

7. Click **OK** on the **New Service Type** dialog box to add the new service type.

### 9.4.3 Removing a service type

To remove a service type, do the following:

- 1. Select View/Service Types to display the service types in the item list.
- 2. Select the service type you wish to remove.
- 3. Select Edit/Delete. A confirmation dialog appears.
- 4. Click **Yes** to permanently remove the service type.

### **Note**

If a service type has subtypes, you will not be able to remove the type until all of its subtypes have been removed.

### 9.4.4 Masking a service type

To mask a service type, do the following:

- 1. Select View/Service Types to display the service types in the item list.
- 2. Select the service type you wish to mask.
- 3. Select Tools/Mask Type.

### 9.4.5 Unmasking a service type

To unmask a service type, do the following:

- 1. Select View/Service Types to display the service types in the item list.
- 2. Select the service type you wish to unmask.
- 3. Select Tools/Unmask Type.

## 9.5 Managing Offers

### 9.5.1 Adding a new offer

To add a new offer, do the following:

1. Select Insert/Offer. The New Offer dialog box appears as shown below.

🌺 New Offer	×
Service type:	
Printer	-
IOR O From file Browse	
Properties	
Property       Value         ✓       bldg         ✓       color         ✓       cost_per_page         ✓       ppm	Add Dynamic Reset
	K Cancel

Figure 11: Adding a new offer

- 2. Select a service type from the drop-down list. Each time you select a service type, the **Properties** table is updated to reflect the properties defined for that service type.
- 3. Select a method for specifying the object reference for this offer. Select the **IOR** toggle if you want to paste the stringified interoperable object reference into the text box. If you want the application to read the reference from a file, select **From file** and enter the filename in the text box, or click the **Browse...** button to display a file selection dialog box. If the trader service is configured to allow nil objects, and you do not wish to specify an object reference for this offer, you may leave the object reference blank.
- 4. Enter values for the properties in the **Properties** table. All properties have a checkbox to the left of the property name. For a mandatory property, the checkbox is disabled, meaning that a value must be provided for this property. For an optional property, you can use the checkbox to indicate whether this property should be included with the offer. To enter a value for a property, double-click on the property value field. For properties with sequence types, you can enter multiple values by separating them with commas. Press **Return** when you are finished entering the value for a property.

5. Click the **Add...** button if you wish to add a property that is not defined by the service type. The **Add Property** dialog box appears as shown below. Enter a name for the property, select the property's type from the drop-down list, and enter a value in the text box. The name you use for the property must not be the same as any existing properties. Click **OK** to add the property to the **Properties** 

	鸄 Add Property	×
	Name:	
	Type:	
	boolean Value:	
table.		OK Cancel

Figure 12: Adding a property

### **Note**

Once the property has been added to the **Properties** table, you can edit it directly, just as you can with any other property. If you later decide that you do not want to include the property with the offer, simply uncheck the property's checkbox.

6. If you wish to make a property dynamic, select the property and click the **Dynamic...** button. The **Dynamic Property** dialog box appears as shown below. Select a method for specifying an object reference as outlined in step 3 above. If you wish to include additional data, select a type from the drop-down list and enter a value in the text box. Click **OK** to save the dynamic property. The property table displays <dynamic> as the value of a dynamic property.

🌺 Dynamic Property - color 🛛 💌	1
IOR O From file Browse	
Extra information:	
Value:	
OK Cancel	

Figure 13: Making a property dynamic

- 7. To clear the value of a property, select the property and click **Reset**. You can use this command to convert a property from a dynamic property to a regular property.
- 8. Click **OK** to add the new offer. The application validates the information and reports any errors in a dialog box.

#### **Note**

For properties of type string, an empty value is accepted as a valid value, even for mandatory properties.

## 9.5.2 Modifying an offer

To modify an offer, do the following:

- 1. Select View/Offers to display the offers in the item list.
- 2. Select the offer you wish to modify.
- 3. Select Edit/Modify. The Edit Offer dialog box appears as shown below.

Properties	Value	
Property V bidg	Value Bidg 1	Add
✓ color	TRUE	Dynamic
🗹 cost_per_page	0.25	
🗹 ppm	5	Reset
🗹 queue	HP Color LaserJet	
		OK Cancel

Figure 14: Editing an offer

- 4. You can modify a property by double-clicking on the property value. Press **Return** when you have finished editing a property value.
- 5. You can remove an existing property from the offer (if it is an optional property) by unchecking its checkbox. Similarly, you can add a property to the offer by checking its checkbox and entering a value for the property.

- 6. See the discussion of adding a new offer above for details on adding new properties and configuring dynamic properties.
- 7. Click **OK** to update the offer.

## 9.5.3 Withdrawing offers

There are two distinct ways to withdraw offers. The first way is by selecting individual offers, as outlined below:

- 1. Select View/Offers to display the offers in the item list.
- 2. Select the offer(s) you wish to withdraw.
- 3. Select Edit/Delete. A confirmation dialog appears.
- 4. Click **Yes** to withdraw the offers.

The above method is suitable for withdrawing a limited number of specific offers. A more efficient method for removing a large quantity of offers for a single type, or for removing offers without having to manually search for the right ones, is by withdrawing offers with a constraint expression:

1. Select **Tools/Withdraw Offers**. The **Withdraw Offers** dialog box appears as shown below.

🌺 Withdraw Offers	×
Service type: Printer	
Constraint:	
	OK Cancel

Figure 15: Withdrawing an offer

- 2. Select the service type from the drop-down list. Offers with this service type or a subtype of this service type are considered for withdrawal.
- 3. Enter a constraint expression in the text box. See Service Types for more information on constraint expressions.
- 4. Click **OK** to withdraw the offers. Only offers that match the constraint expression are withdrawn. An error message appears if no matching offers were found.

### **Q** Note

A simple way to remove all of the offers for a service type is to use **TRUE** for the constraint expression.

# 9.6 Managing Proxy Offers

## 9.6.1 Adding a new proxy offer

To add a new proxy offer, do the following:

1. Select **Insert/Proxy Offer**. The **New Proxy Offer** dialog box appears as shown below.

鸄 New Proxy Offer			×
Service type:			
Printer			-
Target Lookup IOR	O From file	Browse	
Constraint recipe:			
🗌 If match all			
Properties			
Property		Value	Add
<ul> <li>✓ bldg</li> <li>✓ color</li> </ul>			
cost_per_page			Dynamic
🗹 ppm			Reset
value due due due due due due due due due d			
Policies to pass on			
			Add
			Edit
			Delete
		Oł	Cancel

Figure 16: Adding a new proxy offer

- 2. Select a service type from the drop-down list. Each time you select a service type, the property table is updated to reflect the properties defined for that service type.
- 3. Select a method for specifying the object reference of the target CosTrading::Lookup object for this proxy offer. Select the **IOR** toggle if you want to paste the stringified interoperable object reference into the text box. If you want the application to read the reference from a file, select **From file** and enter the filename in the text box, or click the **Browse...** button to display a file selection dialog box.
- 4. Enter the constraint recipe in the text box.
- 5. Select **If match all** if a matching service type is all that is required for this proxy offer to be considered a match during a query.
- 6. Enter values for the properties in the **Properties** table. See Adding a new offer for more information on entering offer properties.
- 7. Use the **Add...**, **Edit...** and **Delete** buttons to manipulate the policies to be passed on to the target object. Clicking the **Add...** or **Edit...** buttons displays the **Policy** dialog box as shown below.

🌺 Policy	X
Name:	
Type:	
double	<b></b>
Value:	
	OK Cancel

Figure 17: Adding a policy to a proxy offer

8. Click **OK** to add the new proxy offer. The application validates the information and reports any errors in a dialog box.

### 9.6.2 Withdrawing proxy offers

To withdraw a proxy offer, do the following:

- 1. Select View/Proxy Offers to display the proxy offers in the item list.
- 2. Select the proxy offer you wish to withdraw.
- 3. Select Edit/Delete. A confirmation dialog appears.
- 4. Click Yes to withdraw the proxy offer.

## 9.7 Managing Links

### 9.7.1 Adding a new link

To add a new link, do the following:

1. Select Insert/Link. The New Link dialog box appears as shown below.

🌺 New Link	×
Name:	
Target Lookup IO	R O From file Browse
Default follow rule	Always
Limiting follow rule	Always
	OK Cancel

Figure 18: Adding a link

- 2. Enter a name for this link in the text box.
- 3. Select a method for specifying the target trader's object reference for this link. Select the **IOR** toggle if you want to paste the stringified interoperable object reference into the text box. If you want the application to read the reference from a file, select **From file** and enter the filename in the text box, or click the **Browse...** button to display a file selection dialog box.
- 4. Select the appropriate link-follow rules from the drop-down lists.
- 5. Click **OK** to add the new link.

## 9.7.2 Modifying a link

To modify a link, do the following:

- 1. Select View/Links to display the links in the item list.
- 2. Select the link you wish to modify.
- 3. Select Edit/Modify. The Edit Link dialog box appears.
- 4. Update the settings for the link-follow rules.
- 5. Click **OK** to update the link.

## 9.7.3 Removing a link

To remove a link, do the following:

- 1. Select View/Links to display the links in the item list.
- 2. Select the link you wish to remove.
- 3. Select Edit/Delete. A confirmation dialog appears.
- 4. Click Yes to remove the link.

# 9.8 Configuring the Trader Attributes

## 9.8.1 Configuring attributes

To configure the trader attributes, select **Tools/Attributes**. The **Attributes** dialog box appears, containing a tabbed folder with four tabs.

🎘 Attributes	×
Support Import Link Admin	
☑ Supports modifiable properties	
Supports dynamic properties	
Supports proxy offers	
Service Type Repository	
IOR From file Browse	
090000001000101000000000000000000000000	]
OK Car	icel

Figure 19: Configuring trader attributes

The tabs provide access to the attributes from the following four IDL interfaces:

- CosTrading::SupportAttributes
- CosTrading::ImportAttributes
- CosTrading::LinkAttributes
- CosTrading::Admin

Each of the tabs is described below. Click **OK** when you have finished modifying the attributes.

### 9.8.2 Support Attributes

#### Supports modifiable properties

If enabled, the trader considers offers with modifiable properties (that is, properties that are not readonly) during a query, unless the importer requests otherwise with the use\_modifiable\_properties policy. If disabled, the trader does not consider offers with modifiable properties, regardless of the importer's wishes. This setting also determines the behavior of the modify operation in the CosTrading::Register interface. If enabled, the server allows modification of offers. If disabled, the modify operation raises the NotImplemented exception.

### Supports dynamic properties

If enabled, the trader considers offers with dynamic properties during a query, unless the importer requests otherwise with the use\_dynamic\_properties policy. If disabled, the trader does not consider offers with dynamic properties, regardless of the importer's wishes. The trading service specification does not define the behavior of a trader when this option is disabled and an offer is exported that contains dynamic properties; however, the Trader Service always accepts offers containing dynamic properties.

### Supports proxy offers

If enabled, the trader considers proxy offers during a query, unless the importer requests otherwise with the use\_proxy\_offers policy. If disabled, the trader does not consider proxy offers, regardless of the importer's wishes. This setting also determines the behavior of the proxy\_if attribute in the CosTrading::SupportAttributes interface. If enabled, proxy\_if returns the reference of the server's CosTrading::Proxy object. If disabled, proxy\_if returns nil.

### Service type repository

The IOR of the service type repository currently in use by the trader is displayed in the text box. In order to change the service type repository, you first need to select a method for specifying its object reference. Select the **IOR** toggle if you want to paste the stringified IOR into the text box. If you want the application to read the reference from a file, select **From file** and enter the filename in the text box, or click the **Browse...** button to display a file selection dialog box.

## 9.8.3 Import Attributes

### **Import attributes**

Many of the Import attributes have default and maximum values. The default value is used if an importer does not supply a value for the corresponding importer policy. The maximum value is used as the allowable upper limit for the importer policy. If an importer supplies a policy value that is greater than the maximum value, the importer's policy value is overridden and the maximum value is used

E	🏂 Attributes		X
	Support Import	Link Admin	
		Default	Maximum
	Search cardinality	2147483647	2147483647
	Match cardinality	2147483647	2147483647
	Return cardinality	2147483647	2147483647
	Link hop count	2147483647	2147483647
	Link follow policy	Always 💌	Always 💌
	Maximum list count	2147483647	
			OK Cancel
instead.			

Figure 20: Import attributes

### Search cardinality

The number of offers to be searched during a query. The corresponding importer policy is search\_card.

### **Match cardinality**

The number of matched offers to be ordered during a query. The corresponding importer policy is match\_card.

### **Return cardinality**

The number of ordered offers to be returned by a query. The corresponding importer policy is return\_card.

### Link hop count

The depth of links to be traversed during a query. The corresponding importer policy is hop\_count .

### Link follow policy

The trader's behavior when considering whether to follow a link during a query. The default value is used if an importer does not specify a value for the link\_follow\_rule policy. The maximum value overrides the policy established for a link as well as the link\_follow\_rule policy proposed by an importer.

### Maximum list count

The maximum number of items to be returned from any operation that returns a list, such as the list\_offers operation in CosTrading::Admin or the next\_n operation in CosTrading::OfferIterator. This attribute may override the number of items requested by a client.

### 9.8.4 Link Attributes

#### Link attributes

Support	Import Link	Admin		
	link follow policy	Always	•	

The following is the Link Attributes pane.

Figure 21: Link attributes

#### Maximum link follow policy

Determines the server's upper bound on the value of a link's limiting follow rule at the time of creation or modification of a link. The server raises the LimitingFollowTooPermissive exception if a link's limiting follow rule exceeds the value of this attribute.

# 9.9 Admin Attributes

### 9.9.1 Admin attributes

The following is the Admin attributes pane.

🌺 Attributes	×
Support Import Link Admin	_
Request identifier stem	
OK	<u>!</u>

Figure 22: Admin attributes

## 9.9.2 Request identifier stem

The request identifier stem is used as a prefix by the server to generate unique request identifiers during a federated query. Although the IDL attribute request\_id\_stem returns a sequence of octets, this property is defined in terms of a string, with the characters of the string comprising the octets of the stem. You need to provide a value for this property only if the server will have links to other traders and you want to ensure that circular links are handled correctly.

# 9.10 Executing Queries

### 9.10.1 Executing a query

To execute a query, do the following:

1. Select Tools/Query. The Query dialog box appears as shown below.

🅾 Query	×
Service type:	
Printer	-
Constraint:	
Preference:	
☑ Desired properties:	
color	
Query Policies Close	

Figure 23: Executing a query

- 2. Select a service type from the drop-down list.
- 3. Enter a constraint expression in the **Constraint** text box.
- 4. (Optional) Enter a preference expression in the **Preference** text box. If this field is blank, the trader uses a default preference expression of "first".
- 5. If you wish to specify which properties are returned in the matching offers, click **Desired properties** to activate the text box below and enter the names of the properties in the text box. Use commas to separate the property names.
- 6. To include importer policies, click the **Policies**... button. The **Policies** dialog box appears as shown below. Next to each field label is a checkbox. You must check the box for a policy for it to be included in your query. Click the **Defaults** button to load the trader's default import attributes into the fields of

the dialog box. Click <b>OK</b> to accept your changes.					
SQuery Policies		×			
Exact type match	No	ОК			
Use modifiable properties	Yes	Cancel			
Use dynamic properties	Yes	Defaults			
Use proxy offers	Yes 💌				
🔲 Search cardinality	2147483647				
🔲 Match cardinality	2147483647				
🔲 Return cardinality	2147483647				
Link follow policy	Always 💌				
🗆 Link hop count	2147483647				

Figure 24: Query policies

7. Click Query to execute the query operation. If matching offers were found, the Query Results dialog box appears as shown below. You can scroll through the matching offers with the < and > buttons. Click Close when you have finished examining the results.

🌺 Query Results	×		
Offer < 1	ffer < 1 > of 5		
Object reference:			
IOR:00494f500000001f49444c3a5472616465724465			
Properties:			
Name	Value		
bldg	Bldg 2		
color	FALSE		
cost_per_page	0.15		
ppm	8		
queue	SUNprinter		
1			
	Close		

#### Figure 25: Query results

### **Note**

The Query Results dialog box cannot be used to edit offers.

## 9.11 Connecting to a New Trader

When the console is started, the first console window to appear is already connected to the trader you specified using the command line options. If you are managing multiple traders, you can connect to a different trader with the **Console/Connect** command. The **Connect** dialog appears as shown below.

🌺 Connect	×
Trader IOR	
O IOR from file	Browse
🔘 Link	
	•
	OK Cancel

Figure 26: The Connect dialog box

There are three methods of connecting to the trader.

- 1. To provide the stringified object reference, select the **Trader IOR** option and paste the IOR into the text box.
- 2. To obtain the stringified object reference from a file, select **IOR from file** and enter the filename in the text box, or click the **Browse...** button to display a file selection dialog box.
- 3. To connect to a linked trader, select the **Link** option and choose the link from the drop-down list.

Click **OK** to connect to the trader. The contents of the current console window are updated to reflect the new trader.

### **Q** Note

If you want to be connected to two or more traders at the same time, use the **Console/New Window** command to create a new console window, then select **Console/Connect** to connect the new window to another trader.

# **10. The OMG Constraint Language**

This appendix provides the BNF specification of the CORBA standard constraint language (reproduced from Annex B in the OMG Trading Object Specification with the kind permission of the OMG). It is used for specifying both the constraint and preference expression parameters to various operations in the trader interfaces.

# **10.1 Introduction**

## 10.1.1 Statement

A statement in this language is an Istring. Other constraint languages may be supported by a particular trader implementation; the constraint language used by a client of the trader is indicated by embedding " <<Identifier major.minor>> " at the beginning of the string. If such an escape is not used, it is equivalent to embedding " <<OMG 1.0>> " at the beginning of the string.

# **10.2 Language Basics**

# 10.2.1 Basic elements

Both the constraint and preference expressions in a query can be constructed from property names of conforming offers and literals. The constraint language in which these expressions are written consists of the following items (examples of these expressions are shown in square brackets below each bulleted item):

- Comparative functions:
  - == (equality)
  - != (inequality)

```
>, >=, <, <=
```

- substring match),
- in (element in sequence)

The result of applying a comparative function is a boolean value. ["Cost < 5" implies only consider offers with a Cost property value less than 5; "'Visa' in CreditCards" implies only consider offers in which the CreditCards property, consisting of a set of strings, contains the string 'Visa']

Boolean connectives:

and

or

not

["Cost >= 2 and Cost <= 5" implies only consider offers where the value of the Cost property is in the range 2 <= Cost <= 5]

• Property existence:

exist

- Property names
- Numeric and string constants
- mathematical operators:

+, -, \*, /

["10 < 12.3 \* MemSize + 4.6 \* FileSize" implies only consider offers for which the arithmetic function in terms of the value of the MemSize and FileSize properties exceeds 10]

• grouping operators:

( )

Note that the keywords in the language are case sensitive.

### **10.2.2 Precedence relations**

The following precedence relations hold in the absence of parentheses, in the order of highest to lowest:

```
() exist unary-minus
not
* /
+ -
~
in
== != < <= > >=
and
or
```

### 10.2.3 Legal property value types

While one can define properties of service types with arbitrarily complex IDL value types, only the following property value types can be manipulated using the constraint language:

- boolean, short, unsigned short, long, unsigned long, float, double, char, Ichar, string, Istring
- sequences of the above types

The exist operator can be applied to any property name, regardless of the property's value type.

exist	can be applied to any property
~	can only be applied if left operand and right operand are both strings or both Istrings
in	can only be applied if the left operand is one of the simple types described above and the right operand is a sequence of the same simple type
==	can only be applied if the left and right operands are of the same simple type
! =	can only be applied if the left and right operands are of the same simple type
<	can only be applied if the left and right operands are of the same simple type
<=	can only be applied if the left and right operands are of the same simple type
>	can only be applied if the left and right operands are of the same simple type
>=	can only be applied if the left and right operands are of the same simple type

## **10.2.4 Operator restrictions**

+	can only be applied to simple numeric operands
-	can only be applied to simple numeric operands
*	can only be applied to simple numeric operands
/	can only be applied to simple numeric operands

The comparative functions <, <= , >, >= imply use of the appropriate collating sequence for characters and strings; TRUE is greater than FALSE for booleans.

## **10.2.5 Representation of literals**

boolean	TRUE or FALSE
integers	sequences of digits, with a possible leading + or -
floats	digits with decimal point, with optional exponential notation
characte rs	char and Ichar are of the form ' <char> ', string and Istring are of the form ' <char> <char> + '; to embed an apostrophe in a string, place a backslash ( \ ) in front of it; to embed a backslash in a string, use \\ .</char></char></char>

# **10.3 The Constraint Language BNF**

# 10.3.1 The constraint language proper in terms of lexical tokens

```
<constraint> := /* empty */
| <bool>
<preference> := /* <empty> */
| min <bool>
| max <bool>
| with <bool>
| random
| first
<bool> := <bool_or>
<bool_or> := <bool_or> or <bool_and>
| <bool_and>
<bool_and> := <bool_and> and <bool_compare>
<bool_compare> := <expr_in> == <expr_in>
| <expr_in> != <expr_in>
| <expr_in> < <expr_in>
| <expr_in> <= <expr_in>
| <expr_in> > <expr_in>
| <expr_in> >= <expr_in>
| <expr_in>
<expr_in> := <expr_twiddle> in <Ident>
| <expr_twiddle>
<expr_twiddle> := <expr> ~ <expr>
| <expr>
<expr> := <expr> + <term>
| <expr> - <term>
| <term>
<term> := <term> * <factor_not>
| <term> / <factor_not>
| <factor_not>
<factor_not> := not <factor>
| <factor>
<factor> := ( <bool_or> )
| exist <Ident>
| <Ident>
| <Number>
- <Number>
| <String>
| TRUE
| FALSE
```

### 10.3.2 "BNF" for lexical tokens up to character set issues

```
<Ident> := <Leader> <FollowSeq>
<FollowSeq> := /* <empty> */
| <FollowSeq> <Follow>
<Number> := <Mantissa>
| <Mantissa> <Exponent>
<Mantissa> := <Digits>
| <Digits> .
| . <Digits>
| <Digits> . <Digits>
<Exponent> := <Exp> <Sign> <Digits>
<Sign> := +
- |
<Exp> := E
| e
<Digits> := <Digits> <Digit>
| <Digit>
<String> := ' <TextChars> '
<TextChars> := /* <empty> */
| <TextChars> <TextChar>
<TextChar> := <Alpha>
| <Digit>
| <0ther>
| <Special>
<Special> := \\
| \rangle'
```

### 10.3.3 Character set issues

The previous BNF has been complete up to the non-terminals <Leader>, <Follow>, <Alpha>, <Digit>, and <Other>. For a particular character set, one must define the characters which make up these character classes.

Each character set which the trading service is to support must define these character classes. This annex defines these character classes for the ASCII character set.

<Leader> := <Alpha> <Follow> := <Alpha> | <Digit> | \_ <Alpha> is the set of alphabetic characters [A-Za-Z] <Digit> is the set of digits [0-9] <Other> is the set of ASCII characters that are not <Alpha>, <Digit>, or <Special>

# **11. Glossary**

#### Α

#### ART

Adaptive Runtime Technology. A modular, distributed object architecture, which supports dynamic deployment and configuration of services and application code. ART provides the foundation for Orbix software products.

#### С

#### CFR

See configuration repository.

#### client

An application (process) that typically runs on a desktop and requests services from other applications that often run on different machines (known as server processes). In CORBA, a client is a program that requests services from CORBA objects.

#### configuration

A specific arrangement of system elements and settings.

#### configuration domain

Contains all the configuration information that Orbix ORBs, services and applications use. Defines a set of common configuration settings that specify available services and control ORB behavior. This information consists of configuration variables and their values. Configuration domain data can be implemented and maintained in a centralized Orbix configuration repository or as a set of files distributed among domain hosts. Configuration domains let you organize ORBs into manageable groups, thereby bringing scalability and ease of use to the largest environments. See also configuration file and configuration repository.

#### configuration file

A file that contains configuration information for Orbix components within a specific configuration domain. See also configuration domain.

#### configuration repository

A centralized store of configuration information for all Orbix components within a specific configuration domain. See also configuration domain.

#### configuration scope

Orbix configuration is divided into scopes. These are typically organized into a root scope and a hierarchy of nested scopes, the fullyqualified names of which map directly to ORB names. By organizing configuration properties into various scopes, different settings can be provided for individual ORBs, or common settings for groups of ORB. Orbix services, such as the naming service, have their own configuration scopes.

#### CORBA

Common Object Request Broker Architecture. An open standard that enables objects to communicate with one another regardless of what programming language they are written in, or what operating system they run on. The CORBA specification is produced and maintained by the OMG. See also OMG.

#### CORBA objects

Self-contained software entities that consist of both data and the procedures to manipulate that data. Can be implemented in any programming language that CORBA supports, such as C++ and Java.

#### D

#### deployment

The process of distributing a configuration or system element into an environment.

#### Ι

#### IDL

Interface Definition Language. The CORBA standard declarative language that allows a programmer to define interfaces to CORBA objects. An IDL file defines the public API that CORBA objects expose in a server application. Clients use these interfaces to access server objects across a network. IDL interfaces are independent of operating systems and programming languages.

#### IFR

See interface repository.

#### IIOP

Internet Inter-ORB Protocol. The CORBA standard messaging protocol, defined by the OMG, for communications between ORBs and distributed applications. IIOP is defined as a protocol layer above the transport layer, TCP/IP.

#### implementation repository

A database of available servers, it dynamically maps persistent objects to their server's actual address. Keeps track of the servers available in a system and the hosts they run on. Also provides a central forwarding point for client requests. See also location domain and locator daemon.

#### IMR

See implementation repository.

#### installation

The placement of software on a computer. Installation does not include configuration unless a default configuration is supplied.

#### Interface Definition Language

See IDL.

#### interface repository

Provides centralized persistent storage of IDL interfaces. An Orbix client can query this repository at runtime to determine information about an object's interface, and then use the Dynamic Invocation Interface (DII) to make calls to the object. Enables Orbix clients to call operations on IDL interfaces that are unknown at compile time.

#### invocation

A request issued on an already active software component.

#### IOR

Interoperable Object Reference. See object reference.

#### L

#### location domain

A collection of servers under the control of a single locator daemon. Can span any number of hosts across a network, and can be dynamically extended with new hosts. See also locator daemon and node daemon.

#### locator daemon

A server host facility that manages an implementation repository and acts as a control center for a location domain. Orbix clients use the locator daemon, often in conjunction with a naming service, to locate the objects they seek. Together with the implementation repository, it also stores server process data for activating servers and objects. When a client invokes on an object, the client ORB sends this invocation to the locator daemon, and the locator daemon searches the implementation repository for the address of the server object. In addition, enables servers to be moved from one host to another without disrupting client request processing. Redirects requests to the new location and transparently reconnects clients to the new server instance. See also location domain, node daemon, and implementation repository.

#### Ν

#### naming service

An implementation of the OMG Naming Service Specification. Describes how applications can map object references to names. Servers can register object references by name with a naming service repository, and can advertise those names to clients. Clients, in turn, can resolve the desired objects in the naming service by supplying the appropriate name. The Orbix naming service is an example.

#### node daemon

Starts, monitors, and manages servers on a host machine. Every machine that runs a server must run a node daemon.

#### 0

#### object reference

Uniquely identifies a local or remote object instance. Can be stored in a CORBA naming service, in a file or in a URL. The contact details that a client application uses to communicate with a CORBA object. Also known as interoperable object reference (IOR) or proxy.

#### OMG

Object Management Group. An open membership, not-for-profit consortium that produces and maintains computer industry specifications for interoperable enterprise applications, including CORBA. See www.omg.com.

#### ORB

Object Request Broker. Manages the interaction between clients and servers, using the Internet Inter-ORB Protocol (IIOP). Enables clients to make requests and receive replies from servers in a distributed computer environment. Key component in CORBA.

#### Ρ

#### POA

Portable Object Adapter. Maps object references to their concrete implementations in a server. Creates and manages object references to all objects used by an application, manages object state, and provides the infrastructure to support persistent objects and the portability of object implementations between different ORB products. Can be transient or persistent.

#### protocol

Format for the layout of messages sent over a network.

#### S

#### server

A program that provides services to clients. CORBA servers act as containers for CORBA objects, allowing clients to access those objects using IDL interfaces.

#### Т

#### trader service

An implementation of the OMG CORBA Trading Object Service Specification. Facilitates the offering and the discovery of services. Other objects can use it to advertise their capabilities and to match their needs against those of advertised services.

# 12. Notices

# 12.1 Copyright

© 1996-2025 Rocket Software, Inc. or its affiliates. All Rights Reserved.

# 12.2 Trademarks

Rocket is a registered trademark of Rocket Software, Inc. For a list of Rocket registered trademarks go to: www.rocketsoftware.com/about/legal. All other products or services mentioned in this document may be covered by the trademarks, service marks, or product names of their respective owners.

# 12.3 Examples

This information might contain examples of data and reports. The examples include the names of individuals, companies, brands, and products. All of these names are fictitious and any similarity to the names and addresses used by an actual business enterprise is entirely coincidental.

# 12.4 License agreement

This software and the associated documentation are proprietary and confidentical to Rocket Software, Inc. or its affiliates, are furnished under license, and may be used and copied only in accordance with the terms of such license.

Note: This product may contain encryption technology. Many countries prohibit or restrict the use, import, or export of encryption technologies, and current use, import, and export regulations should be followed when exporting this product.

# 12.5 Corporate information

Rocket Software, Inc. develops enterprise infrastructure products in four key areas: storage, networks, and compliance; database servers and tools; business information and analytics; and application development, integration, and modernization.

Website: www.rocketsoftware.com

# **12.6 Contacting Technical Support**

The Rocket Community is the primary method of obtaining support. If you have current support and maintenance agreements with Rocket Software, you can access the Rocket Community and report a problem, download an update, or read answers to FAQs. To log in to the Rocket Community or to request a Rocket Community account, go to www.rocketsoftware.com/support. In addition to using the Rocket Community to obtain support, you can use one of the telephone numbers that are listed above or send an email to support@rocketsoftware.com.

Rocket Global Headquarters 77 4th Avenue, Suite 100 Waltham, MA 02451-1468 USA

# 12.7 Country and Toll-free telephone number

To contact Rocket Software by telephone for any reason, including obtaining pre-sales information and technical support, use one of the following telephone numbers.

- United States: 1-855-577-4323
- Australia: 1-800-823-405
- Belgium: 0800-266-65
- Canada: 1-855-577-4323
- China: 400-120-9242
- France: 08-05-08-05-62
- Germany: 0800-180-0882
- Italy: 800-878-295
- Japan: 0800-170-5464
- Netherlands: 0-800-022-2961
- New Zealand: 0800-003210
- South Africa: 0-800-980-818
- United Kingdom: 0800-520-0439