

VisiBroker Installation Guide

V8.5.9

Table of Contents

Planning Your Installation	5
Package contents	5
System requirements	5
JDK	6
Licensing	6
Replacing an earlier version of VisiBroker	7
Installing the Service Pack	8
What's next?	8
Installing VisiBroker on Windows	9
Installing VisiBroker	9
Before installation	9
Installing VisiBroker and related components	9
Configuring VisiBroker license variables	13
Uninstalling VisiBroker	14
Installing VisiBroker on Solaris	15
Installing VisiBroker	15
Before installation	15
Mounting the VisiBroker DVD on Solaris	15
Installing VisiBroker and related components	16
Running the installer without a GUI	20
Configuring VisiBroker license variables	20
Uninstalling VisiBroker	21
Installing VisiBroker on Linux	22
Installing VisiBroker	22
Before installation	22
Mounting the VisiBroker DVD on Linux	22
To Install VisiBroker and related components	23
Running the installer without a GUI	27

Configuring VisiBroker license variables	27
Uninstalling VisiBroker	28
Installing VisiBroker on IBM AIX	29
Installing VisiBroker	29
Before installation	29
To Install VisiBroker and related components	30
Running the Installer without a GUI	33
Configuring VisiBroker license variables	34
Uninstalling VisiBroker	34
Installing VisiBroker on HP-UX	35
Installing VisiBroker	35
Before installation	35
To Install VisiBroker and related components	35
Running the Installer without a GUI	39
Configuring VisiBroker license variables	39
Uninstalling VisiBroker	40
Installing VisiBroker in Console Mode	41
Installing VisiBroker	41
Start the installer in console mode on Solaris	41
Using the installer	42
Registering the license in console mode after installation	45
Installing VisiBroker Using Silent Installation	47
What is Silent Installation?	47
Using Silent Installation	47
Silent Installation on Windows	48
Silent Installation on Solaris	49
Silent Installation on Linux	50
Silent Installation on IBM AIX	50
Silent Installation on HP-UX	51
Properties File for Silent Installation	52
Sample Silent Installation Properties for Windows	53

Sample Silent Installation Properties for Solaris	54
Sample Silent Installation Properties for Linux	54
Sample Silent Installation Properties for IBM AIX	54
Sample Silent Installation Properties for HP-UX	54
Product Registration	56
Registration methods	56
Direct registration	57
Email registration	57
Web page registration	58
Telephone registration	58
To register and activate a license after installation	58
Verifying installation and registration	59
Cleaning up and re-registering a license	60
Cleanup instructions	60
Notices	62
Copyright	62
Trademarks	62
Examples	62
License agreement	62
Corporate information	63
Contacting Technical Support	63
Country and Toll-free telephone number	63

Planning Your Installation

This guide describes installation and installation-related tasks for installing VisiBroker 8.5.9 on Windows and on supported UNIX platforms.

Other documentation can be found at the Rocket documentation site.

Some recommendations:

- Typically, you install VisiBroker on a large, shared UNIX or Windows machine.
- Installing the examples is optional, however Rocket Software recommends you do install them.

Package contents

If you have received a physical installation package, it contains the VisiBroker DVD. Your package may include additional products that ship with VisiBroker.

You may alternatively have downloaded the installation.

System requirements

For the latest information on platforms supported by VisiBroker and for JDK requirements, refer to www.rocketsoftware.com/support.

In addition to platform-specific requirements, VisiBroker components use TCP and UDP Broadcast services to communicate. Even if you are running the components on a single machine you must have TCP and UDP services available.

JDK

For information on the JDK versions that are supported for running VisiBroker, refer to www.rocketsoftware.com/support.

A JDK is no longer redistributed with VisiBroker.

A JRE is not sufficient for installing VisiBroker.

If your VisiBroker installation binary is 64-bit, then your JDK must be 64-bit as well.



Ω Note

If you choose a 32-bit version of VisiBroker 8.5.n, then you would normally need a 32-bit JDK. If, however, you want to use a 32-bit VisiBroker installer (because for example you need to compile and run 32-bit C++ CORBA applications), but you want to use a 64-bit JDK, then you can do so.

Run the 32-bit installer but select your 64-bit JDK during the installation process. After installation is complete, you will need to patch your installation with a VisiBroker 64-bit Service Overlay.

This overlay is provided as a .zip or .tax file that is unpacked over the installation. Refer to www.rocketsoftware.com/support for further information.

Note that you can run java -version to make sure that you have installed the intended version of JDK (that is, 32 or 64-bit).

Licensing

All VisiBroker licenses are locked to the system on which they are applied and activated. You cannot copy these licenses to another system, and they cannot be accessed from a VisiBroker product running on another system. If you reinstall the software on the same system, you will need to reactivate the license.

VisiBroker node-locked licenses must be registered and activated before using the product. To apply the licenses you will need:

• The serial number and key, or the activation file for each license.

These will arrive in an email from Rocket Software.

· A user name and password.

This is needed for product registration. Note that the main bdn.boxland.com address is no longer in use. However:

- If you have an existing Borland Developer Network account, you can use the credentials for that account.
- If you have a Borland Developer Network login, but have forgotten your password, go to https://my.embarcadero.com/ and select **Reset my password**.
- If you do not have an account, for example because you are a new VisiBroker user, you can create one at www.rocketsoftware.com/support.
- Alternatively, you can create an account using the VisiBroker Product Registration Wizard, during the registration/activation process described in Product Registration.

Make sure that you record the user name and password that you create.

Internet access.

This is required if you want to use the Direct or Web page methods for activating your license. For web activation, your internet access can be from any system, but for direct activation you need internet access from the system on which your product is installed. If you choose the Web option, you must be able to receive emails to the address that you specified when creating the BDN account.

If you are applying a license to a remote system, you must have Telnet access to that system and some way to copy (that is, FTP) the activation file to that system.

Replacing an earlier version of VisiBroker

You cannot install this version of VisiBroker in the same location as a previous version. Either:

Uninstall the previous version

or:

Install the new version in a different location from any other existing versions

If you have already installed an evaluation version and have since purchased a license to use VisiBroker on a permanent basis, you do not need to reinstall the version of the software you evaluated. See Cleaning up and re-registering a license for information on how to remove your evaluation license, then add and activate your new, permanent license. For information on activating your new license, see Product Registration.

Installing the Service Pack

If you install VisiBroker as a new customer, you do not need to install this Service Pack separately. It is included in your installation package.

Existing users of VisiBroker 8.5 who want to upgrade to this Service Pack should follow the instructions in its accompanying *Release Notes* to install the Service Pack on top of their existing installation.

What's next?

Once you have planned your network installations, you are ready to install VisiBroker.

The following sections give platform-specific details.

Installing VisiBroker on Windows

This section describes how to install VisiBroker and related components on Windows.

Installing VisiBroker

Ensure that you have the prerequisites described in System requirements.

Before installation

Before you install VisiBroker, select the installation method:

- Download the product from the email sent by Rocket Software.
- Download a trial version of the product from https://www.rocketsoftware.com.
- If you are installing from DVD, place the DVD in your drive.

Installing VisiBroker and related components

If you want to perform a silent installation using definitions from a properties file, see Silent Installation on Windows.

Otherwise, depending how you have obtained the VisiBroker installer:

- If you are installing from DVD and autorun is enabled on your system, the installer automatically starts when you insert the DVD into your drive.
- If you have downloaded a VisiBroker installer from the web, navigate to the directory where you have downloaded the installer. Double-click the downloaded executable to start the installation.

Follow the onscreen instructions. For most options, defaults offered by the installation wizard are acceptable. You can click **Previous** to return to earlier screens and change any information that is incorrect.

b Important

Once you select which product you are installing and click **Next**, if you want to select a different product, you must cancel the current installation and restart the installation process.

- 1. The installer prepares and a splash screen briefly displays.
- 2. Introduction: Read the Introduction and click Next.
- 3. **License agreement:** Read the licensing agreement carefully and accept it in order to install and use VisiBroker.
- 4. Choose Install Folder: You can select an empty folder to create a new installation of VisiBroker, or you can specify the location of an existing VisiBroker installation in order to add components to it. Either accept the default (C:\MicroFocus\VisiBroker) or click Choose to specify another location. Note that you cannot install this version of VisiBroker on top of previous releases; you can only specify an existing location in order to add components.
- 5. **Choose Product Components:** You can choose the scope of the installation from the **Install Set** list. The default is **Complete Installation**, which enables you to select any or all of the components.

Note

VisiBroker Console is no longer automatically installed. It is available as an optional component. To install, please download and extract the

\PRODUCT_VERSION_opt_GUI_\PLATFORM\.tar.gz | archive or the \PRODUCT_VERSION_opt_GUI_\PLATFORM\.zip archive onto your product installation.

The GUI components archive can be downloaded from the Rocket Customer Community. Among other benefits, this site provides access to product license keys and install kits, including the relevant GUI components.

The GUI components have been separated from the product as they do not fully comply with the Section 508 and WCAG accessibility requirements and guidelines. It is intended that future product releases will include updated GUI components that comply with the relevant accessibility guidelines.

Depending on the Install Set you choose, you can select from the following product components. By default, all components are selected. You can choose to de-select any components that you do not need. For example, you could de-select the **Examples** option. The options are:

- a. VisiBroker Core: The development tools and server components for VisiBroker for Java and for C++.
- **b. Examples:** Example applications for VisiBroker.

- **c. VisiBroker Services:** Optional components that you can purchase for extended VisiBroker functionality. You can select the specific services you have purchased later in the installation procedure, in Step 2.
- 1. **VisiBroker Core Configuration:** VisiBroker is supported in C++ and Java. By default **VisiBroker for Java and C++** is selected here.
- 2. **Choose VisiBroker Services:** Displays if you chose the option to install **VisiBroker Services** in Step 5 above. Select the services you have purchased. By default, no services are selected:
 - a. VisiNotify: An industrial strength, ORB-level implementation of the OMG Event/Notification Service.
 - b. VisiSecure: A framework for establishing secure connections between clients and servers.
 - c. **VisiTransact:** A complete implementation of the OMG transaction management solution for transactions with CORBA applications over the internet or intranets.
- 3. Choose Install Type: Choose:
 - a. Typical to use default settings, including:
 - a. **Smart Agent port:** Also known as the <code>osagent</code> . Client-side ORBs use this port to locate server objects before invoking their services. The default is <code>14000</code> .
 - b. **VisiBroker bin folder**: By default this is not added to your PATH. If you select the default, you may have to add certain components to your environment path manually.
 - c. **VisiBroker environment variables:** By default, these variables are not added to your system environment.
 - b. **Custom** to customize your installation. If you select this, you can:
 - a. Set the Smart Agent port (osagent) to a value other than its default: see Step 4.
 - b. Include the VisiBroker bin folder in your PATH: see Step 7.
 - c. Include the VisiBroker environment variables: see Step 8.
- 4. **Configuration Settings:** This appears if you selected **Custom** installation. Specify a setting for the Smart Agent port. The default is 14000.
- 5. **Choose Shortcut Folder:** Choose where to install a VisiBroker shortcut icon. You can install a shortcut in any one of:
 - a. A new program group (default).
 - b. An existing program group.
 - c. The **Start** menu.
 - d. The desktop.

- e. The Quick Launch bar.
- f. Another selected folder, which you can browse for, or you can choose not to create icons at all.
- By default, icons are created for all users, but you can disable this option.
- 6. **Java Development Kit:** Enter the path of the JDK to be used for this installation. See JDK for details of the JDK versions that you can use.
- 7. **Modification of PATH:** This dialog appears if you selected **Custom** installation type in Step 3. Specify whether to include the VisiBroker bin folder in your PATH. The default is **No**. To add the directory to your PATH, choose **Yes**.
- 8. **Modification of system environment:** This also appears if you selected **Custom** installation type in Step 3. Specify whether to include the VisiBroker environment variables. The default is **No**. To add the VisiBroker environment variables to your system environment, choose **Yes**. The installation sets the variable BES_LIC_DIR to \install_dir\var and BES_LIC_DEFAULT_DIR to \install_dir\ license.
- 9. **Pre-Installation Summary:** Review the displayed information before proceeding with the installation. Verify in particular the install folder location and the product features that you have specified. To confirm your choices and start installing, click **Install**.
- 10. **Registration:** You must register and activate your license before you can start to use VisiBroker. This dialog gives you the choice to register now, or to do so at a later date. You are recommended to accept the default **Yes** and register now. If you do so, the Product Registration Wizard dialog appears in a separate window.

Select **No** and click **Next** if you want to register later. See To register and activate a license after installation for information about how to do this.

Registering your license

The most straightforward method of registering VisiBroker is to enter the serial number and license key and choose direct registration, as described in this section. Other methods are described in Product Registration.

- 1. Product Registration Wizard: Select Have Serial Number.
- 2. **Serial Number:** Enter the 20-character serial number and the 6-character license key supplied with your installation into the respective fields.
- 3. Select Registration Method: Choose Direct.
- 4. **Account Information:** This is specified as a prerequisite for installing VisiBroker. See A username and password for information. Choose **I have an account**.
 - If you have not yet set up a developer network account, select **I do not have an account**. The wizard prompts you for the information to create an account.
- 5. **Account Information:** Enter your developer network account information.

- 6. **Proxy settings:** If you have any proxies configured, check **I use a proxy** and enter your proxy information. If you do not use proxies, just click **Next**.
- 7. **Information Summary:** Check the information you have entered and, if it is correct, click **Next**. Click **Back** if you want to change anything.
- 8. **Direct Registration:** This dialog box shows how your registration is progressing. When registration is complete, the **Done** button is enabled. Click **Done**.

Closing the installer

Install Complete: This dialog appears when you complete the Product Registration Wizard dialog, or if you select **No** when asked to register. Click **Done** to finish.

The install log

The installer generates an install log that is written to the root of the installation directory if you installed VisiBroker from DVD, or to the folder where the installer file resides if you used a downloaded file to install VisiBroker.

The VisiBroker install log file is:

\install_dir\VisiBroker_InstallLog.xml

The file is an XML formatted log with installation-specific information, such as errors.

Using the VisiBroker documentation

The VisiBroker DVD contains a complete library of online documentation. You can also access the documentation online

Configuring VisiBroker license variables

Before running a VisiBroker server or client, or VisiBroker services, you need to set two license environment variables (BES_LIC_DIR and BES_LIC_DEFAULT_DIR). During installation, a batch script is created for you to use for setting these environment variables.

To set these variables:

- 1. Open a command window.
- 2. Change directories to \install dir\bin.
- 3. Execute vbroker.bat. Verifying installation and registration

To verify that you have installed and registered VisiBroker correctly:

- 1. Open a windows command prompt and go to the \VBROKERDIR\bin folder. (The default value for \VBROKERDIR\ is C:\MicroFocus\ VisiBroker.)
- 2. Setup the VisiBroker environment by running vbroker.bat.
- 3. Go to the sample folder \VBROKERDIR\examples\vbroker\basic\bank_agent to compile and run the server to verify if the installation has been installed properly.
- 4. Compile the example using the supported compiler for the operating system where you are installing VisiBroker. For the compilers supported by this release of VisiBroker, see www.rocketsoftware.com/ support.
- 5. Assuming the "nmake" command is in the PATH, enter "nmake -f Makefile_cpp" for a C++ example and "vbmake.bat" for a Java example.
- 6. Once the compilation is successful, run "osagent" from the same folder. This is a lookup service from where clients will receive the server's IOR.
- 7. Start the server as follows:

For VisiBroker for C++:

server.exe

For VisiBroker for Java:

vbj Server

The server starts and displays the object reference which is hosted by this server.

Uninstalling VisiBroker

To uninstall VisiBroker:

- 1. Make sure there are no background processes (such as osagent) running during the uninstall.
- 2. Open the UninstallerData folder in the installation directory.
- 3. Double-click Uninstall.exe.
- 4. The Uninstall wizard opens. Click Uninstall to completely remove all components that were installed.

Ω Note

Uninstalling does not remove files and folders that were created after the installation. After you run the uninstall program, remove the installation directory.

There may also still be files and folders stored in the user's Documents and Settings or Users folders. For example, ..bdp65. You should delete these as well.

Installing VisiBroker on Solaris

This section describes how to install VisiBroker and related components on the Solaris operating system.

Installing VisiBroker

Ensure that you have the prerequisites described in System requirements.

Before installation

Before you install VisiBroker, select the installation method:

- Download the product from the email sent by Rocket Software.
- Download a trial version of the product from https://www.rocketsoftware.com.
- If you are installing from DVD, place the DVD in your drive.

Mounting the VisiBroker DVD on Solaris

The VisiBroker DVD includes installation software for the Solaris operating systems. This section describes how to prepare to install VisiBroker on Solaris from DVD.

To mount a DVD on your local workstation:

- 1. Log in.
- 2. Insert the DVD into the drive.
- 3. Open a command shell.
- 4. To determine if the Volume Manager is running, enter the command:

```
/usr/bin/ps -ef | grep mountd
```

To see a list of all running processes, look for a response similar to the following:

```
root 247 1 0 Oct 30? 0:00/usr/lib/autofs/automountd
```

- 5. If the Volume Manager is running, proceed to Installing VisiBroker and related components.
- 6. If the Volume Manager is not running, you need superuser privileges to mount the DVD. Become root, then enter the following commands to mount the DVD:

/usr/sbin/mount -F hsfs-r /dev/dsk/device/cdrom

where device is the device name of the DVD.

7. Enter the following command to change to the DVD directory:

cd /cdrom

8. To unmount the DVD after installing VisiBroker, become root and enter the following command:

umount /cdrom

Installing VisiBroker and related components

If you want to perform a silent installation using definitions from a properties file, see Silent Installation on Solaris.

You can either download the VisiBroker installer from the web or install from DVD.

If installing VisiBroker from DVD:

- 1. Log in as a non-root user. Make sure that the user name you select has read/write access to the folder where you intend to install VisiBroker.
- 2. Mount the DVD.
- 3. Enter the following command to launch the installer:

install_solaris

The installation wizard launches in a separate window.

4. Select the product you want to install.

Follow the installation wizard's onscreen instructions. For most options, defaults offered by the installation wizard are acceptable. You can use the **Previous** button to return to earlier screens and change any information that is incorrect.

If installing VisiBroker on Solaris from a downloaded file:

- 1. Log in as a non-root user. Make sure that the user name you select has read/write access to the folder where you intend to install VisiBroker.
- 2. Invoke the appropriate command to launch the installer:

```
vb8.5-<release number>-solaris-<arch>.bin
```

where <arch> may be x32 or x64.

Or see Start the installer in console mode on Solaris.

- 1. Follow the installation wizard's onscreen instructions. For most options, defaults offered by the installation wizard are acceptable. You can use the **Previous** button to return to earlier screens and change any information that is incorrect.
- 2. Select the VisiBroker product you want to install.

6 Important

- Once you select which product you are installing and click **Next**, if you wish to select a different product you must cancel the current installation and restart the installation process.
- You cannot install this version of VisiBroker on top of previous releases.
- 3. Introduction: Read the Introduction and click Next.
- 4. **License agreement:** Read the licensing agreement carefully and accept it to install and use VisiBroker.
- 5. **Choose Install Folder:** This creates a new installation of VisiBroker, or adds components to an existing installation. Either accept the default <code>/opt/MicroFocus/VisiBroker</code> or choose another location. Ensure that the user name you are using has write access to the chosen folder.
 - Note that you cannot install this version of VisiBroker on top of previous releases. however, you can specify an existing location to add components.
- 6. **Choose Product Components:** Depending on the VisiBroker product you are installing, you can select from the following product components.

⊘ Note

VisiBroker Console is no longer automatically installed. It is available as an optional component. To install, please download and extract the \<PRODUCT_VERSION\>_opt_GUI_\<PLATFORM\>.tar.gz archive or \<PRODUCT_VERSION\>_opt_GUI_\<PLATFORM\>.zip archive onto your product installation.

The GUI components archive can be downloaded from the Rocket Customer Community. Among other benefits, this site provides access to product license keys and installkits, including the relevant GUI components.

The GUI components have been separated from the product as they do not fully comply with the Section 508 and WCAG accessibility requirements and guidelines. It is intended that future product releases will include updated GUI components that comply with the relevant accessibility guidelines.

By default, the components are all selected. You can choose to de-select any components which you do not need. For example, you could de-select the *Examples* option. The options are:

- 1. VisiBroker Core: The development tools and server components for VisiBroker for Java and C++.
- 2. Examples: Example applications for VisiBroker.
- 3. **VisiBroker Services:** Optional components that you can purchase for extended VisiBroker functionality. You can select the specific services you have purchased later in the installation procedure.
- 7. **Choose VisiBroker Services:** Displays if you chose the option to install **VisiBroker Services** in Step 4. Select the services you have purchased. By default, no services are selected:
 - a. VisiNotify: An industrial strength, ORB-level implementation of the OMG Event/Notification Service.
 - b. VisiSecure: A framework for establishing secure connections between clients and servers.
 - c. **VisiTransact:** A complete implementation of the OMG transaction management solution for transactions with CORBA applications over the Internet or intranets.
- 8. Choose Install Type: Choose:
 - a. Typical to use default settings, including:
 - a. **Smart Agent port:** Also known as osagent. Client-side ORBs use this port to locate server objects before invoking their services. The default is 14000.
 - b. **Agent name**: Every agent using the same Smart Agent (osagent) port should have a unique name. The default is the host name.
 - b. **Custom** to customize your installation. If you select this, you can:

- a. Set the Smart Agent port (osagent) to a value other than its default. This port is used by the ORB to communicate with the server. You can choose any value between 5000 and 65535 . The default is 14000 .
- b. You can choose the default JDK. If you don't want to use the default JDK, select the JDK home path by clicking the **Choose** button. See JDK for details of the JDK versions that you can use.
- 9. **Pre-Installation Summary:** Review the displayed information before proceeding with the installation. Verify in particular the install folder location and the product features that you have specified. To confirm your choices and start installing, click **Install**.
- 10. **Registration:** You must register and activate your license before you can start to use VisiBroker. On this platform, you cannot register VisiBroker now, but must click **Next** to register later. The ways to do this are described in Product Registration. The preferred method is direct registration as described in To register and activate a license after installation.

Closing the installer

Install Complete: This dialog appears when you have completed the installation. Click **Done** to finish.

The install log

The installer generates an install log that is written to the root of the installation directory if you installed VisiBroker from DVD, or to the folder where the installer file resides if you used a downloaded file to install VisiBroker.

The VisiBroker install log file is:

<install_dir>/VisiBroker_InstallLog.xml

The file is an XML formatted log with installation-specific information, such as errors.

Using the VisiBroker documentation

The VisiBroker DVD contains a complete library of online documentation. You can also access the documentation online.

Running the installer without a GUI

The installer is capable of running in a text only mode (console mode) for UNIX systems. You can invoke the installer with a parameter which specifies that mode. You can run the installer in text-only mode as follows.

Using an installation DVD:

```
install solaris -i console
```

Using a downloaded installer:

```
<install_file>.bin -i console
```

where <install_file> is the name of the downloaded file.

Then see Installing VisiBroker in console mode for further information.

Configuring VisiBroker license variables

Before running a VisiBroker server or client, or VisiBroker services, you need to set two license environment variables (BES_LIC_DIR and BES_LIC_DEFAULT_DIR). During installation, a shell script is created for you to use for setting these environment variables.

To set these variables:

- 1. Open a command window.
- 2. Change directories to <install_dir>/bin.
- 3. Determine the appropriate script for your shell:

If you are using the Korn or Bourne shell, use the following script to set environment variables:

```
$ .<space><install_dir>/bin/vbroker.sh
```

or:

\$ source<space><install_dir>/bin/vbroker.sh

If you are using the C shell, use the following script to set environment variables:

```
$ .<space><install_dir>/bin/vbroker.csh
```

or:

\$ source<space><install_dir>/bin/vbroker.csh

4. To run the script automatically when you log in, add a command to your <code>.profile</code>, <code>.cshrc</code>, or <code>.login</code> file.

Uninstalling VisiBroker

To uninstall VisiBroker:

- 1. Make sure there are no background processes (such as osagent) running during the uninstall.
- 2. Change directories to the VisiBroker UninstallerData directory.
- 3. Enter the uninstall command:

uninstall



⊘ Note

Uninstalling does not remove files and folders that were created after the installation. After you run the uninstall program, remove the installation directory.

Installing VisiBroker on Linux

This section describes how to install VisiBroker and related components on Red Hat Enterprise Linux and SUSE Linux Enterprise Server operating systems.

Installing VisiBroker

Ensure that you have the prerequisites described in System requirements.

Before installation

Before you install VisiBroker, select the installation method:

- Download the product from the email sent by Rocket Software.
- Download a trial version of the product from Rocket Software.
- If you are installing from DVD, place the DVD in your drive.

Mounting the VisiBroker DVD on Linux

The VisiBroker DVD includes installation software for the Linux operating system. This section describes how to prepare to install VisiBroker on Linux from DVD.

To manually mount the DVD on Linux:

- 1. Log in as a user with root authority.
- 2. Insert the DVD in the drive and enter the following command:

```
# mount -t iso9660 -o ro /dev/cdrom /cdrom
```

where /cdrom represents the mount point of the DVD To mount the DVD using auto-mounting software:

If you are using auto-mounting software, the DVD is mounted automatically to the directory specified in your auto-mount configuration when you insert it into the DVD drive.

To check if you have auto-mounting software, use the following command:

```
$ ps aux | grep automount
```

If you do have auto-mounting software, the output should be similar to the following:

```
root 628 0.0 0.2 1148 588 ? S 17:32 0:00 /usr/sbin/ automount
```

To unmount the DVD after installing VisiBroker, go to root and enter one of the following commands:

- umount /cdrom (if you have manually mounted the DVD)
- eject cdrom (if you have used auto-mounting software to mount the DVD)

To Install VisiBroker and related components

If you want to perform a silent installation using definitions from a properties file, see Silent Installation on Linux.

You can either download the VisiBroker installer from the web or install from DVD.

If installing VisiBroker from DVD:

- 1. Log in as a non-root user. Make sure that the user name you select has read/write access to the folder where you intend to install VisiBroker.
- 2. Mount the DVD.
- 3. Enter the following command to launch the installer:
 - \$ /cdrom/install_linux

where <code>/cdrom</code> is the directory where the DVD is mounted, or see Start the installer in console mode on Linux.

Important: Make sure the Mozilla /usr/bin is in your path in order to use the default browser.

The DVD splash screen appears after a few moments. The installation wizard launches a separate window.

To view the Readme and installation documentation on the DVD, or to browse the contents of the DVD, click the appropriate entries on the splash screen.

If installing VisiBroker from the web:

- 1. You can install VisiBroker from the Rocket Software web site.
- 2. Log in as a non-root user. Make sure that the user name you select has read/write access to the folder where you intend to install VisiBroker.
- 3. Enter the following command to launch the installer:

```
vb85-<release number>-linux-<platform>-<arch>.bin
```

where <platform> is either rh5 or suse10 and <arch> is either x86 or x86_64.

The installation wizard launches in a separate window.

Using the installation wizard

Follow the installation wizard's onscreen instructions. For most options, defaults offered by the installation wizard are acceptable. You can use the **Previous** button to return to earlier screens and change any information that is incorrect.

- 1. Introduction: Read the Introduction and click Next.
- 2. **License agreement:** Read the licensing agreement carefully and accept it to install and use VisiBroker.
- 3. **Choose Install Folder:** This creates a new installation of VisiBroker, or adds components to an existing installation. Either accept the default <code>/opt/MicroFocus/VisiBroker</code> or choose another location. Ensure that the user name you are using has write access to the chosen folder.
 - Note that you cannot install this version of VisiBroker on top of previous releases. However, you can specify an existing location to add components.

4. **Choose Product Components:** > depending on the VisiBroker product you are installing, you can select from the following product components.

Note

VisiBroker Console is no longer automatically installed. It is available as an optional component. To install, download and extract the <PRODUCT_VERSION>_opt_GUI_<PLATFORM>.tar.gz archive or <PRODUCT_VERSION>_opt_GUI_<PLATFORM>.zip archive onto your product installation.

The GUI components archive can be downloaded from the Rocket Customer Community. Among other benefits, this site provides access to product license keys and install kits, including the relevant GUI components.

The GUI components have been separated from the product as they do not fully comply with the Section 508 and WCAG accessibility requirements and guidelines. It is intended that future product releases will include updated GUI components that comply with the relevant accessibility guidelines.

By default, the components are all selected. You can choose to de-select any components which you do not need. For example, you could de-select the *Examples* option. The options are:

VisiBroker Core: The development tools and server components for VisiBroker for Java and C++.

Examples: Example applications for VisiBroker.

VisiBroker Services: Optional components that you can purchase for extended VisiBroker functionality. You can select the specific services you have purchased later in the installation procedure.

- 5. **Choose VisiBroker Services**: Displays if you chose the option to install **VisiBroker Services** in Step 4. Select the services you have purchased. By default, no services are selected:
 - a. VisiNotify: An industrial strength, ORB-level implementation of the OMG Event/Notification Service.
 - b. VisiSecure: A framework for establishing secure connections between clients and servers.
 - c. **VisiTransact:** A complete implementation of the OMG transaction management solution for transactions with CORBA applications over the Internet or intranets.

Important: Once you select which product you are installing and click **Next**, then if you wish to select a different product you must cancel the current installation and restart the installation process.

- 6. Choose Install Type: Choose:
 - a. **Typical**: an express install using default settings, including:
 - a. **Smart Agent port:** Also known as the osagent . Client-side ORBs use this port to locate server objects before invoking their services. The default is 14000.
 - b. **VisiBroker bin folder**: Typical install does not add this to your PATH. If you select the default, you may have to add certain components to your environment path manually.

- c. VisiBroker environment variables: Typical install does not add these variables to your system environment.
- b. **Custom** to customize your installation. If you select this, you can:
 - a. Set the Smart Agent port (osagent) to a value other than its default.
 - b. You can choose the default IDK. If you don't want to use the default IDK, select the IDK home path by clicking **Choose**. See JDK for details of the JDK versions that you can use.
 - c. Specify whether to include the VisiBroker bin folder in your PATH. The default is No. To add the directory to your PATH, choose Yes.
 - d. Specify whether to include the VisiBroker environment variables. The default is No. To add the VisiBroker environment variables to your system environment, choose Yes. The installation sets the variable BES_LIC_DIR to <install_dir>/var and BES_LIC_DEFAULT_DIR to <install_dir>/license.
- 7. Pre-Installation Summary: Review the displayed information before proceeding with the installation. Verify in particular the install folder location and the product features that you have specified. To confirm your choices and start installing, click **Install**.
 - The status bar provides information about the installation process. After the installation is complete, the **Registration** page displays
- 8. Registration: You must register and activate your license before you can start to use VisiBroker. On this platform, you cannot register VisiBroker now, but must click **Next** to register later. The ways to do this are described in Product Registration. The preferred method is direct registration as described in To register and activate a license after installation.

Closing the installer

Install Complete: This dialog appears when you have completed the installation. Click **Done** to finish.



Ω Note

When VisiBroker is installed in NFS mounted directories, and if there is insufficient disk space for the system temp directory, post installation cleanup process might not remove all the temporary files as the NFS server periodically locks files in the directories. To resolve this, you must manually clean the temporary directories and files after installation.

The install log

The installer generates an install log that is written to the root of the installation directory if you installed VisiBroker from DVD, or to the folder where the installer file resides if you used a downloaded file to install VisiBroker.

The VisiBroker install log file is:

```
<install_dir>/VisiBroker_InstallLog.xml
```

The file is an XML formatted log with installation-specific information, such as errors.

Using the VisiBroker documentation

The VisiBroker DVD contains a complete library of online documentation. You can also access the documentation online.

Running the installer without a GUI

The installer is capable of running in a text only mode (console mode) for UNIX systems. You can invoke the installer with a parameter which specifies that mode. You can run the installer in text-only mode as follows:

Using an installation DVD:

```
install Linux install -i console
```

Using a downloaded installer:

```
vb85-<release number>-linux-<platform>-<arch>.bin -i console
```

where <platform> is either rh5 or suse10 and <arch> is either x86 or x86_64.

Then see Installing VisiBroker in console mode for further information.

Configuring VisiBroker license variables

Before running a VisiBroker server or client, or VisiBroker services, you need to set two license environment variables (BES_LIC_DIR and BES_LIC_DEFAULT_DIR). During installation, a shell script is created for you to use for setting these environment variables.

To set these variables:

- 1. Open a UNIX shell.
- 2. Change directories to <install dir>/bin.
- 3. Determine the appropriate script for your shell. If you are using the Korn or Bourne shell, use the following script to set environment variables:

```
$ .<space><install_dir>/bin/vbroker.sh
```

or:

\$ source<space><install_dir>/bin/vbroker.sh

If you are using the C shell, use the following script to set environment variables:

\$.<space><install_dir>/bin/vbroker.csh

or:

- \$ source<space><install_dir>/bin/vbroker.csh
- 4. To run the script automatically when you log in, add a command to your <code>.profile</code> , <code>.cshrc</code> , or <code>.login</code> file.

Uninstalling VisiBroker

To uninstall VisiBroker:

- 1. Make sure there are no background processes (such as osagent) running during the uninstall.
- 2. Change directories to the <install_root>/UninstallerData directory.
- 3. Enter the appropriate uninstall command.

For VisiBroker installed from a DVD:

uninstall

For VisiBroker installed from a downloaded installer:

vb85-<release number>-linux-<platform>-<arch>.bin - uninstall

where <platform> is rh5 or suse10, and <arch> is x86 or x86_64.

⊘ Note

Uninstalling does not remove files and folders that were created after the installation. After you run the uninstall command, check the installation directory and remove any unnecessary files and subdirectories.

Installing VisiBroker on IBM AIX

This section describes how to install VisiBroker and related components on IBM AIX operating systems.

Installing VisiBroker

Ensure that you have the prerequisites described in System requirements.

Before installation

Before you install VisiBroker, select the installation method:

- Download the product from the email sent by Rocket Software.
- Download a trial version of the product from https://www.rocketsoftware.com.
- If you are installing from DVD, place the DVD in your drive.

Mounting the VisiBroker DVD on IBM AIX

The VisiBroker DVD includes installation software for the IBM AIX operating systems. This section describes how to prepare to install VisiBroker on IBM AIX from DVD.

To manually mount the DVD on IBM AIX:

- 1. Log in.
- 2. Insert the DVD in the drive and enter the following command:

```
# mount -v cdrfs -o ro /dev/cd0 /cdrom
```

where /cdrom represents the mount point of the DVD To mount the DVD using auto-mounting software:

If you are using auto-mounting software, the DVD is mounted automatically to the directory specified in your auto-mount configuration when you insert it into the drive.

To check if you have auto-mounting software, use the following command:

```
$ ps aux \| grep automount
```

If you have auto-mounting software, the output should be similar to the following:

```
root 628 0.0 0.2 1148 588 ? S 17:32 0:00 /usr/sbin/ automount
```

To unmount the DVD after installing VisiBroker, go to root and enter one of the following commands:

- umount /cdrom (if you have manually mounted the DVD)
- eject cdrom (if you have used auto-mounting software to mount the DVD)

To Install VisiBroker and related components

If you want to perform a silent installation using definitions from a properties file, see Silent Installation on IBM AIX.

You can either download the VisiBroker installer from the web or install from DVD.

If installing VisiBroker from DVD:

- 1. Log in as a non-root user. Make sure that the user name you select has read/write access to the folder where you intend to install VisiBroker.
- 2. Mount the DVD.
- 3. Enter the following command to launch the installer:

```
$ install_aix
```

The installation wizard launches in a separate window.

If installing VisiBroker from the web:

- 1. You can install VisiBroker from the Rocket Software web site.
- 2. Log in as a non-root user. Make sure that the user name you select has read/write access to the folder where you intend to install VisiBroker.
- 3. Enter the following command to launch the installer:

```
vb85-<release number>-aix-<arch>.bin
where <arch> is one of ppc32 or ppc64.
```

Alternatively, see Start the installer in console mode on IBM AIX.

Using the installation wizard

Follow the installation wizard's onscreen instructions. For most options, defaults offered by the installation wizard are acceptable. You can use the **Previous** button to return to earlier screens and change any information that is incorrect.

- 1. Introduction: Read the Introduction and click Next.
- 2. **License agreement:** Read the licensing agreement carefully and accept it to install and use VisiBroker.
- 3. **Choose Install Folder:** This creates a new installation of VisiBroker, or adds components to an existing installation. Either accept the default <code>/opt/MicroFocus/VisiBroker</code> or choose another location. Ensure that the user name you are using has write access to the chosen folder.

Ω Note

You cannot install this version of VisiBroker on top of previous releases; but you can specify an existing location in order to add components.

4. **Choose Product Components:** Depending on the VisiBroker product you are installing, you can select from the following product components.

Note

VisiBroker Console is no longer automatically installed. It is available as an optional component. To install, download and extract the <PRODUCT_VERSION>_opt_GUI_<PLATFORM>.tar.gz archive or <PRODUCT_VERSION>_opt_GUI_<PLATFORM>.zip archive onto your product installation.

The GUI components archive can be downloaded from the Rocket Customer Community. Among other benefits, this site provides access to product license keys and install kits, including the relevant GUI components.

The GUI components have been separated from the product as they do not fully comply with the Section 508 and WCAG accessibility requirements and guidelines. It is intended that future product releases will include updated GUI components that comply with the relevant accessibility guidelines.

By default, the components are all selected. You can choose to de-select any components which you do not need. For example, you could de- select the *Examples* option. The options are:

VisiBroker Core: The development tools and server components for VisiBroker for Java and C++.

Examples: Example applications for VisiBroker.

VisiBroker Services: Optional components that you can purchase for extended VisiBroker functionality. You can select the specific services you have purchased later in the installation procedure.

- 5. **Choose VisiBroker Services**: Displays if you chose the option to install **VisiBroker Services** in Step 4. Select the services you have purchased. By default, no services are selected:
 - a. VisiNotify: An industrial strength, ORB-level implementation of the OMG Event/Notification Service.
 - b. **VisiSecure:** A framework for establishing secure connections between clients and servers.

c. **VisiTransact:** A complete implementation of the OMG transaction management solution for transactions with CORBA applications over the Internet or intranets.

6 Important

Once you select which product you are installing and click **Next** then, if you wish to select a different product, you must cancel the current installation and restart the installation process.

- 6. Choose Install Type: Choose:
 - a. **Typical**: an express install using default settings, including:
 - **Smart Agent port:** Also known as the osagent . Client-side ORBs use this port to locate server objects before invoking their services. The default is 14000 .
 - **VisiBroker bin folder**: Typical install does not add this to your PATH. If you select the default, you may have to add certain components to your environment path manually.
 - **VisiBroker environment variables:** Typical install does not add these variables to your system environment.
 - b. **Custom** to customize your installation. If you select this, you can:
 - a. Set the Smart Agent port (osagent) to a value other than its default.
 - b. You can choose the default JDK. If you don't want to use the default JDK, select the JDK home path by clicking **Choose**. See JDK for details of the JDK versions that you can use.
 - c. Specify whether to include the VisiBroker bin folder in your PATH. The default is $_{No}$. To add the directory to your $_{PATH}$, choose $_{Yes}$.
 - d. Specify whether to include the VisiBroker environment variables. The default is No. To add the VisiBroker environment variables to your system environment, choose Yes. The installation sets the variable BES_LIC_DIR to <install_dir>/var and BES_LIC_DEFAULT_DIR to <install_dir>/license.
- 7. **Pre-Installation Summary:** Review the displayed information before proceeding with the installation. Verify in particular the install folder location and the product features that you have specified. To confirm your choices and start installing, click **Install**.
 - The status bar provides information about the installation process. After the installation is completed, the **Registration** page displays.
- 8. **Registration:** You must register and activate your license before you can start to use VisiBroker. OOn this platform, you cannot register VisiBroker now, but must click **Next** to register later. The ways to do this are described in Product Registration. The preferred method is direct registration as described in To register and activate a license after installation.

Closing the installer

Install Complete: This dialog appears when you have completed the installation. Click **Done** to finish.



Ω Note

When VisiBroker is installed in NFS mounted directories, and if there is insufficient disk space for the system temp directory, post installation cleanup process might not remove all the temporary files as the NFS server periodically locks files in the directories. To resolve this, you must manually clean the temporary directories and files after installation.

The install log

The installer generates an install log that is written to the root of the installation directory if you installed VisiBroker from DVD, or to the folder where the installer file resides if you used a downloaded file to install VisiBroker.

The VisiBroker install log file is:

```
<install_dir>/VisiBroker_InstallLog.xml
```

The file is an XML formatted log with installation-specific information, such as errors.

Using the VisiBroker documentation

The VisiBroker DVD contains a complete library of online documentation. You can also access the documentation online.

Running the Installer without a GUI

The installer is capable of running in a text only mode (console mode) for UNIX systems. You can invoke the installer with a parameter which specifies that mode. You can run the installer in text-only mode as follows:

Using an installation DVD:

```
install_aix install -i console
```

Using a downloaded installer:

```
vb85-<release number>-aix-<arch>.bin -i console
```

where <arch> is one of ppc32 or ppc64

Then see Installing VisiBroker in console mode for further information.

Configuring VisiBroker license variables

Before running a VisiBroker server or client, or VisiBroker services, you need to set two license environment variables (BES_LIC_DIR and BES_LIC_DEFAULT_DIR). During installation, a shell script is created for you to use for setting these environment variables.

To set these variables:

- 1. Open a UNIX shell.
- 2. Change directories to <install dir>/bin.
- 3. Determine the appropriate script for your shell. If you are using the Korn or Bourne shell, use the following script to set environment variables:

vbroker.sh

If you are using the C shell, use the following script to set environment variables:

vbroker.csh

4. To run the script automatically when you log in, add a command to your <code>.profile</code>, <code>.cshrc</code>, or <code>.login</code> file.

Uninstalling VisiBroker

To uninstall VisiBroker:

- 1. Make sure there are no background processes (such as osagent) running during the uninstall.
- 2. Change directories to the <install_root>/UninstallerData directory.
- 3. Enter the appropriate uninstall command. For VisiBroker installed from a DVD:

uninstall

or VisiBroker installed from a downloaded installer:

vb85-<release number>-aix-<arch>.bin -uninstall

where <arch> is one of ppc32 or ppc64.

⊘ Note

Uninstalling does not remove files and folders that were created after the installation. After you run the uninstall command, check the installation directory and remove any unnecessary files and subdirectories.

Installing VisiBroker on HP-UX

This section describes how to install VisiBroker and related components on HP-UX (Itanium) operating systems.

Installing VisiBroker

Ensure that you have the prerequisites described in System requirements.

Before installation

Before you install VisiBroker, select the installation method:

- Download the product from the email sent by Rocket Software.
- Download a trial version of the product from https://www.rocketsoftware.com.
- If you are installing from DVD, place the DVD in your drive.

To Install VisiBroker and related components

If you want to perform a silent installation using definitions from a properties file, see Silent Installation on HP-UX.

You can either download the VisiBroker installer from the web or install from DVD.

If installing VisiBroker from DVD:

- 1. Log in as a non-root user. Make sure that the user name you select has read/write access to the folder where you intend to install VisiBroker.
- 2. Mount the DV
- 3. Enter the following command to run the installer:
 - \$ install_hp

The installation wizard launches a separate window.

If installing VisiBroker from the web:

- 1. You can install VisiBroker from the Rocket Software web site.
- 2. Log in as a non-root user. Make sure that the user name you select has read/write access to the folder where you intend to install VisiBroker.
- 3. Enter the following command to launch the installer:

```
vb85-<release number>-hp-<arch>.bin
```

where <arch> is either ia32 or ia64.

The installation wizard launches in a separate window, or see Start the installer in console mode on HP-UX.

Using the installation wizard

Follow the installation wizard's onscreen instructions. For most options, defaults offered by the installation wizard are acceptable. You can use the **Previous** button to return to earlier screens and change any information that is incorrect.

- 1. Introduction: Read the Introduction and click Next.
- 2. **License agreement:** Read the licensing agreement carefully and accept it in order to install and use VisiBroker.
- 3. **Choose Install Folder:** This creates a new installation of VisiBroker, or adds components to an existing installation. Either accept the default /opt/MicroFocus/VisiBroker or choose another location. Ensure that the user name you are using has write access to the chosen folder.



You cannot install this version of VisiBroker on top of previous releases. However, you can specify an existing location to add components.

4. **Choose Product Components:** Depending on the VisiBroker product you are installing, you can select from the following product components.

⊘ Note

VisiBroker Console is no longer automatically installed. It is available as an optional component. To install, download and extract the <PRODUCT_VERSION>_opt_GUI_<PLATFORM>.tar.gz archive or <PRODUCT_VERSION>_opt_GUI_<PLATFORM>.zip archive onto your product installation.

The GUI components archive can be downloaded from the Rocket Customer Community.

The GUI components have been separated from the product as they do not fully comply with the Section 508 and WCAG accessibility requirements and guidelines. It is intended that future product releases will include updated GUI components that comply with the relevant accessibility guidelines.

By default, the components are all selected. You can choose to de-select any components which you do not need. For example, you could de- select the *Examples* option. The options are:

VisiBroker Core: The development tools and server components for VisiBroker for Java and C++.

Examples: Example applications for VisiBroker.

VisiBroker Services: Optional components that you can purchase for extended VisiBroker functionality. You can select the specific services you have purchased later in the installation procedure.

- 5. **Choose VisiBroker Services:** Displays if you chose the option to install **VisiBroker Services** in Step 4. Select the services you have purchased. By default, no services are selected:
 - a. VisiNotify: An industrial strength, ORB-level implementation of the OMG Event/Notification Service.
 - b. VisiSecure: A framework for establishing secure connections between clients and servers.
 - c. **VisiTransact:** A complete implementation of the OMG transaction management solution for transactions with CORBA applications over the Internet or intranets.

6 Important

Once you select which product you are installing and click **Next** then, if you want to select a different product, you must cancel the current installation and restart the installation process.

- 6. Choose Install Type: Choose:
 - a. **Typical**: an express install using default settings, including:
 - a. **Smart Agent port:** Also known as the osagent . Client-side ORBs use this port to locate server objects before invoking their services. The default is 14000 .
 - b. **VisiBroker bin folder:** Typical install does not add this to your PATH. If you select the default, you may have to add certain components to your environment path manually.

- c. VisiBroker environment variables: Typical install does not add these variables to your system environment.
- b. **Custom** to customize your installation. If you select this, you can:
 - a. Set the Smart Agent port (osagent) to a value other than its default.
 - b. You can choose the default IDK. If you don't want to use the default IDK, select the IDK home path by clicking **Choose**. See JDK for details of the JDK versions that you can use.
 - c. Specify whether to include the VisiBroker bin folder in your PATH. The default is No. To add the directory to your PATH, choose "Yes".
 - d. Specify whether to include the VisiBroker environment variables. The default is No. To add the VisiBroker environment variables to your system environment, choose Yes The installation sets the variable BES_LIC_DIR to <install_dir>/var and BES_LIC_DEFAULT_DIR to <install_dir>/license.
- 7. Pre-Installation Summary: Review the displayed information before proceeding with the installation. Verify in particular the install folder location and the product features that you have specified. To confirm your choices and start installing, click **Install**.
- 8. **Registration:** You must register and activate your license before you can start to use VisiBroker. On this platform, you cannot register VisiBroker now, but must click **Next** to register later. The ways to do this are described in Product Registration. The preferred method is direct registration as described in To register and activate a license after installation.

Closing the installer

Install Complete: This dialog appears when you have completed the installation. Click **Done** to finish.



Ω Note

When VisiBroker is installed in NFS mounted directories, and if there is insufficient disk space for the system temp directory, post installation cleanup process may not remove all the temporary files as the NFS server periodically locks files in the directories. To resolve this, you must manually clean the temp directories/files after installation.

The install log

The installer generates an install log that is written to the root of the installation directory if you installed VisiBroker from DVD, or to the folder where the installer file resides if you used a downloaded file to install VisiBroker.

The VisiBroker install log file is:

<install_dir>/VisiBroker_InstallLog.xml

The file is an XML formatted log with installation-specific information, such as errors.

Using the VisiBroker documentation

The VisiBroker DVD contains a complete library of online documentation. You can also access the documentation online.

Running the Installer without a GUI

The installer is capable of running in a text only mode (console mode) for UNIX systems. You can invoke the installer with a parameter which specifies that mode. You can run the installer in text-only mode as follows.

Using an installation DVD:

```
install_hp install -i console
```

Using a downloaded installer:

```
vb85-<release number>-hp-<arch>.bin -i console
```

where <arch> is either ia32 or ia64.

Then see Installing VisiBroker in console mode for further information.

Configuring VisiBroker license variables

Before running a VisiBroker for C++ server, VisiTransact, or VisiNotify, you need to set two license environment variables (BES_LIC_DIR and BES_LIC_DEFAULT_DIR). During installation, a shell script is created for you to use for setting these environment variables.

To set these variables:

- 1. Open a UNIX shell.
- 2. Change directories to <install dir>/bin.
- 3. Determine the appropriate script for your shell:

If you are using the Korn or Bourne shell, use the following script to set environment variables:

```
vbroker.sh
```

If you are using the C shell, use the following script to set environment variables:

```
vbroker.csh
```

4. To run the script automatically when you log in, add a command to your <code>.profile</code>, <code>.cshrc</code>, or <code>.login</code> file.

Uninstalling VisiBroker

To uninstall VisiBroker:

- 1. Make sure there are no background processes (such as osagent) running during the uninstall.
- 2. Change directories to the <install_root>/UninstallerData directory.
- 3. Enter the appropriate uninstall command.

For VisiBroker installed from a DVD:

uninstall

For VisiBroker installed from a downloaded installer:

vb85-<release number>-hp-<arch>.bin -uninstall

where <arch> is one of ia32 or ia64.

Note

Uninstalling does not remove files and folders that were created after the installation. After you run the uninstall command, check the installation directory and remove any unnecessary files and subdirectories.

Installing VisiBroker in Console Mode

The VisiBroker installer is capable of running in a text-only mode (console mode) for UNIX systems. You can invoke the installer with a parameter which specifies the UI mode.

This section describes how to run the installer in text-only mode.

Installing VisiBroker

Ensure that you have the prerequisites described in System requirements.

Start the VisiBroker installer

You can either download the VisiBroker installer from the web or install from a mounted DVD. The command that starts the installer depends on which UNIX platform you are installing on.

- 1. Log in as a non-root user. Make sure that the user name you select has read/write access to the folder where you intend to install VisiBroker.
- 2. Either mount the installation DVD or download the product from http://www.microfocus.com/products/corba/visibroker/index.aspx.
- 3. From the directory that contains the VisiBroker installer executable file, enter the appropriate command.

Start the installer in console mode on Solaris

Using an installation DVD:

install_solaris -i console

Using a downloaded installer:

<install_file>.bin -i console

where <install_file> is the name of the downloaded file.

Start the installer in console mode on Linux

Using an installation DVD:

```
install_Linux -i console
```

Using a downloaded installer:

```
vb85-<release number>-linux-<platform>-<arch>.bin -i console
```

where <platform> is either rh5 or suse10 and <arch> is either x86 or x86_64.

Start the installer in console mode on IBM AIX

Using an installation DVD:

```
install_aix -i console
```

Using a downloaded installer:

```
vb85-<release number>-aix-<arch>.bin -i console
```

where <arch> is one of ppc32 or `ppc64

Start the installer in console mode on HP-UX

Using an installation DVD:

```
install_hp -i console
```

Using a downloaded installer:

```
vb85-<release number>-hp-<arch>.bin -i console
```

where <arch> is either ia32 or ia64.

Using the installer



Ω Note

The installer writes to stdout and reads from stdin. This allows you to telnet from one system to another and run the installer remotely.

Follow the installer's onscreen instructions. For most options, defaults offered by the installer are acceptable.

- 1. **License agreement:** Read the licensing agreement carefully and enter Y to accept it to install and use VisiBroker.
- 2. **Choose Install Folder:** This creates a new installation of VisiBroker, or adds components to an existing installation. Either enter Y to accept the default /opt/MicroFocus/VisiBroker, or enter another location and enter Y to confirm. Ensure that the user name you are using has write access to the chosen folder.

Note

You cannot install this version of VisiBroker on top of previous releases. However, you can specify an existing location to add components.

3. **Choose Product Components:** Depending on the VisiBroker product you are installing, you can select from the following product components.

⊘ Note

The GUI components archive can be downloaded from the Rocket Customer Community. Among other benefits, this site provides access to product license keys and install kits, including the relevant GUI components.

The GUI components have been separated from the product as they do not fully comply with the Section 508 and WCAG accessibility requirements and guidelines. It is intended that future product releases will include updated GUI components that comply with the relevant accessibility guidelines.

By default, the components are all selected. You can choose to de-select any components which you do not need. For example, you could de- select the *Examples* option. The options are:

VisiBroker Core: The development tools and server components for VisiBroker for Java and C++.

Examples: Example applications for VisiBroker.

VisiBroker Services: Optional components that you can purchase for extended VisiBroker functionality. You can select the specific services you have purchased later in the installation procedure.

- 4. **Choose VisiBroker Services:** Select the services you have purchased. For example, enter 1,2 to select VisiNotify and VisiSecure:
 - a. VisiNotify: An industrial strength, ORB-level implementation of the OMG Event/Notification Service.

- b. VisiSecure: A framework for establishing secure connections between clients and servers.
- c. **VisiTransact:** A complete implementation of the OMG transaction management solution for transactions with CORBA applications over the Internet or intranets.
- 5. Choose Installation Type: Choose:
 - a. Typical: an express install using default settings, including:
 - **Smart Agent port:** Also known as the osagent. Client-side ORBs use this port to locate server objects before invoking their services. The default is 14000.
 - b. **Custom** to customize your installation. If you select this, you can: Set the Smart Agent port (osagent) to a value other than its default. Enter 1 or 2 as required.
- 6. Configuration Settings: If you selected a Custom installation, specify the osagent port you require.
- 7. Java Development Kit: Specify the path of the JDK to be used for this installation (see JDK).
- 8. **Pre-Installation Summary:** Review the displayed information before proceeding with the installation. Verify in particular the install folder location and the product features that you have specified. To confirm your choices and start installing, press **Enter**.
- 9. **Registration and Activation:** You must register and activate your license before you can start to use VisiBroker. Enter Y to register now, or N to do so at a later date. You are recommended to register now. To register later, see Registering the license in console mode after installation, or see Product Registration.)
- 10. License Administration Tool: A list of registration options appears.
- 11. If the machine on which you are installing has direct internet access, enter 0 for direct registration.

 If the machine does not have direct internet access, enter 1 for web registration. Note down the registration key displayed in the console.
- 12. The installer connects to the licensing server and prompts you to enter your serial number. Enter your 20-character license serial number.
- 13. Next the installer prompts Enter the key: . Enter your 6-character license authorization key.
- 14. The installer prompts:

Do you have a Borland Developer Network (BDN) account from a previous Borland product registration (Y)/(N)?

Type Y.

- 15. The installer prompts you for your Developer Network login name or your email address. Enter your developer network user name. See **A username and password**.
- 16. The screen displays Registering your information, followed by Registration completed successfully.
- 17. It then displays the license registration options previously seen in Step 10. Choose option |7| to save the license.

18. Choose option 2 to list the licenses to make sure the installation is registered correctly, then choose option 8 to quit the installer.



When VisiBroker is installed in NFS mounted directories, and if there is insufficient disk space for the system temp directory, the post installation cleanup process may not remove all the temporary files as the NFS server periodically locks files in the directories. To resolve this, you must manually clean the temporary directories and files after installation.

Registering the license in console mode after installation

If you select N when prompted to register your VisiBroker license during installation, you can register and activate the license in console mode later. To do so:

Open a UNIX console and log in using the same non-root user name that installed VisiBroker.

Go to the <install dir>/bin folder.

Set up the VisiBroker environment by running . . . / vbroker.sh.

Run lmadm -i console. A list of registration options appears.

5. If the machine has direct internet access, go to step 6.

If the machine does not have direct internet access, please proceed to step 13.

6. Enter 0 to select direct registration.

The utility connects to the license server and prompts you to enter your serial number. Enter your 20=character license serial number.

Next the installer prompts Enter the key:. Enter your 6-character license authorization key.

9. The installer prompts:

Do you have a Borland Developer Network (BDN) account from a previous Borland product registration (Y)/ (N)?

Type Y.

- 10. The installer prompts you for your Developer Network login name or your email address. Enter your developer network user name. See A username and password.
- 11. The screen displays Registering your information, followed by Registration completed successfully.
- 12. It then displays the license registration options previously seen in Step 4.

Choose option 7 to save the license.

- 13. If the machine does not have direct internet access, choose option 1 and note down the registration key displayed in the console.
- 14. You can then register the license as described in Email registration, Web page registration, or Telephone registration in the Product Registration section.

Installing VisiBroker Using Silent Installation

This section describes procedures for installing VisiBroker using silent installation for Windows, Solaris, Linux, IBM AIX and HP-UX).

What is Silent Installation?

Silent installation is recommended for use in medium to large scale deployments. It enables you to set installation configurations once, and then use that configuration for installing on multiple machines. Once the configuration file is set up the silent installation runs without user interaction.



Using silent installation implies your consent to the VisiBroker License Agreement.

Using Silent Installation

Ensure that you have the prerequisites described in System requirements).

⊘ Note

You cannot install this version of VisiBroker in the same location as a previous version. Either:

• Uninstall the previous version

or:

• Install the new version in a different location from any other existing versions

Before invoking the silent installation process, you must first create a text file that contains the properties for configuration settings, such as the install directory, server name, and JDK home. Each property must be listed on its own line, terminated by a carriage return, with no blank spaces at the end of each line and no blank lines at the end of the file. See Properties File for Silent Installation for more information.

After creating the text properties file, save it as cpropertiesfile>.txt, where cpropertiesfile> is the file name prefix for your properties file. Now you can invoke the silent installation process using the values specified in the properties file.

Silent Installation on Windows

All properties and values are case-sensitive. When specifying directory and file paths, always use a backward slash (χ).

To invoke the silent installation process on Windows:

- 1. Open a command prompt.
- 2. Download VisiBroker for Windows.

```
<installer_file>-f <path to properties file>
```

where <installer_file> is the name of the VisiBroker installer file and <path to properties file> is the full path of the propertiesfile> file.

For example:

```
vb85-<release number>-windows-<platform>-<arch>.exe -f c:/ silentproperties.txt
```

Ω Note

After silent installation is complete, you need to register and activate the license you received for your product. The license may be in the form of an email from Rocket Software listing one or more serial numbers and license keys, or it may be a license key file sent to you in an email from Rocket Software. For information on activating your new license, see Product Registration. You can register and activate your license by running the <code>lmadmw</code> executable in the <code><install_dir>\bin</code> directory.

Silent Installation on Solaris

All properties and values are case-sensitive. When specifying directory and file paths, always use a forward slash.

To invoke the silent installation process on Solaris:

- 1. Open a command line shell.
- 2. Go to the directory where you downloaded the installer and obtain all permissions, or chmod all, where 777 indicates all, to run the installer.
- 3. Invoke the silent installation process by entering the following command. Make sure to specify the full path name of the cpropertiesfile file:

```
<installer_file>-f <path to properties file>
```

where <installer_file> is the name of the VisiBroker installer and <path to properties file> is the full path of the cpropertiesfile> file.

For example:

```
vb85-<release number>-solaris-<platform>-<arch>.bin -f / usr/home/myname/silentproperties.txt
or:
```

vb85-<release number>-solaris-<platform>-<arch>.bin -f / opt/myname/silentproperties.txt

⊘ Note

After silent installation is complete, you need to register and activate the license you received for your product. The license may be in the form of an email from Rocket Software listing one or more serial numbers and license keys, or it may be a license key file sent to you in an email from Rocket Software. For information on activating your new license, see Product Registration. You can register and activate your license by running the Imadm executable in the <install_dir>/bin directory.

Silent Installation on Linux

All properties and values are case-sensitive. When specifying directory and file paths, always use a forward slash.

To invoke the silent installation process on Linux:

- 1. Open a UNIX shell.
- 2. Go to the directory where you downloaded the installer and obtain all permissions, or chmod all, where 777 indicates all, to run the installer.
- 3. Invoke the silent installation process by entering the following command. Make sure to specify the full path name of the cpropertiesfile file:

```
<installer_file> -f <path to properties file>
```

where <installer_file> is the name of the VisiBroker installer and <path to properties file> is the full path of the cpropertiesfile> file.

For example:

```
vb85-<release number>-linux-<platform>-<arch>.bin -f /usr/ home/myname/silentproperties.txt
or:
```

vb85-<release number>-linux-<platform>-<arch>.bin -f /opt/ myname/silentproperties.txt

⊘ Note

After silent installation is complete, you need to register and activate the license you received for your product. The license may be in the form of an email listing one or more serial numbers and license keys, or it may be a license key file sent to you in an email. For information on activating your new license, see Product Registration. You can register and activate your license by running the <code>lmadm</code> executable in the <code>kinstall_dir>/bin</code> directory.

Silent Installation on IBM AIX

All properties and values are case-sensitive. When specifying directory and file paths, always use a forward slash.

To invoke the silent installation process on IBM AIX:

- 1. Open a UNIX shell.
- 2. Go to the directory where you downloaded the installer and obtain all permissions, or chmod all, where 777 indicates all, to run the installer.

3. Invoke the silent installation process by entering the following command. Make sure to specify the full path name of the cpropertiesfile file:

```
<installer_file>-f <path to properties file>
```

where <installer_file> is the name of the VisiBroker installer and <path to properties file> is the full path of the cpropertiesfile> file.

Ensure you specify the full path name of the propertiesfile> file. For example:

vb85-<release number>-aix-<platform>-<arch>.bin -f /usr/ home/myname/silentproperties.txt

or:

vb85-<release number>-aix-<platform>-<arch>.bin -f /opt/ myname/silentproperties.txt

Ω Note

After silent installation is completed, you need to register and activate the license you received for your product. The license may be in the form of an email from Rocket Software listing one or more serial numbers and license keys, or it may be a license key file sent to you in an email from Rocket Software. For information on activating your new license, see Product Registration. You can register and activate your license by running the Imadm executable found in the <install_dir>/bin directory.

Silent Installation on HP-UX

All properties and values are case-sensitive. When specifying directory and file paths, always use a forward slash.

To invoke the silent installation process on HP-UX:

- 1. Open a UNIX shell.
- 2. Go to the directory where you downloaded the installer and obtain all permissions, or chmod all, where 777 indicates all, to run the installer.
- 3. Invoke the silent installation process by entering the following command. Make sure to specify the full path name of the propertiesfile file:

```
<installer_file>-f <path to properties file>
```

where <installer_file> is the name of the VisiBroker installer and <path to properties file> is the full path of the cpropertiesfile> file

Make sure to specify the full path name of the cpropertiesfile> file. For example:

```
vb85-<release number>-hp-<platform>-<arch>.bin -f /usr/ home/myname/silentproperties.txt
```

or:

vb85-<release number>-hp-<platform>-<arch>.bin -f /opt/ myname/silentproperties.txt

⊘ Note

After silent installation is completed, you need to register and activate the license you received for your product. The license may be in the form of an email from Rocket Software listing one or more serial numbers and license keys, or it may be a license key file sent to you in an email from Rocket Software. For information on activating your new license, see Product Registration. You can register and activate your license by running the <code>lmadm</code> executable in the <code>sinstall_dir>/bin</code> directory.

Properties File for Silent Installation

This properties file applies to silent installation of VisiBroker. It is a plain text file, with each property listed on its own line, terminated by a carriage return, with no blank spaces at the end of each line and no blank lines at the end of the file. Properties can appear in any order in the file.

Variable	Value
INSTALLER_UI	silent (required). The mode of installation.
USER_INSTALL_ DIR	<pre><install_dir> (required). The full path name for the VisiBroker product directory of your choice For Windows, the default installation directory is C:/MicroFocus/ For all UNIX systems, the default installation directory is /opt/ MicroFocus/.</install_dir></pre>
INSTALL_TYPE	The following type is required: - VisiBroker Installs VisiBroker.
USER_SHORTCU TS	Windows (optional)—The full path name for the product shortcuts directory. For Windows, the default for VisiBroker is/Start Menu/ Programs/VisiBroker UNIX (required)—The required value for UNIX is /dev/null.
JVM_JDK_HOME	(optional) Sets the JDK path for VisiBroker components that host user application code.
OSAGENT_PORT	(optional). Default is 14000.
INSTALL_VISI CORE	(optional). Installs the VisiBroker for Java and C++ development tools and server components. Default is YES.

Variable	Value
INSTALL_EXAM PLES	(optional). Installs the example applications for VisiBroker. Default is YES .
VISI_SERVICES	<pre>(optional) When INSTALL_TYPE is VisiBroker , installs any optional VisiBroker Services you purchased. The value is a comma-delimited list that contains one or more of the following entries: - VisiNotify - VisiSecure - VisiTransact For example, if you purchased VisiBroker with VisiNotify and VisiTransact, include the following line in your silent installation <pre>properties></pre> file to install those additional services: VISI_SERVICES=VisiNotify, VisiTransact</pre>
CONFIGURATIO N_ SETUP	(optional). Installs the VisiBroker example configuration. Default is YES .
VBROKER_SETUP (optional).	Windows only. If you select YES, the system variable BES_LIC_DIR is set to <install_dir>/var and BES_LIC_DEFAULT_DIR is set to <in stall_dir="">/license. The default is NO.</in></install_dir>

Sample Silent Installation Properties for Windows

This example installs VisiBroker on non-default agent ports, and sets VisiBroker system variables:

INSTALLER_UI=silent

USER_INSTALL_DIR=C:/MicroFocus

OSAGENT_PORT=14925

INSTALL_TYPE=VisiBroker

VBROKER_SETUP=YES

Sample Silent Installation Properties for Solaris

This example installs VisiBroker on non-default agent ports, and installs several VisiBroker Services:

INSTALLER_UI=silent
USER_INSTALL_DIR=/opt/MicroFocus USER_SHORTCUTS=/dev/null
OSAGENT_PORT=14925
INSTALL_TYPE=VisiBroker
VISI_SERVICES=VisiNotify, VisiSecure, VisiTransact

Sample Silent Installation Properties for Linux

This example installs VisiBroker Edition on non-default management and agent ports, and installs several VisiBroker Extended Services:

INSTALLER_UI=silent
USER_INSTALL_DIR=/opt/MicroFocus
USER_SHORTCUTS=/dev/null
OSAGENT_PORT=14925
INSTALL_TYPE=VisiBroker VISI_SERVICES=VisiNotify, VisiSecure, VisiTransact

Sample Silent Installation Properties for IBM AIX

This example installs VisiBroker Edition on non-default management and agent ports, and installs several VisiBroker Extended Services:

INSTALLER_UI=silent
USER_INSTALL_DIR=/opt/MicroFocus
USER_SHORTCUTS=/dev/null OSAGENT_PORT=14925
INSTALL_TYPE=VisiBroker
VISI_SERVICES=VisiNotify, VisiSecure, VisiTransact

Sample Silent Installation Properties for HP-UX

This example installs VisiBroker Edition on non-default management and agent ports, and installs several VisiBroker Extended Services:

INSTALLER_UI=silent

USER_INSTALL_DIR=/opt/MicroFocus

USER_SHORTCUTS=/dev/null

OSAGENT_PORT=14925

INSTALL_TYPE=VisiBroker

Product Registration

Before using VisiBroker, you need to register and activate the license you received for your product. The license may be in the form of an email from Rocket Software listing one or more serial numbers and license keys, or it may be a license key file sent to you in an email from Rocket Software.

If you have a valid license for an earlier versions of VisiBroker installed on the same machine as the newly-installed VisiBroker software, use the Imadm command-line tool to migrate your previous license for use with the newly-installed VisiBroker software. For information about VisiBroker licenses, see Licensing.

If you have already received a key file in an email from Rocket Software for a product you purchased online or downloaded for evaluation, or if you downloaded a free version of the product, you can use the registration wizard to apply the key file, or you can copy it to the <install_dir>\ license directory and it will be applied automatically when you restart your product.

Registration methods

If you have a serial number and key, you can register and activate your VisiBroker product using one of the following registration methods:

- Direct. If your system is connected to the Internet, this is the simplest method.
 - If you were presented with the option Do you want to register and activate VisiBroker now? during the installation process and answered Yes, the Product Registration Wizard launches automatically. Otherwise you can launch the Wizard after installation:
- 1. Go to <install_root>/bin directory.
- 2. Launch lmadm from the /bin directory and complete the license registration process. The Wizard appears.
- Email. You send your registration request via your own email account (from any system), and will receive an activation file via email that you can apply to your installation. For more information, see Email registration.
- **Web page**. Similar to email, except you register by visiting the Rocket Software web site. For more information, see Web page registration.
- **Telephone**. You provide information to a Rocket Software representative, who will send you an activation file by email or mail. For more information, see Telephone registration.

Depending on which method you choose, you may be asked to indicate whether you have a Developer Network (BDN) account. See Licensing. If you do not have an account, you will be prompted to create one in the Product Registration Wizard.

If you do not choose the Direct registration method, you will receive an activation file. Simply copy this file into the <install_dir>\license directory and it will be applied automatically when you start your product.

Alternatively, you can start the wizard at another time by running <code>lmadm.exe</code> from the VisiBroker installation folder.

Direct registration

The most straightforward method of registering VisiBroker is to enter the serial number and license key and choose direct registration, as described in this section. See the *Registering your License* sections in the various platform-specific installation chapters.

Email registration

- 1. At the Select Registration Method screen, choose **Email**.
- 2. Indicate whether you have an account, and click **Next**. If you do not have an account, you are prompted to create one.
- 3. Review the Information Summary and click **Next**.
- 4. Copy the content of the Email Registration content pane into an email message addressed to support@rocketsoftware.com. You can send your registration request via your own email account from any system. Include in the email:
 - a. The information in the Information Summary window.
 - b. The information in the Email Registration window.
 - c. The registration key, which you can retrieve by choosing the Web page option.
 - d. Your support contract serial number.
- 5. Click **Next** and **Finish** to close the wizard.
- 6. You will receive an activation key file by email. Copy the activation key file to the <install_dir>\license directory and it will be applied automatically when you restart VisiBroker.

Web page registration

For the latest information on web registration, email support@rocketsoftware.com.

Telephone registration

- 1. At the Select Registration Method screen, choose **Telephone** and click **Next**.
- 2. Select the appropriate region's telephone number from the information at www.rocketsoftware.com/support, and call the number for telephone assistance.
- 3. Click **Next** and **Finish** to close the wizard.
- 4. You will receive a product activation file. Copy the activation key file to the <install_dir>\license directory and it will be applied automatically when you restart VisiBroker.

To register and activate a license after installation

To register and activate your license after you have installed VisiBroker:

- 1. Go to /bin directory.
- 2. Launch lmadm from the /bin directory and complete the license registration process.
- 3. The Wizard appears and presents the following panels:
 - a. Product Registration Wizard: Select Have Serial Number.
 - b. **Serial Number:** Enter the 20-character serial number and the 6- character license key supplied with your installation into the respective fields.
 - c. Select Registration Method: Choose Direct.
 - d. Account Information: This is specified as a prerequisite for installing VisiBroker. See the section A username and password for information. Choose I have an account. If you have not yet set up a developer network account, select I do not have an account. The wizard prompts you for the information to create an account.
 - e. Account Information: Enter your developer network account information.
 - f. **Proxy settings:** If you have any proxies configured, check **I use a proxy** and enter your proxy information. If you do not use proxies, click **Next**.
 - g. **Information Summary:** Check the information you have entered and, if it is correct, click **Next**. Click **Back** if you want to change anything.
 - h. **Direct Registration:** This dialog box shows how your registration is progressing. When registration is complete, the **Done** button is enabled. Click **Done**.

Registering an evaluation copy of VisiBroker

If you are installing an evaluation or free version of VisiBroker, copy the license activation key file you receive by email frm Rocket Software to the <install_dir>/license directory. If you did not receive a license activation key file, or if you are reinstalling the software, contact www.rocketsoftware.com/support.

Verifying installation and registration

To verify that you have installed and registered VisiBroker correctly:

1. Open a windows command prompt and go to the <VBROKERDIR>\bin folder.

The default value for <VBROKERDIR> is C:\MicroFocus\VisiBroker.

- 2. Setup the VisiBroker environment by running vbroker.bat.
- 3. Go to the sample folder <vbroker\basic\bank_agent to compile and run the server
 to verify if the installation has been installed properly.</pre>
- 4. Compile the example using the supported compiler for the operating system where you are installing VisiBroker. For the compilers supported by this release of VisiBroker, see www.rocketsoftware.com/support.
- 5. Assuming the nmake command is in the PATH, enter nmake -f Makefile_cpp for a C++ example and vbmake.bat for a Java example.
- 6. Once the compilation is successful, run osagent from the same folder. This is a lookup service from where clients will receive the server's IOR.
- 7. Start the server as follows:

For VisiBroker for C++:
server.exe

For VisiBroker for Java:

`vbj Server

8. The server starts and displays the object reference which is hosted by this server.

Cleaning up and re-registering a license

You can clean up and re-register an existing VisiBroker installation if there is a license issue.



Before cleaning up and re-registration, contact www.rocketsoftware.com/support if you need to increase the registration count for your license. A valid reason is necessary to increase the registration count. For example, if you are just planning to re-install the product in a different location in the same machine, the license count will not be increased. For re-hosting the license, contact Rocket Software support.

Cleanup instructions

1. In the problematic VisiBroker installation, remove the following files and folders from the <install_dir>/var folder:

```
borland.lic
borland.pkg
mf_license.dat and mf_licensej.dat (if present)
```

the hidden files and folders under the var folder, for example var\.bpy-tjacqr

If you do not see the hidden files and folders, then:

In Windows, enable viewing hidden files by using Folder Options.

In UNIX, use the 1s -1a command to list the hidden files and folders.

- 2. Remove the reg*.txt or hidden *.slip from the <install_dir>/ license folder.
- 3. Open a UNIX console or Windows command prompt.

On a UNIX operating system, log in using the same non-root user who installed VisiBroker.

- 4. Go to the <install_dir>/bin folder.
- 5. Set up the VisiBroker environment by running . ./vbroker.sh for a UNIX system, or vbroker.bat for Windows.
- 6. Run lmadm -i console.

Select option 2 to list all licenses. You should not see any license listed. This step makes sure that you have cleaned up the license successfully.

Re-registration of VisiBroker license

You can re-register the VisiBroker license by any of the same methods that you use to register a new license. See Registration methods.

Notices

Copyright

© 1996-2025 Rocket Software, Inc. or its affiliates. All Rights Reserved.

Trademarks

Rocket is a registered trademark of Rocket Software, Inc. For a list of Rocket registered trademarks go to: www.rocketsoftware.com/about/legal. All other products or services mentioned in this document may be covered by the trademarks, service marks, or product names of their respective owners.

Examples

This information might contain examples of data and reports. The examples include the names of individuals, companies, brands, and products. All of these names are fictitious and any similarity to the names and addresses used by an actual business enterprise is entirely coincidental.

License agreement

This software and the associated documentation are proprietary and confidentical to Rocket Software, Inc. or its affiliates, are furnished under license, and may be used and copied only in accordance with the terms of such license.

Note: This product may contain encryption technology. Many countries prohibit or restrict the use, import, or export of encryption technologies, and current use, import, and export regulations should be followed when exporting this product.

Corporate information

Rocket Software, Inc. develops enterprise infrastructure products in four key areas: storage, networks, and compliance; database servers and tools; business information and analytics; and application development, integration, and modernization.

Website: www.rocketsoftware.com

Contacting Technical Support

The Rocket Community is the primary method of obtaining support. If you have current support and maintenance agreements with Rocket Software, you can access the Rocket Community and report a problem, download an update, or read answers to FAQs. To log in to the Rocket Community or to request a Rocket Community account, go to www.rocketsoftware.com/support. In addition to using the Rocket Community to obtain support, you can use one of the telephone numbers that are listed above or send an email to support@rocketsoftware.com.

Rocket Global Headquarters 77 4th Avenue, Suite 100 Waltham, MA 02451-1468 USA

Country and Toll-free telephone number

To contact Rocket Software by telephone for any reason, including obtaining pre-sales information and technical support, use one of the following telephone numbers.

- United States: 1-855-577-4323

- Australia: 1-800-823-405
- Belgium: 0800-266-65
- Canada: 1-855-577-4323
- China: 400-120-9242
- France: 08-05-08-05-62
- Germany: 0800-180-0882

- Italy: 800-878-295 - Japan: 0800-170-5464

Netherlands: 0-800-022-2961New Zealand: 0800-003210South Africa: 0-800-980-818

- United Kingdom: 0800-520-0439